



STABAXOL I

MSDS Number

BXPXQ

National Stock Number

6850-00D003597

Product Name

STABAXOL I

Manufacturer

RHEIN CHEMIE CORP

Product Identification

Product ID: STABAXOL I
MSDS Date: 05/02/1994
FSC: 6850
NIIN: 00D003597
MSDS Number: BXPXQ

Responsible Party

RHEIN CHEMIE CORP
1008 WHITEHEAD RD EXT
TRENTON , NJ 08638
US
Emergency Phone: 609-771-3516

Info Phone: 609-771-3516

Preparer: PATRICIA A. ALLEY

Cage: RHEIN

Contractor

RHEIN CHEMIE CORP
TRENTON, NJ 08638
US
609-771-9100
Cage: RHEIN

Ingredients

2,2,6,6'-TETRAISOPROPYLDIPHENYL CARBODIIMIDE
CAS: 2162-74-5

2,6-DIISOPROPYLPHENYLISOCYANATE (DIPI)

CAS: 28178-42-9

RTECS: CY8545000

Fraction By Weight:

Hazards

LD50 LC50 Mixture: ORAL LD50 (RAT) IS 2395 MG/KG
Routes of Entry: Inhalation: YES Skin: YES Ingestion: NO
Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO
Health Hazards Acute and Chronic: ACUTE: VAPORS & LIQUIDS GENERATED DURING HEATING MAY CAUSE RESPIRATORY IRRITATION IF INHALED-MAY CAUSE ALLERGIC RESPIRATORY ATTACK (ASTHMA); IRRITATION OF SKIN & EYES



ON CONTACT.CHRONIC:PROLONGED/REPEATED EXPOSURE MAY CAUSE RESPIRATORY SENSITIZATION/ASTHMA.MAY CAUSE SKIN SENSITIZATION/CONJUNCTIVITIS.

Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.

Effects of Overexposure:INHALED- RUNNY NOSE,SORE THROAT,COUGHING,CHEST DISCOMFORT, SHORTNESS OF BREATH,REDUCED LUNG FUNCTION,BRONCHITIS,FLU-LIKE SYMPTOMS. SKIN-REDDENING, SWELLING, RASH, SCALING OR BLISTERING. EYES-PAIN, RED DENING, TEARING, SWELLING.

Medical Cond Aggravated by Exposure:ASTHMA, OTHER RESPIRATORY DISORDERS, SKIN ALLERGIES, ECZEMA.

First Aid

First Aid:EYES-FLUSH WITH LOTS OF WATER FOR 15 MINUTES, HOLD LIDS OPEN. SEE DOCTOR. SKIN-REMOVE CONTAMINATED CLOTHES. WASH WITH SOAP & WATER. SEE DOCTOR IF SYMPTOMS DEVELOP. INHALED-REMOVE TO FRESH AIR. GIVE OX YGEN OR ARTIFICIAL RESPIRATION AS NEEDED. GET IMMEDIATE MEDICAL ATTENTION. INGESTED-DO NOT INDUCE VOMITING! IF CONSCIOUS, GIVE 250 ML OG MILK OR WATER TO DRINK. GET IMMEDIATE MEDICAL ATTENTION.

Fire Fighting

Flash Point Method:PMCC

Flash Point:365F,185C

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL, CHEMICAL FOAM.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. COOL FIRE EXPOSED CONTAINERS WITH WATER.

Unusual Fire/Explosion Hazard:DURING A FIRE, CARBODIIMIDE VAPORS AND OTHER IRRITATING, HIGHLY TOXIC GASES SUCH AS DIISOPROPYLPHENYL DIISOCYANTE MAY BE GENERATED.

Accidental Release

Spill Release Procedures:IF MOLTEN, LET SOLIDIFY. MECHANICALLY SWEEP UP SPILLED MATERIAL AND PLACE IN A PROPERLY MARKED CONTAINER. COVER LIQUID SPILL WITH SAWDUST, VERMICULITE OR SIMILAR MATERIAL. POUR DECONTAMINATION SOLUTIO N ON SPILL AND ALLOW TO REACT FOR 10 MINUTES.

Neutralizing Agent:UNION CARBIDES TERGITOL TMN-10 (20%) AND WATER (80%).

Handling

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE AT A TEMPERATURE BETWEEN 40F AND 120F. KEEP CONTAINER CLOSED WEHN NOT IN USE. RESEAL UNDER NITROGEN BLANKET.

Other Precautions:DO NOT RESEAL IF CONTAMINATION SUSPECTED. AVOID CONTACT WITH SKIN & EYES. PRODUCT IS LIGHT AND AIR SENSITIVE.

Exposure Controls

Respiratory Protection:IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE OR AN EMERGENCY OCCURS; WEAR AN MSHA/NIOSH APPROVED RESPIRATOR OR AN AIR-SUPPLIED RESPIRATOR OR SCBA, AS REQUIRED. USE IN ACCORDANCE WITH 29 CFR 1910.13 4 AND MANUFACTURER'S RECOMMENDATIONS.

Ventilation:USE ADEQUATE MECHANICAL VENTILATION OR LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:BUTYL, NITRILE, PVA.

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES.

Other Protective Equipment:EYE WASH STATION & SAFETY SHOWER. EMPLOYEE TRAINING ON PROPER HANDLING PROCEDURES IS HIGHLY RECOMMENDED.

Work Hygienic Practices:WASH HANDS AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

RCRA WASTE: NO.

Chemical Properties

HCC:T6



Boiling Pt: B.P. Text: 410F, 210C
Melt/Freeze Pt: M.P/F.P Text: 104F, 40C
Vapor Pres: 6 MBAR
Spec Gravity: 0.94
Solubility in Water: NEGLIGIBLE
Appearance and Odor: WHITE TO PALE YELLOW, WAXY SOLID; SLIGHT AROMATIC ODOR.
Percent Volatiles by Volume: NIL

Stability

Stability Indicator/Materials to Avoid: YES
WATER, AMINES, STRONG BASES, ALCOHOLS.
Stability Condition to Avoid: AVOID CREATING DUST; POSSIBLE DUST EXPLOSION HAZARD. KEEP AWAY FROM INCOMPATIBLE MATERIALS.
Hazardous Decomposition Products: THERMAL DECOMPOSITION-CARBON MONOXIDE & CARBON DIOXIDE, NITROGEN OXIDES, HCW & MONOISOCYANATES, ANILINE DERIVATIVES.....
Conditions to Avoid Polymerization: WILL NOT OCCUR.

Disposal

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL ENVIRONMENTAL REGULATIONS. INCINERATION IS PREFERRED METHOD. HANDLE EMPTY CONTAINERS AS IF FULL DUE TO RESIDUE; DECONTAMINATE PRIOR TO DISPOSAL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.