

# CYCOM 907 LAMINATING DISPERSION, 1937-01

#### **MSDS Number**

**BBQGX** 

#### **National Stock Number**

8030-00F004443

#### **Product Name**

CYCOM 907 LAMINATING DISPERSION, 1937-01

#### Manufacturer

AMERICAN CYANAMID

### **Product Identification**

Product ID:CYCOM 907 LAMINATING DISPERSION, 1937-01 MSDS Date: 01/01/1987 FSC:8030 NIIN:00F004443

MSDS Number: BBQGX

## **Responsible Party**

AMERICAN CYANAMID/WAYNE, NJ 07470

Emergency Phone: (201) 835-3100

Cage: 70361 Contractor

AMERICAN CYANAMID CO

CLIFTON, NJ 07015

US

973-683-2000 Cage: 70361

#### **Ingredients**

ETHYLENE DICHLORIDE (SARA III)

CAS: 107-06-2 RTECS: KI0525000

Fraction By Weight: 50% OSHA PEL50 PPM/C,100PPM ACGIH TLV: 10 PPM; 9293 EPA Report Quantity: 100 LBS DOT Report Quantity: 100 LBS

#### Hazards

Effects of Overexposure: OVEREXPOSURE TO VAPOR DURING HEAT CURING MAY CAUSE IRRITATION OF THE RESP TRACT/EYE IRRITATION.

#### First Aid

First Aid: EYES/SKIN: FLUSH WITH WATER FOR 15 MINUTES. REMOVE CONTAMINATED CLOTHING/SHOES. DON'T REUSE CONTAMINATED CLOTHING WITHOUT LAUNDERING. EYE: IRRIGATE WITH WATER FOR 15 MINUTES. OBTAIN MEDICAL ATTENTION IF IRRITATION PERSISTS.

# Fire Fighting

Flash Point:72F (CC)

Extinguishing Media: WATER SPRAY, ALCOHOL FOAM, CO2, DRY CHEMICAL



Fire Fighting Procedures: WATER COOL CONTAINERS. WEAR SCBA/FULL PROTECTIVE CLOTHING.

#### **Accidental Release**

Spill Release Procedures: COVER SPILLS WITH SOME INERT ABSORBENT MATERIAL; SWEEP UP AND PLACE IN A WASTE DISPOL CONTAINER. FLUSH AREA WITH WATER. REMOVE SOURCES OF IGNITION. WEAR NIO POSITIVE PRESSURE RESP.

## Handling

Handling and Storage Precautions: AREAS CONTAINING THIS MATERIAL SHOULD HAVE FIRE-SAFE PRACTICES/ELECTRICAL EQUIPMENT IN ACCORDAE WITH ELECTRICAL AND PROTECTION CODES.

Other Precautions: VAPOR PRESSURE OF ORGANIC LIQUIDS INCREASES WITH TEMPERATURE. STORE AWAY FROM SOURCES OF HEAT. BEFORE EATING, DRINKING & SMONG WASH FACE AND HANDS WITH SOAP AND WATER.

## **Exposure Controls**

Respiratory Protection: WEAR NIOSH FULL FACEPIECE IF >TLV.

Ventilation: PROVIDE LOCAL EXHAUST VENTILATION TO KEEP BELOW TLV.

Protective Gloves:IMPERVIOUS Eye Protection:CHEMICAL GOGGLES

Other Protective Equipment: PROVIDE EYEWASH FOUNTAIN/SAFETY

SHOWER/BARRIER CREAM. Supplemental Safety and Health MSDS DATE: 20 MAR 86.

## **Chemical Properties**

Vapor Pres:62 Spec Gravity:1.1 Solubility in Water:NONE

Appearance and Odor: WATER WHITE/TURBIDE LIQ/ETHYLENE DICHLORIDE ODOR

Percent Volatiles by Volume:50%

## **Stability**

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS, STRONG BASES, STRONG ACIDS Stability Condition to Avoid:STORE AT OR BELOW 0 F TO PROLONG SHELF LIFE.

Hazardous Decomposition Products: COMBUSTION MAY PRODUCE CO AND CO2.

#### **Disposal**

Waste Disposal Methods: DISPOSAL MUST BE MADE IN ACCORDANCE WITH APPLICABLE GOVERNMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.