

## **"EPA 2000" WCI-140 CM**

### **MSDS Number**

BWLJX

### **National Stock Number**

6850-01-359-9218

### **Product Name**

"EPA 2000" WCI-140 CM

### **Manufacturer**

WESTERN CHEMICAL INTL INC

### **Product Identification**

Product ID:"EPA 2000" WCI-140 CM

MSDS Date:09/08/1993

FSC:6850

NIIN:01-359-9218

MSDS Number: BWLJX

### **Responsible Party**

WESTERN CHEMICAL INTL INC

2939 N 6TH PL

SCOTTSDALE , AZ 85251-6001

US

Emergency Phone: 602-990-9487

Info Phone: 602-990-9487

Preparer: MATT MICHAELS

Cage: 3T389

### **Contractor**

WESTERN CHEMICAL INTERNATIONAL INC.

SCOTTSDALE, AZ 85251

US

480-990-9487

Cage: 3T389

### **Ingredients**

HYDROTREATED LIGHT PETROLEUM DISTILLATE

CAS: 64742-47-8

OSHA PEL100 PPM

ACGIH TLV: 100 PPM

PETROLEUM DISTILLATE

CAS: 68551-16-6

### **Hazards**

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PRODUCT HAS LOW VAPOR PRESSURE AND SHOULD NOT PRESENT A HAZARD UNDER NORMAL WORKING CONDITIONS.

Explanation of Carcinogenicity:NOT CARCINOGENIC.

Effects of Overexposure:PRODUCT CONSIDERED SAFE UNDER NORMAL USAGE.

OVEREXPOSURE, HOWEVER, MAY RESULT IN THE FOLLOWING:

INHALATION-DIZZINESS, SKIN/EYES-IRRITATION,  
INGESTION-GASTROINTESTINAL IRRITATION.

Medical Cond Aggravated by Exposure:NONE KNOWN.

## First Aid

First Aid:INHALATION-REMOVE TO FRESH AIR; SKIN-WASH WITH SOAP AND WATER; EYES-FLUSH WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION; INGESTION-DO NOT INDUCE VOMITING, GET MEDICAL ATTENTION.

## Fire Fighting

Flash Point Method:TCC

Flash Point:145F,63C

Lower Limits:1.0

Upper Limits:7

Extinguishing Media:CARBON DIOXIDE, DRY POWDER, FOAM, WATER SPRAY.

Fire Fighting Procedures:CLASS B PROCEDURES.

Unusual Fire/Explosion Hazard:KEEP AWAY FROM SPARKS & OPEN FLAMES. DO NOT USE WELDING TORCH ON OR NEAR DRUM.

## Accidental Release

Spill Release Procedures:ALLOW SMALL SPILLS TO EVAPORATE. LARGER SPILLS SHOULD BE COLLECTED AND DISPOSED OF PROPERLY IN ACCORDANCE WITH REGULATIONS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

## Handling

Handling and Storage Precautions:STORE IN COOL, DRY AREA, AWAY FROM HEAT. KEEP CONTAINER TIGHTLY CLOSED WHEN PRODUCT IS NOT BEING USED.

Other Precautions:NONE

## Exposure Controls

Respiratory Protection:NOT REQUIRED IF TLV KEPT BELOW PPM.

Ventilation:LOCAL EXHAUST: ADEQUATE. MECHANICAL (GENERAL): ADEQUATE.

Protective Gloves:NITRILE/PVC GLOVES.

Eye Protection:GOGGLES OR SAFETY GLASSES.

Other Protective Equipment:NONE REQUIRED.

Work Hygienic Practices:KEEP EYE WASH IN VICINITY. WASH WITH SOAP & WATER BEFORE HANDLING FOOD.

Supplemental Safety and Health

NONE

## Chemical Properties

HCC:V4

Boiling Pt:B.P. Text:320-390F

Vapor Pres:2

Vapor Density:5

Spec Gravity:0.75

Evaporation Rate & Reference:Solubility in Water:NEGLIGIBLE

Appearance and Odor:NON VISCOUS LIQUID-CLEAR COLOR. MILD ODOR.

## Stability

Stability Indicator/Materials to Avoid:YES

OXIDIZING AGENTS.

Stability Condition to Avoid:OPEN FLAMES, WELDING ARCS, OR OTHER HIGH TEMPERATURE SOURCES.

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE.

## Disposal

Waste Disposal Methods:EPA 2000 HAS A HIGH BTU VALUE. WASTE PRODUCT CAN, THEREFORE, BE MIXED WITH NORMAL WASTE OIL FOR BURNING AS INDUSTRIAL FUEL. IT CAN ALSO BE RECYCLED OR RECLAIMED.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.