

## **90549 WIRE PULL LUBE**

### **MSDS Number**

CCFNS

### **National Stock Number**

9150-00F051699

### **Product Name**

90549 WIRE PULL LUBE

### **Manufacturer**

PREMIER INDUSTRIAL CORP

### **Product Identification**

Product ID:90549 WIRE PULL LUBE

MSDS Date:08/18/1994

FSC:9150

NIIN:00F051699

MSDS Number: CCFNS

### **Responsible Party**

PREMIER INDUSTRIAL CORPORATION

4500 EUCLID AVE

CLEVELAND , OH 44103-3736

US

Emergency Phone: 216-391-8300

Info Phone: 216-391-8300

Cage: 18399

### **Contractor**

PREMIER FARNELL CORPORATION

CLEVELAND, OH 44103-3736

US

216-391-8300

Cage: 18399

### **Ingredients**

ISOPROPANOL (ISOPROPYL ALCOHOL), 2-PROPANOL, DIMETHYL

CAS: 67-63-0

RTECS: NT8050000

Fraction By Weight: 5-10%

OSHA PEL400 PPM

ACGIH TLV: 400 PPM

1,2-PROPANEDIOL (PROPYLENE GLYCOL)

CAS: 57-55-6

RTECS: TY2000000

Fraction By Weight: 1-5%

WATER

CAS: 7732-18-5

RTECS: ZC0110000

Fraction By Weight: 60-90%

HYDROXYETHYL CELLULOSE, 2-HYDROXYETHYL ETHER CELLULOSE,

CAS: 9004-62-0

RTECS: FJ5958000

Fraction By Weight: 1-5%

OSHA PEL5 PPM

ACGIH TLV: 10 PPM

0.86 LBS/GAL; 0.10 GM/L

RTECS: 9999999VO

## Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYES/SKIN: IRRITATION. INHALATION: MAY  
BE HARMFUL TO RESPIRATORY SYSTEM.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:IRRITATION, DIZZINESS, GIDDINESS, NAUSEA,  
CRAMPS, VOMITING, DIARRHEA.

## First Aid

First Aid:EYES: FLUSH W/PLENTY OF WATER FOR 15 MINS. SKIN: WASH  
THOROUGHLY W/PLENTY OF WATER & SOAP. INHALATION: REMOVE TO FRESH  
AIR, GIVE OXYGEN IF NEEDED. INGESTION: INDUCE VOMITING. OBTAIN  
MEDICAL ATTENTION IN ALL CASES.

## Fire Fighting

Lower Limits:2  
Upper Limits:12.7  
Extinguishing Media:WATER, FOG, FOAM, DRY CHEMICAL, CO2.  
Fire Fighting Procedures:WEAR SCBA & EQUIPMENT.  
Unusual Fire/Explosion Hazard:IF USED IN CONFINED SPACES, HAZARDOUS  
VAPORS MAY SPREAD, BURN/BUILD UP IN LOW AREAS. AUTOIGNITION TEMP:  
750F.

## Accidental Release

Spill Release Procedures:REMOVE SOURCES OF IGNITION. VENTILATE THE  
AREA. CLEAN UP W/ABSORBENT MATERIAL. CONTAIN & PICKUP WASTE  
MATERIALS. PUT IN A SEALED APPROVED CONTAINER.

## Handling

Handling and Storage Precautions:KEEP AWAY FROM HEAT & FLAME.  
INDUSTRIAL USE ONLY. USE ONLY IN WELL VENTILATED AREAS.  
Other Precautions:AVOID PROLONGED BREATHING OF VAPOR/SPRAY MIST. AVOID  
PROLONGED/REPEATED CONTACT W/SKIN. KEEP OUT OF REACH OF CHILDREN.  
ALWAYS READ & FOLLOW DIRECTIONS ON PRODUCT LABEL.

## Exposure Controls

Respiratory Protection:IF VENTILATION IS INADEQUATE, WEAR APPROVED  
RESPIRATORY EQUIPMENT.  
Ventilation:LOCAL EXHAUST/MECHANICAL (GENERAL): REQUIRED.  
Protective Gloves:SOLVENT RESISTANT  
Eye Protection:SAFETY GLASSES  
Work Hygienic Practices:WASH THOROUGHLY AFTER USING.  
Supplemental Safety and Health

---

## Chemical Properties

Boiling Pt:B.P. Text:176F  
Melt/Freeze Pt:M.P/F.P Text:10F  
Vapor Pres:33  
Vapor Density:0.6  
Spec Gravity:0.9915  
pH:8  
Evaporation Rate & Reference:(WATER = 1): 1  
Solubility in Water:98%  
Appearance and Odor:LIGHT GREEN VISCOUS LIQUID  
Percent Volatiles by Volume:98

## Stability

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZERS.  
Stability Condition to Avoid:HEAT, SPARKS, FLAMES/SOURCES OF IGNITION.

## Disposal

Waste Disposal Methods:DISPOSE OF IAW/FEDERAL, STATE & LOCAL  
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.