

WOOD FLOOR FINISH (BOTH COLORS)

MSDS Number

CDQWL

National Stock Number

9150-00F052977

Product Name

WOOD FLOOR FINISH (BOTH COLORS)

Manufacturer

WATCO DENNIS CORP

Product Identification

Product ID:WOOD FLOOR FINISH (BOTH COLORS)

MSDS Date:09/01/1987

FSC:9150

NIIN:00F052977

MSDS Number: CDQWL

Responsible Party

WATCO-DENNIS CORP

19610 RANCHO WAY

RANCHO DOMINGUEZ , CA 90220-5000

US

Emergency Phone: OUT OF BUSINESS

Info Phone: OUT OF BUSINESS

Cage: 51611

Contractor

WATCO-DENNIS CORP/SANTA MONICA, CA 90404

Cage: 51611

Ingredients

KEROSENE (PETROLEUM), (C10-C15 SATURATED HYDROCARBONS 97%,

CAS: 64742-47-8

RTECS: OA5504000

Fraction By Weight: 31-34%

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN: MAY BE ABSORBED & CAUSE

IRRITATION. EYES: IRRITATING & BLURRED VISION. INGESTION:

GASTROINTESTINAL IRRITATION.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:IRRITATION, REDNESS, BLURRED VISION, DIZZINESS,

LIGHTHEADEDNESS, HEADACHE, NAUSEA, VOMITING, FATIGUE, SLEEP

DISTURBANCES, DIFFICULTIES IN CONCENTRATION & MEMORY

First Aid

First Aid:SKIN: WASH W/SOAP & WATER. EYES: FLUSH W/WATER FOR 15 MINS.

INHALATION: REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NECESSARY.

INGESTION: DON'T INDUCE VOMITING. GIVE 4 CUPS OF WATER/OTHER

LIQUIDS. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method:TCC
Flash Point:104F
Lower Limits:1
Upper Limits:6.7
Extinguishing Media:CO2, DRY CHEMICAL, FOAM, WATER SPRAY
Fire Fighting Procedures:DON'T ENTER ANY ENCLOSED/CONFINED SPACE W/O PROTECTIVE EQUIPMENT.
Unusual Fire/Explosion Hazard:WATERSOAK OILY CLOTHES AFTER USE TO AVOID SPONTANEOUS COMBUSTION.

Accidental Release

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. CLEAN UP AS SOON AS POSSIBLE W/ABSORBENT CLAY, DIATOMACEOUS EARTH/OTHER SUITABLE MATERIAL. IF USING CLOTHS, WATER SOAK BEFORE DISPOSAL.

Handling

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE & AWAY FROM HEAT/OPEN FLAME. DON'T STORE INSIDE THE HOME. KEEP AWAY FROM CHILDREN.

Other Precautions:USE ONLY IN WELL VENTILATED AREAS. WATER SOAK OILY CLOTHS AFTER USE TO AVOID SPONTANEOUS COMBUSTION & PLACE CLOTHS OUTSIDE OF BUILDINGS & AWAY FROM COMBUSTIBLE MATERIALS.

Exposure Controls

Respiratory Protection:APPROVED RESPIRATOR FOR ORGANIC VAPOR/MIST IF PPM REQUIRES.

Ventilation:ADEQUATE FOR PPM. LOCAL EXHAUST: IF REQUIRED BY PPM.

Protective Gloves:NEOPRENE

Eye Protection:CHEMICAL SAFETY GOGGLES

Other Protective Equipment:WASHING FACILITIES FOR EYES & SKIN.

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. AFTER USE, WASH HANDS THOROUGHLY W/SOAP & WATER.

Supplemental Safety and Health

COMPANY IS OUT OF BUSINESS PER ANNA WILLIS.

Chemical Properties

Boiling Pt:B.P. Text:302-395F

Vapor Pres:4

Vapor Density:4.8

Spec Gravity:0.89-0.91

Evaporation Rate & Reference:(BU AC=1): 0.2

Solubility in Water:INSOLUBLE

Appearance and Odor:AMBER LIQUID W/BLAND ODOR

Percent Volatiles by Volume:36-38

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:OPEN FLAMES, HOT SURFACES/ANY IGNITION SOURCES

Hazardous Decomposition Products:TOXIC FUMES

Disposal

Waste Disposal Methods:PLACE ALL CONTAMINATED MATERIAL IN DISPOSABLE CONTAINERS & BURY IN APPROVED DUMPING AREA. DISPOSE OF IAW/LOCAL, STATE & FEDERAL REGULATIONS. COMBUSTIBLE LIQUID UN1263.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.