

CLOVER SILICON CARBIDE GREASE MIX, LAPPING COMPOUND.

MSDS Number

CDXQX

National Stock Number

5350-00-193-7225

Product Name

CLOVER SILICON CARBIDE GREASE MIX, LAPPING COMPOUND.

Manufacturer

FEL PRO INC DIV OF FELT PRODUCTS MFG CO

Product Identification

Product ID:CLOVER SILICON CARBIDE GREASE MIX, LAPPING COMPOUND.

MSDS Date:10/14/1986

FSC:5350

NIIN:00-193-7225

MSDS Number: CDXQX

Responsible Party

FEL-PRO INC DIV OF FELT PRODUCTS MFG CO

7450 N MCCORMICK

SKOKIE , IL 60076-4046

US

Emergency Phone: 708-674-7700

Info Phone: 708-674-7700

Preparer: DIANNE GALLAGHER

Cage: 73165

Contractor

FEL-PRO INC DIV OF FELT PRODUCTS MFG CO

1103

SKOKIE, IL 60076-4046

US

847-674-7700 OR 312-761-4500

Cage: 73165

Ingredients

NON-HAZARDOUS INGREDIENTS

OSHA PELNOT RELEVANT

ACGIH TLV: NOT RELEVANT

Hazards

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:POSSIBLE MECHANICAL IRRITATION IF
INTRODUCED INTO EYE DUE TO ABRASIVE GRIT PRESENT.

First Aid

First Aid:EYE: FLUSH W/TEPID WATER FOR 15 MINUTES, HOLD EYELIDS APART.
DO NOT RUB EYES, GET MED AID.

Fire Fighting

Flash Point Method:COC
Flash Point:>300F,>149C
Lower Limits:NA
Upper Limits:NA
Extinguishing Media:CO2, FOAM, DRY CHEMICAL.
Fire Fighting Procedures:WATER MAY BE INEFFECTIVE. USE EYE PROTECTION & SCBA WHEN FIGHTING FIRES IN CONFINED AREAS.
Unusual Fire/Explosion Hazard:NONE EXCEPT AS FOR PETROLEUM GREASE FIRES.

Accidental Release

Spill Release Procedures:SCOOP UP. WIPE UP W/RAGS OR USE ABSORBENT MATERIAL. COMPLETE CLEANUP W/DETERGENT & WATER, HIGH FLASH POINT SOLVENT OR CHLORINATED SOLVENT CLEANER W/ADEQUATE VENT.

Handling

Handling and Storage Precautions:NORMAL STORAGE & HANDLING FOR PETROLEUM GREASE PRODUCTS.
Other Precautions:KEEP OUT OF REACH OF CHILDREN.

Exposure Controls

Respiratory Protection:NONE REQUIRED.
Ventilation:LOCAL EXHAUST ACCEPTABLE. MECHANICAL, (GENERAL) ACCEPTABLE.
Protective Gloves:NONE REQUIRED.
Eye Protection:YES
Other Protective Equipment:NONE REQUIRED.
Work Hygienic Practices:NO SPECIAL WORK OR HYGENIC PRACTICE REQUIRED.
Supplemental Safety and Health
NK

Chemical Properties

Boiling Pt:B.P. Text:>500F,>260C
Melt/Freeze Pt:M.P/F.P Text:NA
Vapor Pres:NEGLIGIBLE
Vapor Density:NA
Spec Gravity:1.15
Evaporation Rate & Reference:NA
Solubility in Water:INSOLUBLE.
Appearance and Odor:GRAY PASTE, SLIGHT PETROLATUM ODOR.

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:NONE
Hazardous Decomposition Products:PYROLISIS YIELDS CO, CO2, & INCOMPLETELY BURNED HYDROCARBONS.

Disposal

Waste Disposal Methods:CONTROLLED INCINERATION OR BURY IN POSTED LANDFILL IN ACCORDANCE W/FEDERAL/STATE/LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.