



ANTIFREEZE, ETHYLENE GLYCOL

MSDS Number

BHBGH

National Stock Number

6850-00-181-7933

Product Name

ANTIFREEZE, ETHYLENE GLYCOL

Manufacturer

J B WATTS COMPANY INC

Product Identification

Product ID:ANTIFREEZE, ETHYLENE GLYCOL

MSDS Date:01/01/1987

FSC:6850

NIIN:00-181-7933

MSDS Number: BHBGH

Responsible Party

J. B. WATTS COMPANY, INC.

50 WEST 60TH STREET

CHICAGO , IL 60621

Emergency Phone: 800-424-9300 (CHEMTREC)

Info Phone: 312-324-4900

Preparer: BARRY WATTS.

Cage: 7U402

Contractor

J. B. WATTS COMPANY, INC.

CHICAGO, IL 60621-3906

US

312-324-4900

Cage: 7U402

Ingredients

ETHYLENE GLYCOL (SARA III)

CAS: 107-21-1

RTECS: KW2975000

OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM,VAPOR; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

DIETHYLENE GLYCOL

CAS: 111-46-6

RTECS: ID5950000

ACGIH TLV: 25 PPM

Hazards



LD50 LC50 Mixture:ACUTE ORAL LD50 (RAT) IS 5840 MG/KG
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: EYE AND SKIN CONTACT- PRIMARY IRRITATION TO SKIN, DEFATTING, DERMATITIS. PRIMARY IRRITATION TO EYES, REDNESS, TEARING, BLURRED VISION. ABSORPTION THRU SKIN INCREASES EXPOSURE. SWALLOWING- HARM FUL OR FATAL IF SWALLOWED. SWALLOWING MAY CAUSE ABDOMINAL IRRITATION, NAUSEA, VOMITING. AVOID BREATHING VAPORS OR MISTS.
Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.
Effects of Overexposure:SEE HEALTH HAZARDS.
Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF SKIN OR RESPIRATORY DISORDERS MAYBE AT INCREASED RISK FROM EXPOSURE.

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. CALL A PHYSICIAN IF DISCOMFORT PERSISTS. EYE: IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR 15 MINUTES. CALL A PHYSICIAN. SKIN: WASH WITH PLENTY OF SOAP & WATER. REM OVE CONTAMINATED CLOTHING/SHOES. INGESTION: IF CONSCIOUS, GIVE 2 GLASSES OF WATER TO DRINK AND INDUCE VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. CALL A PHYSICIAN IMMEDIATELY.

Fire Fighting

Flash Point Method:TCC
Flash Point:245F,118C
Lower Limits:1.5
Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER FOG.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.
Unusual Fire/Explosion Hazard:KEEP CONTAINER TIGHTLY CLOSED, ISOLATE FROM OXIDIZERS, HEAT AND OPEN FLAME. CLOSED CONTAINERS MAY EXPLODE IF EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:SMALL SPILL: WIPE/SOAK UP WITH PAPER TOWEL OR INERT ABSORBANT. PUT IN DISPOSAL CONTAINER. FLUSH RESIDUE WITH WATER. LARGE SPILL: VENTILATE AREA. IF POSSIBLE, STOP LEAK. DIKE TO RETAIN RUN OFF. VACUUM UP FREE LIQUID. FLUSH RESIDUE WITH WATER.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER. WATER DILUTION RECOMMENDED.

Handling

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED AREA. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. PROTECT CONTAINERS FROM PHYSICAL DAMAGE.
Other Precautions:DO NOT TAKE INTERNALLY. DO NOT BREATHE MIST. AVOID PROLONGED OR REPEATED BREATHING OF VAPOR. AVOID CONTACT WITH EYES. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING. FOR INDUSTRIAL USE ONLY.

Exposure Controls

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL(TLV), USE NIOSH/MSHA APPROVED ORGANIC VAPOR CARTRIDGE AND DUST/MIST PRE-FILTER RESPIRATORS AS PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/ WARNINGS AND NIOSH-RESPIRATOR SELECTION.
Ventilation:MECHANICAL (GENERAL) ROOM VENTILATION IS ADEQUATE IF USE IS ENCLOSED. LOCAL EXHAUST IS NEEDED IF VENTED INTO WORK AREA.
Protective Gloves:NEOPRENE, NITRILE, PVC OR NATURAL RUBBER
Eye Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD
Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER. INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.
Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR



FOOTWEAR.
Supplemental Safety and Health
DO NOT TAKE INTERNALLY. DO NOT GET ON SKIN OR IN EYES. AVOID PROLONGED
OR REPEATED BREATHING OF VAPOR. DO NOT BREATHE MISTS. WASH
THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING OR SMOKING
OR USING RESTROOM.

Chemical Properties

HCC:V5
Boiling Pt:B.P. Text:339F,171C
Vapor Pres:0.4
Vapor Density:2.1
Spec Gravity:1.114
Appearance and Odor:GREEN LIQUID WITH MILD ODOR
Percent Volatiles by Volume:97

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, OXIDIZERS AND
OPEN FLAMES
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE AND
OXIDES OF NITROGEN.

Disposal

Waste Disposal Methods:DISPOSAL SHOULD BE MADE BY INCINERATION IN
ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND
REGULATIONS. AT VERY LOW CONCENTRATIONS IN WATER, DISPOSE OF THIS
MATERIAL IN A BIOLOGICAL W ASTEWATER TREATMENT PLANT.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.