https://msdsreport.com/msds/BBBCH

# 3-5350 COLORED OIL BASE OFFSET INK

### **MSDS Number**

BBBCH

### **National Stock Number**

7510-00B010025

### **Product Name**

3-5350 COLORED OIL BASE OFFSET INK

### Manufacturer

A B DICK COMPANY

### **Product Identification**

Product ID:3-5350 COLORED OIL BASE OFFSET INK MSDS Date:08/19/1986 FSC:7510 NIIN:00B010025 MSDS Number: BBBCH

### **Responsible Party**

A.B.DICK COMPANY

5700 WEST TOUHY AVENUE

CHICAGO, IL 60648

US

Emergency Phone: 312-647-8800

Cage: HO951

### Contractor

DICK A B CO

CHICAGO, IL 60648

US

312-647-8800

Cage: HO951

### Ingredients

TREATED PETROLEUM OILS Fraction By Weight: 1% ACGIH TLV: 5MG/M3

## STODDARD SOLVENT CAS: 8052-41-3 RTECS: WJ8925000 Fraction By Weight: 3% OSHA PEL500 PPM

ACGIH TLV: 100 PPM; 9293

### Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Effects of Overexposure:POSSIBLE EYE OR SKIN IRRITATION

### **First Aid**



First Aid:IMMEDIATELY FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MIN. CONTACT A PHYSICIAN IF IRRITATION OCCURS. WASH AFFECTED AREA OF SKIN WITH SOAP AND WATER AND REMOVE CONTAMINATED CLOTHING. IF SW ALLOWED,DRINK 1 OR 2 GLASSES OF WATER TO DILUTE, DO NOT INDUCE VOMITING. CONSULT A PHYSICIAN. TREAT SYMPTOMATICALLY.

•

### **Fire Fighting**

Flash Point Method:TCC Flash Point:250F Lower Limits:1% Extinguishing Media:FOAM,CARBON DIOXIDE,DRY CHEMICAL Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS TO ELIMINATE EXPOSURE TO COMBUSTION PRODUCTS. Unusual Fire/Explosion Hazard:DURING EMERGENCY CONDITIONS,OVEREXPOSURE TO COMBUSTION PRODUCTS MAY CAUSE A HEALTH HAZARD

### **Accidental Release**

Spill Release Procedures:WIPE UP AND DISPOSE OF WITH SOLID WASTE.IF SOLVENT WETTED WIPES ARE USED, DISPOSE OF IN APPROVED CONTAINERS.

### Handling

Handling and Storage Precautions: KEEP CONTAINERS CLOSED WHEN NOT IN USE. KEEP AWAY FROM EXCESSIVE HEAT OR OPEN FLAME.

### **Exposure Controls**

Respiratory Protection:NOT NORMALLY REQUIRED WITH ADEQUATE VENTILATION. Ventilation:NORMAL VENTILATION FOR THE WORK AREA. Protective Gloves:GLOVES FOR PROLONGED OR REPEATED CONTACT Eye Protection:NOT NORMALLY NECESSARY Supplemental Safety and Health

### **Chemical Properties**

Boiling Pt:B.P. Text:520-600F Vapor Density:1 Spec Gravity:1.0 Solubility in Water:NEGLIGIBLE Appearance and Odor:VARIOUS COLORED PASTES WITH,HYDROCARBON ODOR Percent Volatiles by Volume:20

### Stability

Stability Indicator/Materials to Avoid:YES OXIDIZING MATERIALS Stability Condition to Avoid:STABLE UNDER NORMAL CONDITIONS Hazardous Decomposition Products:CARBON MONOXIDE,CARBON DIOXIDE,SMOKE

### Disposal

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS FOR NON-FLAMMABLE OILY WASTE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.