



UNLEADED REGULAR GASOLINE

MSDS Number

BBBDF

National Stock Number

9130-00B010045

Product Name

UNLEADED REGULAR GASOLINE

Manufacturer

AMOCO OIL COMPANY

Product Identification

Product ID:UNLEADED REGULAR GASOLINE

MSDS Date:03/07/1988

FSC:9130

NIIN:00B010045

MSDS Number: BBBDF

Responsible Party

AMOCO OIL COMPANY

200 EAST RANDOLPH DRIVE

CHICAGO , IL 60601

US

Emergency Phone: 800 447-8735

Info Phone: 312 856-3907

Cage: 15958

Contractor

AMOCO OIL CO

CHICAGO, IL 60601-6401

US

800 447-8735

Cage: 15958

Ingredients

GASOLINE

CAS: 8006-61-9

RTECS: LX3300000

OSHA PEL300 PPM/500 STEL

ACGIH TLV: 300 PPM/500STEL;9192

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:INHALATION:MODERATELY TOXIC FOR ACUTE EXPOSURES BY THIS ROUTE.EYE:NO SIGNIFICANT IRRITATION EXPECTED.INGESTION:HARMFUL IF SWALLOWED AND/OR ASPIRATED INTO LUNGS.

Effects of Overexposure:INHALATION:EXCESSIVE EXPOSURES TO VAPORS WILL PRODUCE SYMPTOMS OF INTOXICATION,HEADACHE,DIZZINESS,AND NAUSEA.SKIN:PROLONGED OR REPEATED CONTACT CAN DEFAT THE SKIN AND LEAD TO IRRITATION AND/OR DERMATI TIS.

First Aid



First Aid: IN CASE OF EYE CONTACT, FLUSH WITH PLENTY OF WATER. SKIN CONTACT, WASH EXPOSED SKIN WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING, INCLUDING SHOES AND THOROUGHLY CLEAN AND DRY BEFORE REUSE. INHALATION: IF HARMFUL EFFECTS OCCUR, REMOVE TO UNCONTAMINATED AREA. GIVE ARTIFICIAL RESPIRATION IF NOT BREATHING. INGESTION: IF SWALLOWED, DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION.

Fire Fighting

Flash Point: -45 F
Lower Limits: 1.3%
Upper Limits: 7.6%
Extinguishing Media: DRY CHEMICAL B-C, CARBON DIOXIDE, WATER FOG, FOAM (WATER MAY BE INEFFECTIVE).
Unusual Fire/Explosion Hazard: EXTREMELY FLAMMABLE VAPOR/AIR MIXTURES FORM.

Accidental Release

Spill Release Procedures: REMOVE OR SHUT OFF ALL SOURCES OF IGNITION. USE WATER SPRAY TO DISPERSE VAPORS. INCREASE VENTILATION IF POSSIBLE.

Handling

Handling and Storage Precautions: STORE AWAY FROM HEAT, IGNITION SOURCES, AND OPEN FLAME IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE, OR LOCAL REGULATIONS.
Other Precautions: USE AS MOTOR FUEL ONLY.

Exposure Controls

Respiratory Protection: AVOID BREATHING VAPOR AND/OR MIST. USE WITH ADEQUATE VENTILATION.
Protective Gloves: YES
Eye Protection: SAFETY GLASSES
Other Protective Equipment: WEAR PROTECTIVE CLOTHING AND GLOVES IF PROLONGED OR REPEATED CONTACT IS LIKELY.
Supplemental Safety and Health

Chemical Properties

Boiling Pt: B.P. Text: 80F TO 430F
Vapor Pres: 9-15 D-323
Vapor Density: 3 TO 4
Spec Gravity: H₂O=1 0.75
Solubility in Water: NEGLIGIBLE BELOW 0.1
Appearance and Odor: CLEAR, BRIGHT LIQUID. CHARACTERISTIC ODOR

Stability

Stability Indicator/Materials to Avoid: YES
AVOID STRONG OXIDIZERS

Disposal

Waste Disposal Methods: ENCLOSED-CONTROLLED INCINERATION IS RECOMMENDED UNLESS DIRECTED OTHERWISE BY APPLICABLE ORDINANCES.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.