

## **QUICK-SLIP WIRE PULLING LUBRICANT**

### **MSDS Number**

BBBDM

### **National Stock Number**

6850-00B010051

### **Product Name**

QUICK-SLIP WIRE PULLING LUBRICANT

### **Manufacturer**

AMERACE CORP

### **Product Identification**

Product ID:QUICK-SLIP WIRE PULLING LUBRICANT

MSDS Date:12/09/1987

FSC:6850

NIIN:00B010051

MSDS Number: BBBDM

### **Responsible Party**

AMERACE CORPORATION

NEWBURGH ROAD

HACKETTSTOWN , NJ 07840

US

Emergency Phone: 800424-9300

Info Phone: 201852-1122 EXT. 200

Cage: 11117

### **Contractor**

AMERACE CORPORATION

HACKETTSTOWN, NJ 07840

US

201852-1122 EXT. 200

Cage: 11117

### **Ingredients**

ANTIMONY TRIOXIDE (SARA III)

CAS: 1309-64-4

RTECS: CC5650000

Fraction By Weight:

OSHA PEL0.5 MG/M3 (SB)

ACGIH TLV: 0.5 MG SB/M3; 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

### **Hazards**

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:UNKNOWN IARC:UNKNOWN OSHA:NO

Effects of Overexposure:PROLONGED EXPOSURE MAY CAUSE MILD SKIN IRRITATION.

### **First Aid**

First Aid: INHALATION: REMOVE TO FRESH AIR. SKIN: WASH THOROUGHLY WITH WATER. INGESTION: SEEK PROMPT MEDICAL ATTENTION. FLUSH AFFECTED AREAS WITH COPIOUS AMOUNTS OF WATER. SEEK MEDICAL ATTENTION IF DISCOMFORT PERSISTS.

## Fire Fighting

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL POWDER, FOAM.  
Fire Fighting Procedures: FIREFIGHTERS MUST WEAR SELF-CONTAINED BREATHING APPARATUS AND FULLY PROTECTIVE EQUIPMENT.  
Unusual Fire/Explosion Hazard: MATERIAL IS SELF-EXTINGUISHING. PROLONGED BURNING MAY RELEASE HYDROCHLORIC ACID VAPORS.

## Accidental Release

Spill Release Procedures: ABSORB SPILL ON SAND OR VERMICULITE, SCOOP UP, AND HOLD.

## Handling

Handling and Storage Precautions: STORE MATERIAL AT ROOM TEMPERATURE; KEEP STORAGE CONTAINER TIGHTLY CLOSED. AVOID PROLONGED OR FREQUENT EXPOSURE.  
Other Precautions: AVOID CONTACT WITH EYES, SKIN AND CLOTHING. WASH THOROUGHLY AFTER HANDLING.

## Exposure Controls

Respiratory Protection: OSHA/MSHA APPROVED RESPIRATOR.  
Ventilation: USE WITH ADEQUATE VENTILATION.  
Protective Gloves: RUBBER  
Eye Protection: SAFETY GOGGLES  
Other Protective Equipment: SAFETY SHOWER AND EYEBATH.  
Work Hygienic Practices: SURFACES SUBJECT TO SPILLS CAN BECOME SLIPPERY. KEEP FLOORS CLEAN AND DRY.  
Supplemental Safety and Health

## Chemical Properties

Spec Gravity: 1.00  
Solubility in Water: APPRECIABLE  
Appearance and Odor: YELLOW, SEMI-SOLID PASTE. NO ODOR.

## Stability

Stability Indicator/Materials to Avoid: YES  
Stability Condition to Avoid: THERMAL DECOMPOSITION  
Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE, HYDROCHLORIC ACID VAPORS.

## Disposal

Waste Disposal Methods: MIX WASTE WITH A COMBUSTIBLE CARRIER AND BURN IN A SUITABLE EQUIPPED CHEMICAL INCINERATOR. DISPOSAL MUST COMPLY WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.