
CASTROL R RACING SAE 40 MOTOR OIL

MSDS Number

BBBGK

National Stock Number

9150-00B020032

Product Name

CASTROL R RACING SAE 40 MOTOR OIL

Manufacturer

BURMAH CASTROL INC

Product Identification

Product ID:CASTROL R RACING SAE 40 MOTOR OIL

MSDS Date:04/18/1986

FSC:9150

NIIN:00B020032

MSDS Number: BBBGK

Responsible Party

BURMAH-CASTROL,INC.

30 EXECUTIVE AVE

EDISON , NJ 08817

US

Emergency Phone: 201 287-3120

Preparer: CHARLES R. PROSS

Cage: DO826

Contractor

BURMAH-CASTROL,INC.

EDISON, NJ 08817

US

Cage: DO826

Ingredients

NO HAZARDOUS MATERIALS

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE SKIN IRRITATION.

Effects of Overexposure:SAME AS ACUTE AND CHRONIC EXPOSURE.

First Aid

First Aid:INHALATION:REMOVE FROM AREA OF VAPORS.EYES:FLUSH WITH CLEAR WATER UNTIL IRRITATION SUBSIDES.CONTACT A PHYSICIAN AS SOON AS POSSIBLE.SKIN:WIPE OR USE WATERLESS HANDCLEANER,WASH SKIN WITH SOAP AND WATER .INGESTION:DONOT INDUCE VOMITING. CONTACT A PHYSICIAN.

Fire Fighting

Flash Point Method:COC

Flash Point:420-440F

Lower Limits:1.0

Upper Limits:6.0

Extinguishing Media:DRY CHEMICAL,CARBON DIOXIDE,FOAM,WATER FOG

Fire Fighting Procedures:USE AIR-SUPPLIED RESCUE EQUIPMENT FOR ENCLOSED

AREAS.COOL EXPOSED CONTAINERS WITH WATER
Unusual Fire/Explosion Hazard:STORE IN CLOSED CONTAINERS AWAY FROM
SOURCES OF IGNITION AND OXIDIZING SUBSTANCES.

Accidental Release

Spill Release Procedures:MOP OR WIPE UP OR ABSORB WITH
CLAY,DIATOMACEOUS EARTH OR OTHER INERT MATERIAL AND STORE IN CLOSED
METAL CONTAINERS.

Handling

Handling and Storage Precautions:KEEP CONTAINERS CLOSED AND AWAY FROM
EXTREME HEAT.
Other Precautions:AVOID BREATHING OF OIL MIST. REMOVE OIL IMPREGNATED
CLOTHING.WASH THOROUGHLY AFTER EXPOSURE.

Exposure Controls

Respiratory Protection:NOT NORMALLY NEEDED.USE SUPPLIED AIR (SPECIFY
TYPE)RESPIRATORY PROTECTION IN CONFINED OR ENCLOSED AREAS.
Ventilation:MAINTAIN EXPOSURE BELOW 5MG PER CUBIC METER. FAN IF NEEDED.
Protective Gloves:USE CHEMICALLY RESISTANT GLOVES.
Eye Protection:USE SPLASH GOGGLES.
Other Protective Equipment:USE CHEMICALLY RESISTANT APRON OR OTHER
CLOTHING TO AVOID PROLONGED SKIN CONTACT.
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:500F
Vapor Pres:.01 @ 20C
Vapor Density:1.0
Spec Gravity:0.95-0.96
Evaporation Rate & Reference:.01
Solubility in Water:NEGLIGIBLE
Appearance and Odor:YELLOW TO AMBER LIQUID,PETROLEUM ODOR

Stability

Stability Indicator/Materials to Avoid:YES
AVOID STRONG OXIDIZING AGENTS LIKE LIQUID CHLORINE AND CONCENTRATED
OXYGEN.
Hazardous Decomposition Products:COMBUSTION MAY PRODUCE SMOKE,CARBON
MONOXIDE AND OXIDES OF SULFUR AND NITROGEN

Disposal

Waste Disposal Methods:CONTROLLED INCINERATION OR METHOD IN COMPLIANCE
WITH LOCAL,STATE AND FEDERAL REGULATIONS REGARDING HEALTH,AIR AND
WATER POLLUTION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.