

CASTROL R RACING SAE 30 MOTOR OIL

MSDS Number

BBBGL

National Stock Number

9150-00B020033

Product Name

CASTROL R RACING SAE 30 MOTOR OIL

Manufacturer

BURMAH CASTROL INC

Product Identification

Product ID:CASTROL R RACING SAE 30 MOTOR OIL

MSDS Date:04/16/1986

FSC:9150

NIIN:00B020033

MSDS Number: BBBGL

Responsible Party

BURMAH-CASTROL,INC.

30 EXECUTIVE AVE

EDISON , NJ 08817

US

Emergency Phone: 201287-3120

Preparer: CHARLES R. PROSS

Cage: D0826

Contractor

BURMAH-CASTROL,INC.

EDISON, NJ 08817

US

Cage: D0826

Ingredients

NO HAZARDOUS INGREDIENTS

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE SKIN IRRITATION.

Effects of Overexposure:SAME AS ACUTE AND CHRONIC EXPOSURE.

First Aid

First Aid:INHALATION:REMOVE FROM AREA OF VAPORS. EYES:FLUSH WITH CLEAR WATER UNTIL IRRITATION SUBSIDES. CONTACT A PHYSICIAN AS SOON AS POSSIBLE. SKIN:WIPE OR USE WATERLESS HANDCLEANER. WASH SKIN WITH SOAP AND WATER. INGESTION:DO NOT INDUCE VOMITING.CONTACT A PHYSICIAN.

Fire Fighting

Flash Point Method:COC

Flash Point:420-440F

Lower Limits:1.0

Upper Limits:6.0

Extinguishing Media:DRY CHEMICAL,CARBON DIOXIDE,FOAM,WATER FOG

Fire Fighting Procedures:USE AIR-SUPPLIED RESCUE EQUIPMENT FOR ENCLOSED AREAS.COOL EXPOSED CONTAINERS WITH WATER.

Unusual Fire/Explosion Hazard:STORE IN CLOSED CONTAINERS AWAY FROM SOURCES OF IGNITION AND OXIDIZING SUBSTANCES.

Accidental Release

Spill Release Procedures:MOP OR WIPE UP OR ABSORB WITH CLAY,DIATOMACEOUS EARTH OR OTHER INERT MATERIAL AND STORE IN CLOSED METAL CONTAINERS.

Handling

Handling and Storage Precautions:KEEP CONTAINERS CLOSED AND AWAY FROM EXTREME HEAT.

Other Precautions:AVOID BREATHING OF OIL MIST.REMOVE OIL IMPREGNATED CLOTHING.WASH THOROUGHLY AFTER EXPOSURE.

Exposure Controls

Respiratory Protection:NOT NORMALLY NEEDED.USE SUPPLIED AIR (SPECIFY TYPE) RESPIRATORY PROTECTION IN CONFINED OR ENCLOSED AREAS.

Ventilation:MAINTAIN EXPOSURE BELOW 5MG PER CUBIC METER.FAN IF NEEDED.

Protective Gloves:USE CHEMICALLY RESISTANT GLOVES.

Eye Protection:USE SPLASH GOGGLES.

Other Protective Equipment:USE CHEMICALLY RESISTANT APRON OR OTHER CLOTHING TO AVOID PROLONGED SKIN CONTACT.

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:500F

Vapor Pres:.01 @ 20C

Vapor Density:1.0

Spec Gravity:0.95-0.96

Evaporation Rate & Reference:.01

Solubility in Water:NEGLIGIBLE

Appearance and Odor:YELLOW TO AMBER LIQUID;PETROLEUM ODOR.

Stability

Stability Indicator/Materials to Avoid:YES

AVOID STRONG OXIDIZING AGENTS LIKE LIQUID CHLORINE AND CONCENTRATED OXYGEN.

Hazardous Decomposition Products:COMBUSTION MAY PRODUCE SMOKE,CARBON MONOXIDE AND OXIDES OF SULFUR AND NITROGEN.

Disposal

Waste Disposal Methods:CONTROLLED INCINERATION OR METHOD IN COMPLIANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS REGARDING HEALTH,AIR AND WATER POLLUTION.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.