



CASTROL REGAL COAT

MSDS Number

BBBGP

National Stock Number

6850-00B020036

Product Name

CASTROL REGAL COAT

Manufacturer

BURMAH CASTROL INC

Product Identification

Product ID: CASTROL REGAL COAT

MSDS Date: 10/27/1985

FSC: 6850

NIIN: 00B020036

MSDS Number: BBBGP

Responsible Party

BURMAH-CASTROL INC.

30 EXECUTIVE AVE

EDISON , NJ 08817

US

Emergency Phone: 201 287-3120

Preparer: MICHAEL P. SHEEHAN

Cage: DO827

Contractor

BURMAH-CASTROL INC.

EDISON, NJ 08817

US

201 287-3120

Cage: DO827

Ingredients

MINERAL SPIRITS

CAS: 64475-85-0

RTECS: PY8240000

Fraction By Weight: 33%

ASBESTOS, CHRYSOTILE

CAS: 12001-29-5

RTECS: CI6478500

Fraction By Weight: 3%

OSHA PEL0.2 FIBERS/CC

ACGIH TLV: 2 FIBERS/CC,A1; 9495

Hazards

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES



Health Hazards Acute and Chronic: MAY CAUSE SEVERE IRRITATION TO EYES, MILD IRRITATION AND POSSIBLE DERMATITIS TO SKIN. INHALATION MAY CAUSE HEADACHES, NAUSEA AND DIZZINESS.
Effects of Overexposure: SAME AS SYMPTOMS FOR ACUTE AND CHRONIC

First Aid

First Aid: INHALATION: REMOVE FROM AREA OF VAPORS. APPLY OXYGEN AND ARTIFICIAL RESPIRATION. EYES: FLUSH EYES WITH CLEAR WATER UNTIL IRRITATION SUBSIDES. CONTACT A PHYSICIAN AS SOON AS POSSIBLE. SKIN: WIPE OR USE WATERLESS HANDCLEANER, WASH SKIN WITH SOAP AND WATER. INGESTION: DO NOT INDUCE VOMITING, CONTACT A PHYSICIAN.

Fire Fighting

Flash Point Method: TCC
Flash Point: 108
Lower Limits: 0.7
Upper Limits: 6.0
Extinguishing Media: DRY CHEMICAL, CARBON DIOXIDE, FOAM, WATER FOG
Fire Fighting Procedures: USE AIR-SUPPLIED RESCUE EQUIPMENT FOR ENCLOSED AREAS. COOL EXPOSED CONTAINERS WITH WATER
Unusual Fire/Explosion Hazard: TYPICAL FOR COMBUSTIBLE SOLVENT.

Accidental Release

Spill Release Procedures: REMOVE ALL IGNITION SOURCES. VENTILATE AREA WELL IF ABOVE TLV USE SELF CONTAINED BREATHING APPARATUS. COVER AND CONTAIN SPILL WITH ABSORBANT MATERIAL. USE NON-SPARKING TOOLS TO SHOVEL INTO CONT.

Handling

Handling and Storage Precautions: STORE AND USE ONLY IN WELL VENTILATED AREAS, AWAY FROM ALL IGNITION SOURCES. STORE WITH CONTAINERS TIGHTLY SEALED.
Other Precautions: FOLLOW GOOD PERSONAL HYGIENE PRACTICES.

Exposure Controls

Respiratory Protection: ORGANIC VAPOR MASK.
Ventilation: LOCAL EXHAUST RECOMMENDED. FAN IF NEEDED.
Protective Gloves: USE CHEMICALLY RESISTANT GLOVES.
Eye Protection: USE SPLASH GOGGLES.
Other Protective Equipment: USE CHEMICALLY RESISTANT APRON OR OTHER CLOTHING TO AVOID PROLONGED SKIN CONTACT.
Supplemental Safety and Health

Chemical Properties

Boiling Pt: B.P. Text: 318-380F
Vapor Pres: 2.0
Vapor Density: 4.90
Spec Gravity: 1.09
Evaporation Rate & Reference: 0.21
Solubility in Water: NEGLIGIBLE
Appearance and Odor: BLACK, THIXOTROPIC MASTIC, PETROLEUM ODOR.
Percent Volatiles by Volume: 58

Stability

Stability Indicator/Materials to Avoid: YES
AVOID STRONG OXIDIZING AGENTS LIKE LIQUID CHLORINE AND CONCENTRATED OXYGEN.
Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE, SMOKE UPON IGNITION POSSIBLY FREE ASBESTOS AT EXTREMELY.

Disposal

Waste Disposal Methods: CONTROLLED INCINERATION OR METHOD IN COMPLIANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS REGARDING HEALTH, AIR AND WATER POLLUTION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department



of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.