

CONOCO FLEET MOTOR OIL SAE 10W

MSDS Number

BBBHK

National Stock Number

9150-00B030008

Product Name

CONOCO FLEET MOTOR OIL SAE 10W

Manufacturer

CONOCO INC

Product Identification

Product ID: CONOCO FLEET MOTOR OIL SAE 10W MSDS Date:10/21/1985 FSC:9150 NIIN:00B030008 MSDS Number: BBBHK

Responsible Party

CONOCO, INC.

PONCA CITY, OK 74603

US

Emergency Phone: 800 424-9300

Info Phone: 405 767-6000

Cage: DO836 **Contractor**

CONOCO, INC.

1267

PONCA CITY, OK 74603

US

405 767-6000 Cage: DO836

Ingredients

NO HAZARDOUS MATERIALS

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Effects of Overexposure: THIS PRODUCT MAY CAUSE IRRITATION TO EYES, LUNGS, OR SKIN AFTER PROLONGED EXPOSURE.

First Aid

First Aid: EYES: QUICKLY WASH WITH FRESH WATER FOR 15 MIN AND GET MEDICAL ATTENTION.SKIN: WASH WITH SOAP AND WATER AND REMOVE CONTAMINATED CLOTHIG.INHALATION: IF OVEREXPOSED, REMOVE INDIVIDUAL TO FRESH AIR. IF BREATH ING STOPS ADMINISTER ARTIFICIAL RESPIRATION.INGESTION:IF SWALLOWED, DONOT INDUCE VOMITING, IF VOMITING BEGINS, LOW VICTIMS HEAD IN AN EFFORT TO PREVENT VOMITUS FROM ENTERING LUNGS.CALL DOCTOR.

Fire Fighting

Flash Point Method: PMCC Flash Point:340

Extinguishing Media: USE WATER SPRAY, DRY CHEMICAL, FOAM, OR CARBON



DIOXIDE.

Fire Fighting Procedures: WATER OR FOAM MAY CAUSE FROTHING. USE WATER TO KEEP FIRE EXPOSED CONTAINERS COOL. WATER SPRAY MAY BE USED TO FLUSH SPILLS AWAY FROM EXPOSURES.

Unusual Fire/Explosion Hazard: PRODUCTS OF COMBUSTON MAY CONTAIN CARBON MONOXIDE, CARBON DIOXIDE, AND OTHER TOXIC MATERIALS. DONOT ENTER ENCLOSED SPACE WITHOUT PROTECTIVE EQUIPMENT.

Accidental Release

Spill Release Procedures: CONTAIN SPILL IMMEDIATELY IN SMALLEST AREA POSSIBLE.RECOVER AS MUCH OF THE PRODUCT ITSELF AS POSSIBLE BY VACUUMING, FOLLOWED BY SOAKING UP RESIDUAL FLUIDS BY USE OF ABSORBENT MATERIALS.

Handling

Handling and Storage Precautions: PRODUCT IS CLASS IIIB COMBUSTIBLE LIQUID.STORE AND HANDLE ACCORDINGLY.

Other Precautions: PROLONGED OR REPEATED SKIN CONTACT WITH USED MOTOR

Other Precautions: PROLONGED OR REPEATED SKIN CONTACT WITH USED MOTOR OIL MAY BE HARMFUL. WASH THOROUGHLY WITH SOAP AND WATER AFTER CONTACT.

Exposure Controls

Respiratory Protection: NONE REQUIRED EXCEPT UNDER UNUSUAL

CIRCUMSTANCES.

Ventilation: NORMAL SHOP VENTILATION.

Protective Gloves: NONE REQUIRED. Eye Protection: NONE REQUIRED.

Other Protective Equipment: NONE REQUIRED.

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:650-1200 F

Spec Gravity: 0.88

Solubility in Water: INSOLUBLE

Appearance and Odor: BROWN LIQUID, MILD PETROLEUM HYDROCARBON ODOR

Stability

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:STRONG OXIDIZING MATERIALS,HEAT,FLAME.
Hazardous Decomposition Products:NORMAL COMBUSTION FORMS CARBON
DIOXIDE.INCOMPLETE COMBUSTION MAY PRODUCE CARBON MONOXIDE.

Disposal

Waste Disposal Methods: RECYCLE AS MUCH OF THE RECOVERABLE PRODUCT AS POSSIBLE.DISPOSE OF NONRECYCLABLE MATERIAL BY SUCH METHODS AS CONTROLLED INCINERATION, COMPLYING WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.