

## **CONOCO FLEET MOTOR OIL SAE 30**

### **MSDS Number**

BBBHN

### **National Stock Number**

9150-00B030011

### **Product Name**

CONOCO FLEET MOTOR OIL SAE 30

### **Manufacturer**

CONOCO INC

### **Product Identification**

Product ID: CONOCO FLEET MOTOR OIL SAE 30

MSDS Date: 10/21/1985

FSC: 9150

NIIN: 00B030011

MSDS Number: BBBHN

### **Responsible Party**

CONOCO, INC.

PONCA CITY, OK 74603

US

Emergency Phone: 800 424-9300

Info Phone: 405 767-6000

Cage: D0836

### **Contractor**

CONOCO, INC.

1267

PONCA CITY, OK 74603

US

405 767-6000

Cage: D0836

### **Ingredients**

NO HAZARDOUS MATERIALS

### **Hazards**

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Effects of Overexposure: THIS PRODUCT MAY CAUSE IRRITATION TO EYES, LUNGS, OR SKIN AFTER PROLONGED EXPOSURE.

### **First Aid**

First Aid: EYES: QUICKLY WASH WITH FRESH WATER FOR 15 MIN AND GET MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER AND REMOVE CONTAMINATED CLOTHING. INHALATION: IF OVEREXPOSED, REMOVE INDIVIDUAL TO FRESH AIR. IF BREATHING STOPS ADMINISTER ARTIFICIAL RESPIRATION. INGESTION: IF SWALLOWED, DO NOT INDUCE VOMITING, IF VOMITING BEGINS, LOW VICTIMS HEAD IN AN EFFORT TO PREVENT VOMITUS FROM ENTERING LUNGS. CALL DOCTOR.

### **Fire Fighting**

Flash Point Method: PMCC

Flash Point: 340

Extinguishing Media:USE WATER SPRAY,DRY CHEMICAL,FOAM OR CARBON DIOXIDE  
Fire Fighting Procedures:WATER OR FOAM MAY CAUSE FROTHING. USE WATER TO  
KEEP FIRE EXPOSED CONTAINERS COOL. WATER SPRAY MAY BE USED TO FLUSH  
SPILLS AWAY FROM EXPOSURES.  
Unusual Fire/Explosion Hazard:PRODUCTS OF COMBUSTION MAY CONTAIN CARBON  
MONOXIDE,CARBON DIOXIDE,AND OTHER TOXIC MATERIALS.DONOT ENTER  
EXPOSED SPACE WITHOUT PROTECTIVE EQUIPMENT.

## Accidental Release

Spill Release Procedures:CONTAIN SPILL IMMEDIATELY IN SMALLEST AREA  
POSSIBLE.RECOVER AS MUCH OF THE PRODUCT ITSELF AS POSSIBLE BY  
VACUUMING,FOLLOWED BY SOAKING UP RESIDUAL FLUIDS BY USE OF  
ABSORBENT MATERIALS.

## Handling

Handling and Storage Precautions:PRODUCT IS CLASS IIIB COMBUSTIBLE  
LIQUID.STORE AND HANDLE ACCORDINGLY.  
Other Precautions:PROLONGED OR REPEATED SKIN CONTACT WITH USED MOTOR  
OIL MAY BE HARMFUL. WASH THOROUGHLY WITH SOAP AND WATER AFTER  
CONTACT.

## Exposure Controls

Respiratory Protection:NONE REQUIRED EXCEPT UNDER UNUSUAL  
CIRCUMSTANCES.  
Ventilation:NORMAL SHOP VENTILATION.  
Protective Gloves:NONE REQUIRED.  
Eye Protection:NONE REQUIRED.  
Other Protective Equipment:NONE REQUIRED.  
Supplemental Safety and Health

## Chemical Properties

Boiling Pt:B.P. Text:650-1200 F  
Spec Gravity:0.88  
Solubility in Water:INSOLUBLE  
Appearance and Odor:BROWN LIQUID,MILD PETROLEUM HYDROCARBON ODOR

## Stability

Stability Indicator/Materials to Avoid:YES  
Stability Condition to Avoid:STRONG OXIDIZING MATERIALS,HEAT,FLAME  
Hazardous Decomposition Products:NORMAL COMBUSTION FORMS CARBON  
DIOXIDE.INCOMPLETE COMBUSTION MAY PRODUCE CARBON MONOXIDE.

## Disposal

Waste Disposal Methods:RECYCLE AS MUCH OF THE RECOVERABLE PRODUCT AS  
POSSIBLE.DISPOSE OF NONRECYCLABLE MATERIAL BY SUCH METHODS AS  
CONTROLLED INCINERATION,COMPLYING WITH FEDERAL,STATE AND LOCAL  
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.