

CONOCO FLEET MOTOR OIL SAE 50

MSDS Number

BBBHQ

National Stock Number

9150-00B030013

Product Name

CONOCO FLEET MOTOR OIL SAE 50

Manufacturer

CONOCO INC

Product Identification

Product ID: CONOCO FLEET MOTOR OIL SAE 50

MSDS Date: 10/21/1985

FSC: 9150

NIIN: 00B030013

MSDS Number: BBBHQ

Responsible Party

CONOCO, INC.

PONCA CITY, OK 74603

US

Emergency Phone: 800 424-9300

Info Phone: 405 767-6000

Cage: DO836

Contractor

CONOCO, INC.

1267

PONCA CITY, OK 74603

US

405 767-6000

Cage: DO836

Ingredients

NO HAZARDOUS MATERIALS

Hazards

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Effects of Overexposure: THIS PRODUCT MAY CAUSE IRRITATION TO EYES, LUNGS OR SKIN AFTER PROLONGED EXPOSURE.

First Aid

First Aid: EYES: QUICKLY WASH WITH FRESH WATER FOR 15 MIN AND GET MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER AND REMOVE CONTAMINATED CLOTHING. INHALATION: IF OVEREXPOSED, REMOVE INDIVIDUAL TO FRESH AIR. IF BREATHING STOPS ADMINISTER ARTIFICIAL RESPIRATION. INGESTION: IF SWALLOWED, DO NOT INDUCE VOMITING. IF VOMITING BEGINS, LOW VICTIMS HEAD IN AN EFFORT TO PREVENT VOMITUS FROM ENTERING LUNGS. CALL DOCTOR.

Fire Fighting

Flash Point Method: PMCC

Flash Point: 340

Extinguishing Media: USE WATER SPRAY, DRY CHEMICAL, FOAM, OR CARBON DIOXIDE

Fire Fighting Procedures:WATER OR FOAM MAY CAUSE FROTHING.USE WATER TO KEEP FIRE EXPOSED CONTAINERS COOL.WATER SPRAY MAY BE USED TO FLUSH SPILLS AWAY FROM EXPOSURES
Unusual Fire/Explosion Hazard:PRODUCTS OF COMBUSTION MAY CONTAIN CARBON MONOXIDE,CARBON DIOXIDE,AND OTHER TOXIC MATERIALS. DO NOT ENTER ENCLOSED SPACE WITHOUT PROTECTIVE EQUIPMENT.

Accidental Release

Spill Release Procedures:CONTAIN SPILL IMMEDIATELY IN SMALLEST AREA POSSIBLE.RECOVER AS MUCH OF THE PRODUCT ITSELF AS POSSIBLE BY VACUUMING,FOLLOWED BY SOAKING UP RESIDUAL FLUIDS BY USE OF ABSORBENT MATERIALS.

Handling

Handling and Storage Precautions:PRODUCT IS CLASS IIIB COMBUSTIBLE LIQUID.STORE AND HANDLE ACCORDINGLY.
Other Precautions:PROLONGED OR REPEATED SKIN CONTACT WITH USED MOTOR OIL MAY BE HARMFUL. WASH THOROUGHLY WITH SOAP AND WATER AFTER CONTACT.

Exposure Controls

Respiratory Protection:NONE REQUIRED EXCEPT UNDER UNUSUAL CIRCUMSTANCES.
Ventilation:NORMAL SHOP VENTILATION.
Protective Gloves:NONE REQUIRED
Eye Protection:NONE REQUIRED
Other Protective Equipment:NONE REQUIRED
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:650-1200 F
Spec Gravity:0.88
Solubility in Water:INSOLUBLE
Appearance and Odor:BROWN LIQUID,MILD PETROLEUM HYDROCARBON ODOR

Stability

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:STRONG OXIDIZING MATERIALS,HEAT,FLAME.
Hazardous Decomposition Products:NORMAL COMBUSTION FORMS CARBON MONOXIDE.INCOMPLETE COMBUSTION MAY PRODUCE CARBON MONOXIDE

Disposal

Waste Disposal Methods:RECYCLE AS MUCH OF THE RECOVERABLE PRODUCT AS POSSIBLE.DISPOSE OF NONRECYCLEABLE MATERIAL BY SUCH METHODS AS CONTROLLED INCINERATION,COMPLYING WITH FEDERAL,STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.