

## **BELT DRESSING,TM 731 #81871 POWER GRIP**

### **MSDS Number**

BBBJN

### **National Stock Number**

6850-00B030032

### **Product Name**

BELT DRESSING,TM 731 #81871 POWER GRIP

### **Manufacturer**

CURTIS INDUSTRIES

### **Product Identification**

Product ID:BELT DRESSING,TM 731 #81871 POWER GRIP

MSDS Date:07/04/1986

FSC:6850

NIIN:00B030032

MSDS Number: BBBJN

### **Responsible Party**

CURTIS INDUSTRIES

34999 CURTIS BLVD

EASTLAKE , OH 44094

US

Emergency Phone: 216951-2400 EXT.5678

Info Phone: 216951-2400 EXT.282

Cage: 91636

### **Contractor**

CURTIS INDUSTRIES

EASTLAKE, OH 44094

US

216951-2400 EXT. 282

Cage: 91636

### **Ingredients**

METHYLENE CHLORIDE (SARA III)

CAS: 75-09-2

RTECS: PA8050000

Fraction By Weight: 60%

OSHA PEL500 PPM/C,1000; Z2

ACGIH TLV: 50 PPM, A2; 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

PROPANE

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight: 5%

OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIA NT; 9192

## Hazards

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES  
Health Hazards Acute and Chronic: MAY CAUSE DIZZINESS OR NARCOSIS IN HIGH VAPOR CONCENTRATIONS. WILL CAUSE DEFATTING OF SKIN. EFFECTS ARE REVERSIBLE.  
Explanation of Carcinogenicity: PRESENTLY NOT ON ANY LIST.  
Effects of Overexposure: INHALATION: DIFFICULTY IN BREATHING. SKIN: REDNESS. INGESTION: VOMITING. LONGTERM EXPOSURE (YEARS) VAPOR MAY CAUSE LUNG, LIVER OR KIDNEY DAMAGE.  
Medical Cond Aggravated by Exposure: HEART DISEASE

## First Aid

First Aid: GIVE OXYGEN-DO NOT INDUCE VOMITING-GASTRIC LAVAGE-WASH EYES AND SKIN WITH WATER.

## Fire Fighting

Flash Point Method: TCC  
Flash Point: 40F  
Lower Limits: 1.8  
Upper Limits: 12.0  
Extinguishing Media: USE WATER FOG, DRY CHEMICAL OR CARBON DIOXIDE.  
Fire Fighting Procedures: AEROSOL CANS MAY RUPTURE WHEN HEATED.  
Unusual Fire/Explosion Hazard: HEATED CANS MAY BURST.

## Accidental Release

Spill Release Procedures: USE ABSORBENT SWEEPING COMPOUND TO SOAK UP MATERIAL. PUT INTO CONTAINER. DISPOSE AS HAZARDOUS WASTE.

## Handling

Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS, OR OPEN FLAME. STORE AT TEMPERATURES BELOW 120F.  
Other Precautions: NONE

## Exposure Controls

Respiratory Protection: SELF CONTAINED BREATHING APPARATUS IF ABOVE TLV LIMIT.  
Ventilation: LOCAL EXHAUST  
Protective Gloves: NONE REQUIRED IF SPRAYING.  
Eye Protection: WEAR EYE PROTECTION.  
Other Protective Equipment: LONG SLEEVE AND LONG PANTS.  
Work Hygienic Practices: DO NOT SMOKE WHILE SPRAYING; WASH HANDS AFTER USE.  
Supplemental Safety and Health

## Chemical Properties

Boiling Pt: B.P. Text: 40F TO 350F  
Vapor Pres: 28  
Vapor Density: 4.0  
Spec Gravity: 0.9  
Evaporation Rate & Reference: 0.3  
Solubility in Water: NONE  
Appearance and Odor: CLEAR-SOLVENT ODOR

## Stability

Stability Indicator/Materials to Avoid: YES  
NONE  
Stability Condition to Avoid: HIGH TEMPERATURES.  
Hazardous Decomposition Products: IN A FIRE, FORMS PHOSGENE & HYDROCHLORIC ACID.

## Disposal

Waste Disposal Methods: DISPOSE AS HAZARDOUS WASTE IN ACCORDANCE WITH

EPA RCRA.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.