

---

## **DURAFLOW RTV SILICONE CAULK**

### **MSDS Number**

BBBJP

### **National Stock Number**

6850-00B030033

### **Product Name**

DURAFLOW RTV SILICONE CAULK

### **Manufacturer**

CURTIS INDUSTRIES

### **Product Identification**

Product ID:DURAFLOW RTV SILICONE CAULK

MSDS Date:07/01/1985

FSC:6850

NIIN:00B030033

MSDS Number: BBBJP

### **Responsible Party**

CURTIS INDUSTRIES

34999 CURTIS BLVD.

EASTLAKE , OH 44094

US

Emergency Phone: 216951-2400 EXT. 5678

Cage: 91636

### **Contractor**

CURTIS INDUSTRIES

EASTLAKE, OH 44094

US

216951-2400 EXT. 282

Cage: 91636

### **Ingredients**

ACETOXSILANE

Fraction By Weight: 5%

ACGIH TLV: 10 PPM

### **Hazards**

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Effects of Overexposure:IRRITATES EYES.PROLONGED OR REPEATED CONTACT  
MAY IRRITATE SKIN.

### **First Aid**

First Aid:WIPE OFF.FLUSH WITH WATER.OBTAIN MEDICAL ATTENTION FOR EYES  
IF NECESSARY.

### **Fire Fighting**

Flash Point Method:OC

Flash Point:250F/120C

Extinguishing Media:CARBON DIOXIDE OR FOAM

Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS AND  
PROTECTIVE CLOTHING SHOULD BE WORN IF FIGHTING FIRES INVOLVING  
CHEMICALS.

Unusual Fire/Explosion Hazard:CONTENTS UNDER PRESSURE.HIGH TEMPERATURES MAY CAUSE THE CONTAINER TO RUPTURE.

### **Accidental Release**

Spill Release Procedures:USE ABSORBENT MATERIAL TO COLLECT AND CONTAIN FOR SALVAGE OR DISPOSAL.

### **Handling**

Handling and Storage Precautions:STORE BELOW 120F/49C.USE REASONABLE CARE.

### **Exposure Controls**

Respiratory Protection:ACID VAPOR TYPE.  
Ventilation:GENERAL VENTILATION  
Protective Gloves:RUBBER PLASTIC RECOMMENDED.  
Eye Protection:PROPER EYE PROTECTION.  
Other Protective Equipment:AS REQUIRED BY YOUR COMPANY.  
Supplemental Safety and Health

### **Chemical Properties**

Boiling Pt:B.P. Text:300F/149C  
Vapor Pres:Spec Gravity:1.05  
Evaporation Rate & Reference:Solubility in Water:Percent Volatiles by Volume:

### **Stability**

Stability Indicator/Materials to Avoid:YES  
OXIDIZING MATERIAL CAN CAUSE A REACTION.  
Stability Condition to Avoid:AIR OR MOISTURE CAUSES POLYMERIZATION AND ACETIC ACID VAPORS ARE FORMED.  
Hazardous Decomposition Products:SILICON DIOXIDE,CARBON DIOXIDE,AND TRACES OF INCOMPLETELY BURNED CARBON PRODUCTS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.