

PRINTERS TOP PADDING CEMENT

MSDS Number

BBBJW

National Stock Number

6850-00B030039

Product Name

PRINTERS TOP PADDING CEMENT

Manufacturer

CHAMPION MFG CO

Product Identification

Product ID:PRINTERS TOP PADDING CEMENT

MSDS Date:11/18/1985

FSC:6850

NIIN:00B030039

MSDS Number: BBBJW

Responsible Party

CHAMPION MFG,CO.

425 W.32ND STREET

CHARLOTTE , NC 28206

US

Emergency Phone: 704333-3797

Info Phone: 704333-3797

Cage: DO838

Contractor

CHAMPION MFG,CO.

CHARLOTTE, NC 28206

US

704333-3797

Cage: DO838

Ingredients

DIBUTYL PHTHALATE (SARA III)

CAS: 84-74-2

RTECS: TI0875000

Fraction By Weight: 8.0%

OSHA PEL5 MG/M3

ACGIH TLV: 5 MG/M3; 9192

EPA Report Quantity: 10 LBS

DOT Report Quantity: 10 LBS

Hazards

Health Hazards Acute and Chronic:EYES-MAY CAUSE IRRITATION. SKIN-MAY BE IRRITATING ON CONTINUED OR PROLONGED CONTACT. DO NOT TAKE INTERNALLY.

Effects of Overexposure:SWALLOWING MAY CAUSE NAUSEA, DIZZINESS, OVEREXPOSURE TO HOT VAPORS OR MIST MAY CAUSE NOSE AND THROAT IRRITATION.

First Aid

First Aid:EYES:FLUSH WITH WATER FOR FIFTEEN MINUTES AND CALL PHYSICIAN.SKIN:WASH WITH SOAP AND WATER.IF INGESTED,INDUCE VOMITING AND CALL PHYSICIAN AT ONCE.

Fire Fighting

Extinguishing Media:FOAM,DRY CHEMICAL,WATER SPRAY,CO2
Fire Fighting Procedures:FIRE FIGHTERS SHOULD WEAR SELF CONTAINED BREATHING APPARATUS TO AVOID INHALATION OF SMOKE OR VAPORS IF MATERIAL IS INVOLVED IN GENERAL FIRE.
Unusual Fire/Explosion Hazard:NON-FLAMMABLE-/NONE KNOWN

Accidental Release

Spill Release Procedures:SMALL SPILL:CLEAN UP WITH WATER BY ALLOWING TO DRY OUT.FOR LARGE SPILL,DAM UP TO PREVENT SPREAD,VENTILATE AREA,SCOOP UP MATERIAL AND PLACE IN SUITABLE CONTAINER,AND WASH UP WITH WATER.

Handling

Handling and Storage Precautions:PREVENT FROM FREEZING--STORE BETWEEN 40-90 DEG F.KEEP CONTAINERS CLOSED TO PREVENT DRYING OUT AND MICROORGANISM CONTAMINATION.USE ADEQUATE VENTILATION
Other Precautions:USE WITH GOOD VENTILATION WHEN USING LARGE VOLUMES,USING IN SMALL AREA,OR IN SPRAYING.

Exposure Controls

Respiratory Protection:SHOULD BE WORN TO PREVENT INHALATION OF SPRAY MIST OR HEATED VAPORS.
Ventilation:LOCAL EXHAUST:RECOMMENDED TO CONTROL MIST OR VAPORS.
MECHANICAL:GENERAL VENTILATION FOR NORMAL USE.
Protective Gloves:CHEMICALLY RESISTANT RUBBER GLOVES
Eye Protection:GOGGLES
Other Protective Equipment:AS NEEDED TO PROTECT SKIN.
Work Hygienic Practices:USE WITH GOOD VENTILATION-AVOID PROLONGED OR REPEATED CONTACT WITH SKIN-AVOID CONTACT WITH EYES-DO NOT TAKE INTERNALLY.
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:212 DEG F
Vapor Pres:17.6
Vapor Density:.9976
Spec Gravity:1.02-1.08
Solubility in Water:YES
Appearance and Odor:LIQUID-WHITE OR COLORS (RED,BLUE,GREEN,YELLOW) MILD ODOR.

Stability

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:UNDER SEVERE THERMAL DEGRADATION-LOW MOLECULAR WEIGHT HYDROCARBON MAY BE FORMED.

Disposal

Waste Disposal Methods:INCINERATE OR BURY IN LOCAL LANDFILL IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.