

ATL-AIR TOOL LUBRICANT

MSDS Number

BBBJZ

National Stock Number

6850-00B030042

Product Name

ATL-AIR TOOL LUBRICANT

Manufacturer

COILHOSE PNEUMATICS

Product Identification

Product ID:ATL-AIR TOOL LUBRICANT MSDS Date:01/01/1987 FSC:6850 NIIN:00B030042 MSDS Number: BBBJZ

Responsible Party

COILHOSE PNEUMATICS

200 CLAY AVE

MIDDLESEX, NJ 08846

US

Emergency Phone: 201752-5000

Cage: 58277

Contractor

COILHOSE PNEUMATICS

MIDDLESEX, NJ 08846

US

908-752-5000 Cage: 58277

Ingredients

SOLVENT REFINED PARAFFINIC DISTILLATE PETROLEUM OIL

CAS: 64741-88-4 ACGIH TLV: 5 MG/M3

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic: SKIN AND EYE IRRITANT. INHALATION OF

OIL MIST CAUSES RESPIRATORY IRRITATION.

Effects of Overexposure: OVEREXPOSURE TO SKIN CAUSES DEFATTING.

First Aid

First Aid:IF INGESTED DO NOT INDUCE VOMITING.GET MEDICAL ATTENTION.SKIN CONTACT:FLUSH W/SOAP AND WATER.REMOVE CONTAMINATED CLOTHING & LAUNDER.EYE CONTACT:FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MIN.GET MEDICAL ATTENTION.INHALATION:REMOVE TO FRESH AIR.

Fire Fighting

Flash Point Method:COC Flash Point:141C 385F Lower Limits:1%



Upper Limits:6%

Extinguishing Media: CO2, DRY CHEMICAL, FOAM

Fire Fighting Procedures: USE SELF-CONTAINED BREATHING APPARATUS.

Accidental Release

Spill Release Procedures: ABSORB WITH SAND OR INERT MATERIAL. SWEEP OR SCOOP UP AND REMOVE. PREVENT SPREAD OF SPILL. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR MAY ENTER SEWERS, WATERCOURSES OR EXTENSIVE LAND AREAS.

Handling

Handling and Storage Precautions: AVOID PROLONGED OR REPEATED CONTACT WITH SKIN.WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING. AVOID BREATHING MIST OR VAPOR.

Other Precautions: KEEP CONTAINER CLOSED.DO NOT BREATHE DUST, VAPOR, MIST, GAS.DO NOT GET IN EYES, ON SKIN OR CLOTHING. WASH THOROUGHLY AFTER HANDLING.

Exposure Controls

Respiratory Protection: USE ONLY NIOSH APPROVED EQUIPMENT. FILTER

DUST, FUME, MIST UNDER MISTING CONDITIONS.

Ventilation: LOCAL EXHAUST TO CONTROL TO STANDARD.

Protective Gloves: NEOPRENE, POLYVINYL ALCOHOL

Eye Protection: GOGGLES

Other Protective Equipment: APRON Supplemental Safety and Health

Chemical Properties

Vapor Pres: Vapor Density: >12 Spec Gravity: 0.870@25/25C

Evaporation Rate & Reference: Solubility in Water: NEGLIGIBLE Appearance and Odor: PALE CLEAR LIQUID, PETROLEUM ODOR.

Stability

STRONG OXIDIZERS

Hazardous Decomposition Products: CARBON MONOXIDE MAY FORM UPON INCOMPLETE COMBUSTION.AVOID OPEN FLAMES.

Disposal

Waste Disposal Methods: ASSURE CONFORMITY W/APPLICABLE DISPOSAL REGULATIONS. DISPOSE OF ABSORBED MATERIAL AT AN APPROVED WASTE DISPOSAL SITE OR FACILITY.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.