

DIESEL FUEL 2

MSDS Number

BBBML

National Stock Number

9140-00B070004

Product Name

DIESEL FUEL 2

Manufacturer

GASCO GASOLINE INC

Product Identification

Product ID:DIESEL FUEL 2

MSDS Date:10/07/1985

FSC:9140

NIIN:00B070004

MSDS Number: BBBML

Responsible Party

GASCO GASOLINE INC.

OXNARD , CA 93032

US

Emergency Phone: 713-877-1400

Cage: 6W116

Contractor

GASCO GASOLINE INC

VENTURA, CA 93003-2060

US

805-654-8084/800-424-9300(CHEMTREC)

Cage: 6W116

Ingredients

COMPLEX MIXTURE OF PARAFFINIC,OLEFINIC,NAPHTHENIC AND

CAS: 68476-34-6

Fraction By Weight: >99%

OSHA PEL5

ACGIH TLV: 5

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:EYES:SLIGHT TO MODERATE EYE IRRITATION.SKIN:MODERATELY IRRITATING;CAUSES REDNESS,DRYING OF SKIN.INHALATION:IRRITATING TO MUCOUS MEMBRANES AND RESPIRATORY TRACT;HEADACHE,DIZZINESS,NAUSEA,VOMITING AND LOSS OF COORDINATION.INGESTION:DAMAGING TO LUNGS AND INTERNAL ORGANS. Effects of Overexposure:PROLONGED AND REPEATED SKIN CONTACT MAY CAUSE DERMATITIS.

First Aid

First Aid:EYE CONTACT:FLUSH WITH WATER FOR AT LEAST 15 MINUTES.SKIN CONTACT:REMOVE CONTAMINATED CLOTHING.WASH AFFECTED AREAS WITH SOAP AND WATER.INHALATION:REMOVE TO FRESH AIR.APPLY ARTIFICIAL RESPIRATION IF NOT BREATHING.INGESTION:DO NOT INDUCE VOMITING.IF

SPONTANEOUS VOMITING OCCURS,HOLD THE VICTIMS HEAD LOWER THAN HIPS TO PREVENT ASPIRATION.

Fire Fighting

Flash Point:> 125F (PM)

Lower Limits:0.6

Upper Limits:7.5

Extinguishing Media:DRY CHEMICAL CARBON,DIOXIDE,FOAM,AND WATER SPRAY.

Fire Fighting Procedures:USE A WATER SPRAY TO COOL FIRE-EXPOSED CONTAINERS.DO NOT USE A FORCED WATER STREAM DIRECTLY ON OIL FIRES,THIS WILL SCATTER FIRE.

Unusual Fire/Explosion Hazard:FLOWING OIL CAN BE IGNITED BY SELF-GENERATED STATIC ELECTRICITY;CONTAINERS SHOULD BE GROUNDED AND BONDED.

Accidental Release

Spill Release Procedures:REMOVE SOURCES OF HEAT OR IGNITION,INCLUDING INTERNAL COMBUSTION ENGINES AND POWER TOOLS.CLEAN UP SPILL BUT DO NOT FLUSH TO SEWER OR SURFACE WATER.AVOID BREATHING VAPORS OR MISTS.

Handling

Handling and Storage Precautions:STORE IN TIGHTLY CLOSED CONTAINERS IN A DRY,COOL PLACE,AWAY FROM SOURCES OF HEAT OR IGNITION.GROUND AND BOND ALL TRANSFER AND STORAGE EQUIPMENT.

Exposure Controls

Respiratory Protection:USE APPROVED RESPIRATORY PROTECTIVE EQUIPMENT FOR CLEANING LARGE SPILLS OR ENTRY INTO LARGE TANKS,VESSELS OR OTHER CONFINED SPACES.

Ventilation:PROVIDE ADEQUATE VENTILATION TO KEEP MIST OR VAPORS BELOW ALLOWABLE EXPOSURE LEVELS.

Protective Gloves:WEAR IMPERVIOUS GLOVES TO PROTECT SKIN.

Eye Protection:SAFETY GLASSES OR GOGGLES

Work Hygienic Practices:WASH HANDS THOROUGHLY WITH SOAP AND WATER.

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:340-675 F

Vapor Pres:20 C:1.6

Vapor Density:(AIR=1):8

Spec Gravity:0.87

Evaporation Rate & Reference:0.01

Solubility in Water:INSOLUBLE

Appearance and Odor:CLEAR TO LIGHT AMBER.MILD PETROLEUM ODOR.

Stability

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE,SULFUR DIOXIDE AND HYDROCARBONS.

Disposal

Waste Disposal Methods:DISPOSE THROUGH A LICENSED WASTE DISPOSAL COMPANY.FOLLOW FEDERAL,STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.