

GLIDDEN WALL CONDITIONER

MSDS Number

BBBMQ

National Stock Number

6850-00B070008

Product Name

GLIDDEN WALL CONDITIONER

Manufacturer

SCM GLIDDEN COATINGS AND RESINS DIV

Product Identification

Product ID:GLIDDEN WALL CONDITIONER

MSDS Date:11/03/1987

FSC:6850

NIIN:00B070008

MSDS Number: BBBMQ

Responsible Party

SCM GLIDDEN COATINGS&RESINS DIVISION

925 EUCLID AVENUE

CLEVELAND , OH 44115

US

Emergency Phone: 216826-5566

Cage: DO862

Contractor

SCM GLIDDEN COATINGS&RESINS DIVISION

15049

CLEVELAND, OH 44115

US

216-344-8000

Cage: DO862

Ingredients

GLYCOLS,POLYETHYLENE,MONO

CAS: 9036-19-5

RTECS: MN0907600

Fraction By Weight: 1%

KAOLIN

CAS: 1332-58-7

RTECS: GF1670500

Fraction By Weight: 8%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 2 MG/M3 TDUST; 9293

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Effects of Overexposure:IRRITATION OF EYES,SKIN,RESPIRATORY TRACT.

First Aid

First Aid:REMOVE TO FRESH AIR.RESTORE AND SUPPORT CONTINUED BREATHING.GET MEDICAL ATTENTION.SKIN CONTACT:WASH OFF QUICKLY W/PLENTY OF WATER,THEN SOAP AND WATER;REMOVE CONTAMINATED CLOTHING.WASH CONTAMINATED CLOTHING BEFORE RE-USE.EYE CONTACT:FLUSH IMMEDIATELY W/LARGE AMOUNTS OF WATER,ESPECIALLY UNDER LIDS FOR AT LEAST 15 MIN.GET MEDICAL TREATMENT.INGESTION:IF SWALLOWED,GET MEDICAL ATTEN.

Fire Fighting

Flash Point:ABOVE 200 F
Extinguishing Media:DRY CHEMICAL OR FOAM
Fire Fighting Procedures:WATER MAY BE USED TO COOL AND PROTECT EXPOSED CONTAINERS.
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:COMPLY WITH ALL APPLICABLE HEALTH AND ENVIRONMENTAL REGULATIONS.VENTILATE AREA.SPILLS MAY BE PICKED UP W/ABSORBENT MATERIAL.LARGE SPILLS:SHUT OFF LEAK IF SAFE TO DO SO.DIKE AND CONTAIN SPILL.PUMP TO STORAGE OR SALVAGE VESSELS.RINSE WATER OUT OF SEWER

Handling

Handling and Storage Precautions:STORE BELOW 100 F.
Other Precautions:USE ONLY W/ADEQUATE VENTILATION.DO NOT TAKE INTERNALLY.KEEP OUT OF REACH OF CHILDREN.AVOID CONTACT W/SKIN AND EYES,AND BREATHING OF VAPORS.WASH HANDS THOROUGHLY AFTER HANDLING.KEEP CONTAINERS CLOSED AND UPRIGHT.

Exposure Controls

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATORS IN ACCORDANCE W/OSHA STANDARD 29 CFR 1910.134.
Ventilation:PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST TO PREVENT BUILD-UP OF VAPORS.
Protective Gloves:IMPERVIOUS GLOVES
Eye Protection:SAFETY GLASSES OR GOGGLES
Other Protective Equipment:EYE WASH,SAFETY SHOWER
Work Hygienic Practices:WASH HANDS AFTER HANDLING,ESPECIALLY BEFORE SMOKING AND EATING.
Supplemental Safety and Health
EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUE.WEAR A DUST MASK TO AVOID BREATHING OF SANDING DUST.

Chemical Properties

Percent Volatiles by Volume:85.36

Stability

Stability Indicator/Materials to Avoid:YES
OXIDIZERS,REDUCING AGENTS
Stability Condition to Avoid:ELEVATED TEMPERATURES
Hazardous Decomposition Products:CARBON MONOXIDE,CARBON DIOXIDE

Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS.AVOID DISCHARGE TO NATURAL WATERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.