

TRU-TEST SUPREME WOODSMAN WOODSTAIN

MSDS Number

BBBMR

National Stock Number

8010-00B070009

Product Name

TRU-TEST SUPREME WOODSMAN WOODSTAIN

Manufacturer

GENERAL PAINT AND CHEMICAL

Product Identification

Product ID:TRU-TEST SUPREME WOODSMAN WOODSTAIN

MSDS Date:01/24/1985

FSC:8010

NIIN:00B070009

MSDS Number: BBBMR

Responsible Party

GENERAL PAINT&CHEMICAL

201 JANDUS ROAD

CARY , IL 60013

US

Emergency Phone: 312639-5383

Info Phone: SAME

Cage: DO863

Contractor

GENERAL PAINT&CHEMICAL

CARY, IL 60013

US

SAME

Cage: DO863

Ingredients

MINERAL SPIRITS

CAS: 64742-88-7

Fraction By Weight: 59%-62%

OSHA PEL500

ACGIH TLV: 100 PPM

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Effects of Overexposure:SEVERE EYE IRRITATION,DRYING OF SKIN,EXCESSIVE INHALATION,CAUSES HEADACHE,DIZZINESS AND NAUSEA.

Medical Cond Aggravated by Exposure:NONE KNOWN TO GENERAL PAINT AND CHEMICAL COMPANY.

First Aid

First Aid:EYE AND SKIN:WASH WITH FRESH WATER.WASH SKIN WITH WARM WATER AND SOAP.INHALATION:REMOVE TO FRESH AIR.APPLY ARTIFICIAL RESPIRATION IF NECESSARY.GET MEDICAL ATTENTION.INGESTION:DO NOT INDUCE VOMITING.KE EP PERSON WARM AND QUIET.GET MEDICAL ATTENTION.

Fire Fighting

Flash Point:105F

Lower Limits:0.9

Extinguishing Media:FOAM,CO2,DRY CHEMICAL,WATER FOG

Fire Fighting Procedures:TREAT AS A VOLATILE LIQUID FIRE.WATER SPRAY MAY BE INEFFECTIVE.IF WATER SPRAY IS USED,FOG NOZZLES ARE PREFERABLE.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.ISOLATE FROM HEAT,SPARKS AND OPEN FLAME.

Accidental Release

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES.CONTAIN SPILL,ABSORB LIQUID WITH CLAY,SAND OR FLOOR ABSORBENT.PREVENT RUN-OFF TO SEWERS,STREAMS OR OTHER BODIES OF WATER.

Handling

Handling and Storage Precautions:KEEP AWAY FROM HEAT,SPARKS AND OPEN FLAMES.

Other Precautions:DO NOT TAKE INTERNALLY.AVOID PROLONGED CONTACT WITH SKIN.CONTAINERS SHOULD BE GROUNDED WHEN POURING.AVOID FREE FALL OF MORE THAN 2-3 INCHES WHEN POURING.

Exposure Controls

Respiratory Protection:NIOSH/MSHA JOINTLY APPROVED AIR SUPPLIED RESPIRATOR IF TLV LIMITS ARE EXCEEDED.APPROVED MECHANICAL FILTER TO REMOVE SOLID AIRBORNE PARTICLES OF OVERSPRAY DURING SPRAY APPLICATION.

Ventilation:PROVIDE SUFFICIENT MECHANICAL(GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV.

Protective Gloves:REQUIRED TO PREVENT PROLONGED CONTACT.

Eye Protection:RECOMMENDED.

Other Protective Equipment:IMPERVIOUS CLOTHING AND BOOTS ARE SUGGESTED TO PREVENT PROLONGED OR REPEATED SKIN CONTACT.

Work Hygienic Practices:WASH HANDS BEFORE EATING,SMOKING OR USING BATHROOM.DO NOT REUSE CONTAMINATED CLOTHING.

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:300-380F

Vapor Density:HEAVIER

Evaporation Rate & Reference:SLOWER THAN ETHER

Stability

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:ISOLATE FROM HEAT AND OPEN FIRE.

Hazardous Decomposition Products:CARBON DIOXIDE AND CARBON MONOXIDE FROM BURNING.

Disposal

Waste Disposal Methods:CONTAMINATED ABSORBENT MAY BE DEPOSITED IN A LANDFILL IN ACCORDANCE W/LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.