

TRU-TEST SUPREME EZ-KARE FLAT ENAMEL BAMBOO

MSDS Number

BBBNS

National Stock Number

8010-00B070031

Product Name

TRU-TEST SUPREME EZ-KARE FLAT ENAMEL BAMBOO

Manufacturer

GENERAL PAINT AND CHEMICAL COMPANY

Product Identification

Product ID:TRU-TEST SUPREME EZ-KARE FLAT ENAMEL BAMBOO

MSDS Date:03/03/1987

FSC:8010

NIIN:00B070031

MSDS Number: BBBNS

Responsible Party

GENERAL PAINT&CHEMICAL COMPANY

201 JANDUS ROAD

CARY , IL 60013

US

Emergency Phone: 312639-5383

Info Phone: SAME

Cage: DO863

Contractor

GENERAL PAINT&CHEMICAL

CARY, IL 60013

US

SAME

Cage: DO863

Ingredients

"NO HAZARDOUS INGREDIENTS"

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Effects of Overexposure:INHALATION:VAPORS OR SPRAYMISTS MAY BE IRRITATING TO EYES,NOSE,THROAT AND MUCOUS MEMBRANES OF RESPIRATORY TRACT.SKIN CONTACT:MAY CAUSE SKIN IRRITATION.EYE CONTACT:DIRECT EYE CONTACT WITH PAINT WILL RE SULT IN IRRITATION.

Medical Cond Aggravated by Exposure:NONE KNOWN TO GENERAL PAINT&CHEMICAL CO.

First Aid

First Aid:INHALATION:REMOVE TO FRESH AIR.SKIN CONTACT:REMOVE WITH SOAP AND WATER.REMOVE CONTAMINATED CLOTHING AND WASH BEFORE REUSE.EYE CONTACT:FLUSH IMMEDIATELY W/LARGE AMTS.OF WATER.SEE PHYSICIAN FOR MEDICAL TREATMENT.INGESTION:GIVE 1 OR 2 GLASSESOF WATER TO DILUTE.DO NOT INDUCE VOMITING.CALL PHYSICIAN IMMEDIATELY.

Fire Fighting

Extinguishing Media:CO2,DRY CHEMICAL,WATER FOG.

Fire Fighting Procedures:WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP AND EXPLOSION WHEN EXPOSED TO EXTREME HEAT.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:DIKE AND CONTAIN SPILL W/INERT MATERIAL(SAND,EARTH,ETC.).TRANSFER THE LIQUID TO CONTAINERS FOR RECOVERY OR DISPOSAL.KEEP SPILL OUT OF SEWERS AND OPEN BODIES OF WATER.

Handling

Handling and Storage Precautions:KEEP FROM FREEZING.AVOID PROLONGED CONTACT WITH SKIN.DO NOT TAKE INTERNALLY.

Exposure Controls

Respiratory Protection:WHEN BRUSHED OR ROLLED ON NONE REQUIRED IF GOOD VENTILATION IS MAINTAINED.SPRAY APPLICATION REQUIRES MECHANICAL FILTER RESPIRATOR TO REMOVE AIRBORNE PARTICLES IF OVERSPRAY.

Ventilation:SUFFICIENT VENTILATION SHOULD BE PROVIDED TO KEEP THE AIR CONTAMINATE CONCENTRATION BELOW OSHA PEL AND TLV LIMITS.

Eye Protection:SAFETY GLASSES W/SPLASH GUARDS

Other Protective Equipment:EYEWASH FACILITY,PROTECTIVE CLOTHING TO AVOID EXCESSIVE SKIN CONTACT.

Work Hygienic Practices:WASH HANDS BEFORE EATING,SMOKING OR USING WASHROOM.

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:212F

Vapor Density:Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:VARIES WITH COLOR

Stability

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:EXPOSURE TO HIGH HEAT OR FIRE.

Disposal

Waste Disposal Methods:LIQUID MATERIAL AND CONTAMINATED DIKING MATERIAL SHOULD BE LANDFILLED ACCORDING TO CURRENT LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.