

UMBRELLA WATERPROOFING WP-48

MSDS Number

BBBPW

National Stock Number

6850-00B110007

Product Name

UMBRELLA WATERPROOFING WP-48

Manufacturer

KLEAN STRIP

Product Identification

Product ID:UMBRELLA WATERPROOFING WP-48

MSDS Date:01/01/1987

FSC:6850

NIIN:00B110007

MSDS Number: BBBPW

Responsible Party

KLEAN STRIP

2105 CHANNEL AVENUE

MEMPHIS , TN

US

Emergency Phone: 901-775-0100

Info Phone: 901-775-0100

Cage: DO874

Contractor

KLEAN-STRIP DIV BARR W M AND CO

1879

MEMPHIS, TN 38114

US

901-775-0100

Cage: 25451

Ingredients

MINERAL SPIRITS

CAS: 64741-41-9

Fraction By Weight:

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

OXALUMINIUM STEARATE

Fraction By Weight:

MINERAL SPIRITS

CAS: 8032-32-4

Fraction By Weight: 40%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

POLYVIS POLYBUTENE

Fraction By Weight:

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:INHALATION:SEVERE OVEREXPOSURE MAY CAUSE ANESTHESIA,HEADACHE,DIZZINESS,NAUSEA AND IRRITATION OF RESPIRATORY TRACT.INGESTION:MAY CAUSE ANESTHESIA,HEADACHE,DIZZINESS,NAUSEA AND GASTROINTESTINAL IRRITATION.SKIN&EYE CONTACT MAY CAUSE IRRITATION.

Effects of Overexposure:PROLONGED OR REPEATED CONTACT MAY CAUSE DERMATITIS.REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OVEREXPOSURE TO SOLVENTS WITH NEUROLOGICAL AND OTHER PHYSIOLOGICAL DAMAGE.

First Aid

First Aid:INHALATION:IF BREATHING IS DIFFICULT,MOVE PERSON TO AIR FREE OF VAPORS,ADMINISTER OXYGEN OR ARTIFICIAL RESPIRATION UNTIL MEDICAL ASSISTANCE CAN BE RENDERED.INGESTION:DO NOT INDUCE VOMITING.CALL YOUR POISON CONTROL CENTER,HOSPITAL EMERG ROOM OR PHYSICIAN IMMEDIATELY.SKIN CONTACT:WASH W/SOAP AND WATER.EYE CONTACT:FLUSH W/LARGE QUANT OF WATER FOR 15 MIN.IF IRRITATION PERSISTS GET MEDICAL ATTN.

Fire Fighting

Flash Point:90F

Lower Limits:1.0

Extinguishing Media:CARBON DIOXIDE,DRY POWDER,FOAM

Fire Fighting Procedures:SELF-CONTAINED RESPIRATORY PROTECTION SHOULD BE PROVIDED FOR FIREFIGHTERS IN BUILDINGS OR CONFINED AREAS.KEEP STORAGE CONTAINERS COOL WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:KEEP CONTAINER TIGHTLY CLOSED. ISOLATE FROM HEAT AND HOT SURFACES.

Accidental Release

Spill Release Procedures:AVOID BREATHING VAPORS.VENTILATE AREA.FLUSH LARGE SPILLS INTO SUITABLE RETAINING AREA OR CONTAINERS W/LARGE QUANTITIES OF WATER.SMALL SPILLS CAN BE ABSORBED BY APPROPRIATE INERT ABSORBENT.

Exposure Controls

Respiratory Protection:FOR OSHA CONTROLLED WORK PLACE,USE ONLY W/ADEQUATE VENTILATION.FOR OCCASIONAL USE,WEAR NIOSH APPROVED RESPIRATORS.FOR OCCASIONAL CONSUMER USE,USE ONLY W/ADEQUATE VENTILATION.

Ventilation:ADEQUATE VENTILATION.

Protective Gloves:IMPERMEABLE GLOVES

Eye Protection:SAFETY GLASSES,CHEMICAL GOGGLES

Other Protective Equipment:IMPERMEABLE APRONS

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:310F

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:60

Stability

Stability Indicator/Materials to Avoid:YES

Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/APPLICABLE LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.