

KLEAN STRIP AEROSOL PAINT REMOVER

MSDS Number

BBBQB

National Stock Number

6850-00B110011

Product Name

KLEAN STRIP AEROSOL PAINT REMOVER

Manufacturer

KLEAN STRIP DIV OF W M BARR AND COMPANY

Product Identification

Product ID:KLEAN STRIP AEROSOL PAINT REMOVER

MSDS Date:01/01/1987

FSC:6850

NIIN:00B110011

MSDS Number: BBBQB

Responsible Party

KLEAN-STRIP DIVISION OF W.M.BARR & COMPANY

2105 CHANNEL AVENUE

MEMPHIS , TN 38113

US

Info Phone: 901-775-0100

Cage: DO875

Contractor

KLEAN-STRIP DIVISION OF W.M.BARR & COMPANY

1879

MEMPHIS, TN 38113

US

901-775-0100

Cage: DO875

Ingredients

METHYLENE CHLORIDE (SARA III)

CAS: 75-09-2

RTECS: PA8050000

Fraction By Weight: 90%

OSHA PEL500 PPM/C,1000; Z2

ACGIH TLV: 50 PPM, A2; 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

METHYL ALCOHOL (METHANOL) (SARA III)

CAS: 67-56-1

RTECS: PC1400000

Fraction By Weight: 05%

OSHA PELs,200PPM/250STEL
ACGIH TLV: S,200PPM/250STEL; 93
EPA Report Quantity: 5000 LBS
DOT Report Quantity: 5000 LBS

NONYLPHENOXYPOLYETHOXYETHANOL
CAS: 9016-45-9
RTECS: MD0905000
Fraction By Weight: 05%

CARBON DIOXIDE
CAS: 124-38-9
RTECS: FF6400000
Fraction By Weight: 05%
OSHA PEL5000 PPM
ACGIH TLV: 5000PPM/30000STEL;93

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:LONG TERM EFFECTS OF OVEREXPOSURE MAY RESULT IN SKIN IRRITATION ON PROLONGED OR REPEATED CONTACT.
METHYLENE CHLORIDE HAS CAUSED CANCER IN CERTAIN LAB ANIMAL TESTS.
RISK TO HEALTH DEPENDS ON LEVEL AND DURATION OF EXPOSURE.
Effects of Overexposure:INHALATION-MAY CAUSE
HEADACHE,DIZZINESS,STUPOR,NAUSEA & VOMITING. SEVERE OVEREXPOSURE MAY CAUSE INCOORDINATION,UNCONSCIOUSNESS AND DEATH. INTENTIONAL OVER-INHALATION MAY CAUSE DEATH. MAY IRRITATE SKIN OR EYES.
INGESTION MAY CAUSE GASTROINTESTINAL IRRITATION. MAY BE HARMFUL OR FATAL IF INGESTED.
Medical Cond Aggravated by Exposure:DISEASES OF THE
EYES,SKIN,BLOOD,LIVER,KIDNEYS,LUNGS AND CENTRAL NERVOUS SYSTEM,MAY BE AGGRAVATED BY OVEREXPOSURE.

First Aid

First Aid:INHALATION-IF USER EXPERIENCES BREATHING DIFFICULTY,MOVE TO AIR FREE OF VAPORS. ADMINISTER OXYGEN OR ARTIFICIAL RESPIRATION UNTIL MEDICAL ASSISTANCE ARRIVES. INGESTION-CALL HOSP. EMER. ROOM,POISON CON TROL CENTER OR DR. IMMEDIATELY. SKIN-WASH WITH SOAP/WATER. EYES-FLUSH WITH LOTS OF WATER FOR 15 MIN. SEEK IMMEDIATE MEDICAL ATTENTION.

Fire Fighting

Extinguishing Media:CARBON DIOXIDE,DRY POWDER OR FOAM
Fire Fighting Procedures:SELF-CONTAINED RESPIRATORY PROTECTION SHOULD BE PROVIDED FOR FIREFIGHTERS IN BUILDINGS OR CONFINED AREAS.
Unusual Fire/Explosion Hazard:ISOLATE FROM HEAT AND HOT SURFACES.
CONTENTS UNDER PRESSURE. DO NOT PUNCTURE,INCINERATE OR STORE ABOVE 120F. EXPOSURE TO HEAT MAY CAUSE BURSTING.

Accidental Release

Spill Release Procedures:AVOID BREATHING VAPORS. VENTILATE AREA,FLUSH LARGE SPILLS OF MATERIAL INTO SUITABLE RETAINING AREA OR CONTAINERS WITH LARGE QUANTITIES OF WATER. SMALL SPILLS CAN BE ABSORBED BY APPROPRIATE INERT ABSOR BENT.

Handling

Handling and Storage Precautions:DO NOT STORE NEAR FLAMES OR AT

ELEVATED TEMPERATURES.
Other Precautions:PROLONGED EXPOSURE TO SUN MAY CAUSE BURSTING. STORAGE CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT COOL WITH WATER SPRAY TO PREVENT PRESSURE BUILD-UP.

Exposure Controls

Respiratory Protection:FOR OSHA CONTROLLED WORK PLACE, USE ONLY WITH ADEQUATE VENTILATION UNDER ENGINEERED AIR CONTROL SYSTEMS DESIGNED TO PROVIDE MAXIMUM TLV. FOR OCCASIONAL USE WHERE ENGINEERED AIR CONTROL ISN'T FEASIBLE, USE NIOSH APPROVED RESPIRATORS.

Ventilation:ADEQUATE VENTILATION MUST BE PROVIDED.

Protective Gloves:USE IMPERMEABLE GLOVES TO PRVNT SKN IRRI

Eye Protection:SAFETY GLASSES,CHEM GOGGLES OR FACESHIEL

Other Protective Equipment:VARYING APPLICATION METHODS CAN DICTATE USE OF ADDITIONAL PROTECTIVE SAFETY EQUIPMENT,SUCH AS IMPERMEABLE APRONS,ETC.

Supplemental Safety and Health

FOR OCCASIONAL CONSUMER USE,USE ONLY WITH ADEQUATE VENTILATION. READ CAREFULLY ALL INSTRUCTIONS ON LABEL BEFORE USE. DISPOSE OF EMPTY CONTAINER ACCORDING TO LOCAL REGULATIONS.

Chemical Properties

Boiling Pt:B.P. Text:140-148F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:95.0

Stability

Stability Indicator/Materials to Avoid:YES

AVOID STRONG OXIDIZING AGENTS.

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.