



UMBRELLA SEALER

MSDS Number

BBBQC

National Stock Number

8030-00B110012

Product Name

UMBRELLA SEALER

Manufacturer

KLEAN STRIP DIV OF W M BARR AND COMPANY

Product Identification

Product ID:UMBRELLA SEALER

MSDS Date:01/01/1987

FSC:8030

NIIN:00B110012

MSDS Number: BBBQC

Responsible Party

KLEAN-STRIP DIVISION OF W.M.BARR & COMPANY

2105 CHANNEL AVENUE

MEMPHIS , TN 38113

US

Info Phone: 901-775-0100

Cage: DO875

Contractor

KLEAN-STRIP DIVISION OF W.M.BARR & COMPANY

1879

MEMPHIS, TN 38113

US

901-775-0100

Cage: DO875

Ingredients

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 80%

OSHA PEL100 PPM

PROPRIETARY INGREDIENTS

Fraction By Weight: 20%

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:CHRONIC-PROLONGED OR REPEATED CONTACT MAY CAUSE DERMATITIS. REPORTS HAVE ASSOCIATED REPEATED & PROLONGED OVEREXPOSURE TO SOLVENTS WITH NEUROLOGICAL AND OTHER PHYSIOLOGICAL DAMAGE. ACUTE-SEVERE OVEREXP OSURE MAY CAUSE ANESTHESIA,HEADACHE,DIZZINESS,NAUSEA & IRRITATION OF RESPIRATORY



TRACT. MAY IRRITATE EYES AND SKIN.
Effects of Overexposure:INGESTION-MAY CAUSE
ANESTHESIA,HEADACHE,DIZZINESS,NAUSEA AND GASTROINTESTINAL
IRRITATION.
Medical Cond Aggravated by Exposure:NONE RECOGNIZED.

First Aid

First Aid:INHALATION-IF USER EXPERIENCES BREATHING DIFFICULTY,MOVE TO
AIR FREE OF VAPORS. ADMINISTER OXYGEN OR ARTIFICIAL RESPIRATION
UNTIL MEDICAL ASSISTANCE CAN BE RENDERED. DON'T INDUCE VOMITING.
CALL POISON CONTROL CTR,HOSP.EMERGENCY ROOM OR PHYSICIAN
IMMEDIATELY. SKIN-WASH WITH SOAP/WATER. EYES-FLUSH WITH WATER FOR
15 MIN. IF IRRITATION PERSISTS,GET MEDICAL ATTENTION.

Fire Fighting

Flash Point Method:SCC
Flash Point:101F
Lower Limits:1.0
Extinguishing Media:CARBON DIOXIDE,DRY POWDER OR FOAM
Fire Fighting Procedures:SELF-CONTAINED RESPIRATORY PROTECTION SHOULD
BE PROVIDED FOR FIREFIGHTERS IN BUILDINGS OR CONFINED AREAS.
Unusual Fire/Explosion Hazard:KEEP CONTAINER TIGHTLY CLOSED.ISOLATE
FROM HEAT AND HOT SURFACES.

Accidental Release

Spill Release Procedures:AVOID BREATHING VAPORS.VENTILATE AREA,FLUSH
LARGE SPILLS OF MATERIAL INTO SUITABLE RETAINING AREA OR CONTAINERS
WITH LARGE QUANTITIES OF WATER. SMALL SPILLS CAN BE ABSORBED BY
APPROPRIATE INERT ABSORB ENT.

Handling

Handling and Storage Precautions:DO NOT STORE NEAR FLAMES OR AT
ELEVATED TEMPERATURES.

Exposure Controls

Respiratory Protection:FOR OSHA CONTROLLED WORK PLACE,USE ONLY WITH
ADEQUATE VENTILATION UNDER ENGINEERED AIR CONTROL SYSTEMS DESIGNED
TO PROVIDE MAXIMUM TLV.FOR OCCASIONAL USE WHERE ENGINEERED AIR
CONTROL ISN'T FEASIBLE, U SE NIOSH APPROVED RESPIRATORS.
Ventilation:ADEQUATE VENTILATION MUST BE PROVIDED
Protective Gloves:USE IMPERMEABLE GLOVES TO PRVNT SKIN IRR
Eye Protection:SAFETY GLASSES,CHEM GOGGLES OR FACESHIEL
Other Protective Equipment:VARYING APPLICATION METHODS CAN DICTATE USE
OF ADDITIONAL PROTECTIVE SAFETY EQUIPMENT,SUCH AS IMPERMEABLE
APRONS,ETC.
Work Hygienic Practices:WASH HANDS THOROUGHLY AFTER USE.
Supplemental Safety and Health
FOR OCCASIONAL CONSUMER USE,USE ONLY WITH ADEQUATE VENTILATION.

Chemical Properties

Boiling Pt:B.P. Text:310-405F
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:60.0

Stability

Stability Indicator/Materials to Avoid:YES
AVOID STRONG OXIDIZING AGENTS
Hazardous Decomposition Products:NONE RECOGNIZED

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL,STATE AND
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,



expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.