https://msdsreport.com/msds/BBBQD

GILLESPIE OLD FURNITURE REFINISHER

MSDS Number

BBBQD

National Stock Number

6850-00B110013

Product Name

GILLESPIE OLD FURNITURE REFINISHER

Manufacturer

KLEAN STRIP DIV OF W M BARR AND COMPANY

Product Identification

Product ID:GILLESPIE OLD FURNITURE REFINISHER MSDS Date:01/01/1987 FSC:6850 NIIN:00B110013 MSDS Number: BBBQD

Responsible Party

KLEAN-STRIP DIVISION OF W.M.BARR & COMPANY

2105 CHANNEL AVENUE

MEMPHIS , TN 38113

US

Info Phone: 901-775-0100

Cage: DO875

Contractor

KLEAN-STRIP DIVISION OF W.M.BARR & COMPANY

1879

MEMPHIS, TN 38113

US

901-775-0100

Cage: DO875

Ingredients

ACETONE (SARA III) CAS: 67-64-1 RTECS: AL3150000 Fraction By Weight: 35 - 40% OSHA PEL1000PPM ACGIH TLV: 750PPM/1000STEL;9293 EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

METHANOL

CAS: 67-56-1 RTECS: PE1400000 Fraction By Weight: 25%

https://msdsreport.com/msds/BBBQD

•

OSHA PELS, 200PPM/250STEL ACGIH TLV: S,200PPM/250STEL; 93 EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

METHYLENE CHLORIDE (SARA III) CAS: 75-09-2 RTECS: PA8050000 Fraction By Weight: 25% OSHA PEL500 PPM/C,1000; Z2 ACGIH TLV: 50 PPM, A2; 9192 EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 20 - 25%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Health Hazards Acute and Chronic: ACUTE-MAY IRRITATE RESPIRATORY TRACT, CAUSE HEADACHE, DIZZINESS, STUPOR, NAUSEA AND ANESTHESIA. SEVERE OVEREXPOSURE MAY CAUSE INCOORDINATION, UNCONSCIOUSNESS AND DEATH. MAY CAUSE INCREASE IN CARBOXYHEMOGLOB IN LEVELS. CHRONIC-MAY CAUSE SKIN IRRITATION ON PROLONGED OR REPEATED CONTACT. Explanation of Carcinogenicity: METHYLENE CHLORIDE HAS CAUSED CANCER IN CERTAIN LABORATORY ANIMAL TESTS. RISK TO YOUR HEALTH DEPENDS ON LEVEL/DURATION.

Effects of Overexposure: MAY BE FATAL OR CAUSE

BLINDNESS, HEADACHE, DIZZINESS, STUPOR OR NAUSEA IF INGESTED. MAY IRRITATE SKIN AND EYES. REPORTS HAVE ASSOCIATED REPEATED OR PROLONGED OVEREXPOSURE TO SOLVENTS WITH NEUROLOGICAL AND OTHER PHYSIOLOGICAL DAMAGE.

Medical Cond Aggravated by Exposure: DISEASES OF THE SKIN, BLOOD, CENTRAL NERVOUS SYSTEM, EYES, LIVER, KIDNEYS AND LUNGS.

First Aid

First Aid: IF USER EXPERIENCES BREATHING DIFFICULTY, MOVE TO AIR FREE OF VAPORS. ADMINISTER OXYGEN OR ARTIFICIAL RESPIRATION UNTIL MEDICAL ASSISTANCE CAN BE RENDERED. IF INGESTED, CALL PHYSICIAN/POISON CONTROL CTR /HOSP. EMERGENCY ROOM IMMEDIATELY FOR INSTRUCTIONS TO INDUCE VOMITING. WASH SKIN WITH SOAP/WATER. FLUSH EYES WITH WATER FOR AT LEAST 15 MIN. AND SEEK IMMEDIATE MEDICAL ATTENTION.

Fire Fighting

Flash Point Method:CC Flash Point:6F SETA Lower Limits: 1.4 Extinguishing Media: CARBON DIOXIDE, DRY POWDER OR FOAM



Fire Fighting Procedures:SELF-CONTAINED RESPIRATORY PROTECTION SHOULD BE PROVIDED FOR FIREFIGHTERS IN BUILDINGS OR CONFINED AREAS. Unusual Fire/Explosion Hazard:KEEP CONTAINER TIGHTLY CLOSED. ISOLATE FROM HEAT,ELECTRICAL EQUIPMENT,SPARKS,OPEN FLAMES & HOT SURFACES. CONTACT WITH FLAMES MAY GENERATE TOXIC FUMES.

•

Accidental Release

Spill Release Procedures:AVOID BREATHING VAPORS. VENTILATE AREA, FLUSH LARGE SPILLS OF MATERIAL INTO SUITABLE RETAINING AREA OR CONTAINERS WITH LARGE QUANTITIES OF WATER. SMALL SPILLS CAN BE ABSORBED BY APPROPRIATE INERT ABSO RBENT.

Handling

Handling and Storage Precautions: DO NOT STORE NEAR FLAMES OR AT ELEVATED TEMPERATURES.

Exposure Controls

Respiratory Protection:FOR OSHA CONTROLLED WORK PLACE,USE ONLY WITH ADEQUATE VENTILATION UNDER ENGINEERED AIR CONTROL SYSTEMS DESIGNED TO PROVIDE MAXIMUM TLV.FOR OCCASIONAL USE WHERE ENGINEERED AIR CONTROL ISN'T FEASIBLE, U SE NIOSH APPROVED RESPIRATORS. Ventilation:ADEQUATE VENTILATION MUST BE PROVIDED. Protective Gloves:USE IMPERMEABLE GLOVES TO PRVNT SKN IRRI Eye Protection:SAFETY GLASSES,CHEM GOGGLES OR FACESHIEL Other Protective Equipment:VARYING APPLICATION METHODS CAN DICTATE USE OF ADDITIONAL PROTECTIVE SAFETY EQUIPMENT,SUCH AS IMPERMEABLE APRONS,ETC. Work Hygienic Practices:WASH HANDS THOROUGHLY AFTER USE. Supplemental Safety and Health

FOR OCCASIONAL CONSUMER USE, USE ONLY WITH ADEQUATE VENTILATION. DELIBERATE CONCENTRATION OR INHALATION CAN BE HARMFUL OR FATAL.

Chemical Properties

Boiling Pt:B.P. Text:135-230F Vapor Density:>AIR Evaporation Rate & Reference:SLOWER THAN ETHER

Stability

Stability Indicator/Materials to Avoid:YES AVOID STRONG OXIDIZING AGENTS. Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY PRODUCE HYDROGEN CHLORIDE AND SMALL QUANTITIES OF PHOSGENE Conditions to Avoid Polymerization:WILL NOT OCCUR

Disposal

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.