

902 FLOOR COVERING ADHESIVE

MSDS Number

BBBQY

National Stock Number

8040-00B130010

Product Name

902 FLOOR COVERING ADHESIVE

Manufacturer

MACLANBURG DUNCAN

Product Identification

Product ID:902 FLOOR COVERING ADHESIVE

MSDS Date:01/01/1988

FSC:8040

NIIN:00B130010

MSDS Number: BBBQY

Responsible Party

MACLANBURG-DUNCAN

15257 EASH PROCTOR AVENUE

INDUSTRY , CA 91745

US

Emergency Phone: 800424-9300

Info Phone: 818333-4578

Cage: DO881

Contractor

MACLANBURG-DUNCAN

INDUSTRY, CA 91745

US

818333-4578

Cage: DO881

Ingredients

VM&P NAPHTHA

CAS: 64742-89-8

Fraction By Weight:

OSHA PEL500 PPM

ACGIH TLV: 300 PPM

METHYL ALCOHOL (METHANOL) (SARA III)

CAS: 67-56-1

RTECS: PC1400000

Fraction By Weight:

OSHA PELS,200PPM/250STEL

ACGIH TLV: S,200PPM/250STEL; 93

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

AMINO ETHANOL

CAS: 34375-28-5

Fraction By Weight: .005%

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Effects of Overexposure:NO LONG TERM LABORATORY TEST TO DETERMINE EFFECTS.

First Aid

First Aid:EYES:MAY CAUSE SLIGHT IRRITATION.FLUSH WITH COLD WATER 10 TO 15 MINUTES.IF IRRITATION CONTINUES,CONSULT A PHYSICIAN.SKIN:MAY CAUSE SLIGHT IRRITATION.WASH WITH SOAP AND WATER OR HAND CLEANER.IF IRRITAT ION CONTINUES,CONSULT A PHYSICIAN.INHALATION:REMOVE TO FRESH AIR,ADMINISTER ARTIFICIAL RESPIRATION IF NECESSARY.INHALATION OF HIGH CONCENTRATIONS MAY ASPHYXiate.INGESTION:DO NOT INDUCE VOMITING.CALL P

Fire Fighting

Flash Point Method:TOC

Flash Point:200F

Extinguishing Media:CO2,CHEMICAL FOAM,DRY CHEMICAL,WATER FOG.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING GEAR WHEN IN CONFINED AREA.

Accidental Release

Spill Release Procedures:SCOOP INTO CONTAINER AND ALLOW TO DRY. PROVIDE ADEQUATE VENTILATION.

Handling

Handling and Storage Precautions:STORE INSIDE AT TEMPERATURE OF 60F-80F.KEEP CONTAINER CLOSED WHEN NOT IN USE.

Other Precautions:NONE

Exposure Controls

Respiratory Protection:NOT REQUIRED IF VENTILATION IS ADEQUATE.

Ventilation:MAINTAIN LOCAL VENTILATION BY OPENING WINDOWS OR USING ELECTRIC FAN.

Protective Gloves:NOT NORMALLY REQUIRED.

Eye Protection:NOT NORMALLY REQUIRED.

Other Protective Equipment:NONE.

Work Hygienic Practices:WASH WITH SOAP AND WATER OR WATERLESS HAND CLEANER AFTER EXPOSURE.

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:195-205F

Vapor Density:>THAN AIR

Spec Gravity:1.10

Evaporation Rate & Reference:1

Solubility in Water:COMPLETE

Appearance and Odor:LIGHT CREAM,SLIGHT LATEX ODOR.

Percent Volatiles by Volume:50-54%

Stability

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:EXCESSIVE HEAT OR COLD.

Hazardous Decomposition Products:WHEN TOTALLY DRY,MAY PRODUCE CO,H2O,CO2,NXO FROM BURNING OF AROMATIC HYDROCARBONS IN THIS PRODUCT.

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL LOCAL AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.