

CARPET ADHESIVE

MSDS Number

BBBSQ

National Stock Number

8040-00B160002

Product Name

CARPET ADHESIVE

Manufacturer

PARA CHEM SOUTHERN INC

Product Identification

Product ID:CARPET ADHESIVE MSDS Date: 09/23/1985 FSC:8040 NIIN:00B160002 MSDS Number: BBBSQ

Responsible Party

PARA-CHEM SOUTHERN, INC.

SIMPSONVILLE, SC 29681

US

Emergency Phone: 1803-967-7691

Cage: 15865 **Contractor**

PARA-CHEM SOUTHERN INC

127

SIMPSONVILLE, SC 29681

US

(803) 967-7691

Cage: 15865

Ingredients

VM&P NAPHTHA CAS: 64742-89-8

Fraction By Weight: 3%

OSHA PEL500 PPM ACGIH TLV: 300 PPM

ETHYLENE GLYCOL (SARA III)

CAS: 107-21-1

RTECS: KW2975000 Fraction By Weight: 2% OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM, VAPOR; 9192

EPA Report Quantity: 1 LB DOT Report Quantity: 1 LB



STYRENE, MONOMER (SARA III)

CAS: 100-42-5

RTECS: WL3675000

Fraction By Weight: 150% PPM

OSHA PEL100 PPM

ACGIH TLV: S,50PPM/100STEL;9293

EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

1,3-BUTADIENE (SARA III)

CAS: 106-99-0

RTECS: EI9275000

OSHA PEL1000 PPM

ACGIH TLV: 10 PPM; A2; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Effects of Overexposure:EYES-MAY CAUSE SLIGHT IRRITATION.SKIN:MAY CAUSE SLIGHT IRRITATION.INHALATION:MAY CAUSE IRRITATION TO THROAT,HEADACHE,NAUSEA,VOMITING,AND DIZZINESS.REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OVEREX PO.TO SOLVENTS WITH PERMANENT BRAIN ANDNERVOUS SYSTEM DAMAGE.MAY BE HARMFUL OR FATAL IF SWALLOWED OR INHALED.

First Aid

First Aid: EYES: FLUSH WITH WATER FOR 15 MINUTES. CALL PHYSICIAN IF IRRITATION OCCURS. INHALATION: MOVE PERSON TO FRESH AIR. IF BREATHING STOPS ADMINISTER ARTIFICIAL RESPIRATION. CALL PHYSICIAN. INGESTION: TO CONSCIOUS PERSON, GIVE TWO GLASSES OF WATER. INDUCEVOMITING, CALL PHYSICIAN IMMEDIATELY.

Fire Fighting

Extinguishing Media: WATER FOG, CO2, DRY CHEMICAL, AND CHEMICAL FOAM Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING GEAR WHEN FIRE FIGHTING IN CONFINED SPACES.

Accidental Release

Spill Release Procedures: DISPENSE SAND, SAWDUST, OR VERMICULITE. COLLECT AND PLACE IN WASTE CONTAINER. WASH AREA THOROUGHLY WITH WATER.

Handling

Handling and Storage Precautions: STORE ABOVE 40F.STORE IN WELL VENTILATED AREA.NEVER USE PRESSURE TO EMPTY.KEEP CLOSURE TIGHT AND CONTAINER UPRIGHT TO PREVENT LEAKAGE.

Other Precautions: DO NOT TAKE INTERNALLY.THIS PRODUCT AS SUPPLIED IS A LIQUID AND THERE ARE NO DUST HAZARDS FROM THE POWDERS IN IT. WHEN PRODUCT IS PROCESSED, POWDERS SHOULD BE ENCAPSULATED. THE USER MUST DETERMINE IF THE RE IS A DUST HAZARD BY THE PROCESS USED.

Exposure Controls

Respiratory Protection: NOT NORMALLY REQUIRED EXCEPT IF DRIED FILM IS BURNING. IF CONDITIONS EXIST WHERE PEL OR TLV MAY BE EXCEEDED, WEAR A NIOSH/MSHA APPROVED RESPIRATOR.



Ventilation: USE SUFFICIENT VENTILATION, IN VOLUME AND PATTERN, TO KEEP

AIR CONTAMINANT CONCENTRATION BELOW TLV OR PEL.

Protective Gloves:YES

Eye Protection: SPLASH GOGGLES

Work Hygienic Practices: WASH HANDS BEFORE EATING OR USING

WASHROOM.SMOKE IN SMOKING AREA ONLY.

Supplemental Safety and Health

ETHYLENE GLYCOL MAY CAUSE KIDNEY DAMAGE AND CENTRAL NERVOUS SYSTEM EFFECTS WITH OVEREXPOSURE OF 100% OF MATERIAL.STYRENE HAS BEEN SHOWN TO BE AN ANIMAL CARCINOGEN AND IS A HUMAN CARCINOGEN

SUSPECT.1,3 -BUTADIENE IS A HUMAN CARCINOGEN SUSPECT.

Chemical Properties

Boiling Pt:B.P. Text:212 Vapor Pres:SAME/H2O Vapor Density:SAME/H2O Spec Gravity:1.1

Evaporation Rate & Reference: WATER=11

Solubility in Water: COMPLETE

Appearance and Odor:LIGHT GREEN COLORED SEMI-LIQUID

Stability

Stability Indicator/Materials to Avoid:YES Hazardous Decomposition Products: DRIED MATERIAL MAY PRODUCE CO,CO2,H2O,NXO,AND OTHER PRODUCTS FROM THE BURNING OF AROMATIC HYDROCARBONS.

Disposal

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever. expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.