

NO.201-207 VULCANIZING FLUID

MSDS Number

BBBSX

National Stock Number

6850-00B180002

Product Name

NO.201-207 VULCANIZING FLUID

Manufacturer

REMACO INC

Product Identification

Product ID:NO.201-207 VULCANIZING FLUID

MSDS Date:01/20/1986

FSC:6850

NIIN:00B180002

MSDS Number: BBBSX

Responsible Party

REMACO,INC.

200 PARIS AVENUE

NORTHVALE , NJ 07647

US

Emergency Phone: 201768-8100(DAY)

Cage: DO900

Contractor

REMACO,INC.

NORTHVALE, NJ 07647

US

201-768-8100/800-424-9300(CHEMTREC)

Cage: DO900

Ingredients

TRICHLOROETHYLENE (SARA III)

CAS: 79-01-6

RTECS: KX4550000

Fraction By Weight: 100%

OSHA PEL100 PPM/100 STEL

ACGIH TLV: 50 PPM/100,A5STEL;93

EPA Report Quantity: 100 LBS

DOT Report Quantity: 100 LBS

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Effects of Overexposure:RESPIRATORY

IRRITATION,HEADACHE,DIZZINESS,CARDIAC

ARRYTHMIAS,UNCONSCIOUSNESS;CENTRAL NERVOUS SYSTEM

DEPRESSION.PROLONGED OR REPEATED SKIN CONTACT MAY LEAD TO

DRYING,IRRITATION AND DERMATITIS.POSSIBLE SKIN ABSORPTION.EYE

IRRITATION WITH REVERSIBLE DAMAGE.POSSIBLE LIVER OR KIDNEY DAMAGE.

First Aid

First Aid:EYES:IMMEDIATELY FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES WHILE HOLDING THE EYELIDS OPEN.GET MEDICAL ATTEN.SKIN:REMOVE CONTAMINATED CLOTHING.WASH SKIN THOROUGHLY WITH SOAP AND WATER.GET MEDICAL ATTENTION IF IRRITATIONPERSISTS.INHALATION:MOVE VICTIM TO FRESH AIR AND RESTORE BREATHING IF NECESSARY.STAY WITH VICTIM UNTIL ARRIVAL OF EMERGENCY MEDICAL PERSONNEL.

Fire Fighting

Flash Point:NONE
Lower Limits:8%
Upper Limits:10.5%
Extinguishing Media:CARBON DIOXIDE,DRY CHEMICAL,OR FOAM.
Fire Fighting Procedures:USE WATER SPRAY OR FOG TO COOL FIRE-EXPOSED CONTAINERS.
Unusual Fire/Explosion Hazard:AS WITH ANY CLOSED CONTAINER,EXTREME HEAT MAY CAUSE IT TO EXPLODE.

Accidental Release

Spill Release Procedures:WEAR PERSONAL PROTECTIVE EQUIPMENT.REMOVE HEAT AND IGNITION SOURCES;VENTILATE THE AREA;CLEAN UP WITH INERT ABSORBANT.

Handling

Handling and Storage Precautions:STORE IN CLOSED CONTAINER IN COOL,WELL-VENTILATED AREA.
Other Precautions:TRICHLOROETHYLENE HAS BEEN SHOWN TO CAUSE CANCER IN LABORATORY ANIMALS.ALCOHOL MAY ENHANCE THE EFFECTS OF TRICHLOROETHYLENE.NOTE TO PHYSICIAN:DO NOT USE ADRENALIN.PERSONS WITH LIVER AND/OR KIDNEY PROBLEMS SHOULD BE CLOSELY MONITORED.

Exposure Controls

Respiratory Protection:IF TLV IS EXCEEDED,OR FOR SYMPTOMS OF OVEREXPOSURE,WEAR A NIOSH-APPROVED RESPIRATOR FOR ORGANIC VAPORS.
Ventilation:LOCAL EXHAUST MAY BE NECESSARY UNDER SOME HANDLING/USE CONDITIONS.
Protective Gloves:WEAR CHEMICAL RESISTANT GLOVES.
Eye Protection:CHEMICAL SPLASH GOGGLES OR FACESHIELD.
Other Protective Equipment:CHEMICAL RESISTANT CLOTHING.
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:188
Vapor Pres:57.8
Vapor Density:4.6
Spec Gravity:1.45
Evaporation Rate & Reference:Solubility in Water:SLIGHT
Appearance and Odor:YELLOW LIQUID:MILDLY SWEET.ETHER-LIKE ODOR.
Percent Volatiles by Volume:>90

Stability

Stability Indicator/Materials to Avoid:YES
STRONG ALKALIES,OXIDIZERS
Stability Condition to Avoid:AVOID ALKALIES,OXIDIZERS
Hazardous Decomposition Products:HYDROGEN CHLORIDE,CARBON MONOXIDE,CARBON DIOXIDE,TRACES OF PHOSGENE AND CHLORINE.

Disposal

Waste Disposal Methods:WASTE MAY BE BURNED IN AN APPROVED INCINERATOR,OR DISPOSE OF ACCORDING TO LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.