

# **RUBBER BUFFER #71**

# **MSDS Number**

BBBSZ

# **National Stock Number**

6850-00B180004

### **Product Name**

RUBBER BUFFER #71

#### Manufacturer

REMACO INC

### **Product Identification**

Product ID:RUBBER BUFFER #71 MSDS Date:01/01/1987 FSC:6850 NIIN:00B180004

NIIN:00B180004 MSDS Number: BBBSZ

# **Responsible Party**

REMACO, INC.

200 PARIS AVENUE

NORTHVALE, NJ 07427

US

Emergency Phone: 201768-8100

Cage: DO900

Contractor

REMACO, INC.

NORTHVALE, NJ 07647

US

201-768-8100/800-424-9300(CHEMTREC)

Cage: DO900

Ingredients

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7 RTECS: ZE2100000

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6 RTECS: SE7555000 OSHA PEL100 PPM

### **Hazards**

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES



Health Hazards Acute and Chronic:PRIMARILY A CENTRAL NERVOUS SYSTEM DEPRESSANT.INHALATION CAN CAUSE IRRITATION OF THE RESPIRATORY TRACT,DIZZINESS,NAUSEA,HEADACHE,LOSS OF COORDINATION AND EQUILIBRIUM,UNCONSCIOUSNESS,AND EVEN DEATH IN CONFINED OR POOLY VENTILATED AREA.EYE CONTACT CAN RESULT IN IRRITATION,PAIN AND DISCOMFORT.

Effects of Overexposure: MAY DAMAGE THE LIVER AND KIDNEYS UPON PROLONGED OR REPEATED INHALATION OF VAPOR.PROLONGED OR REPEATED CONTACT WITH THE SKIN CAN CAUSE IRRITATION AND DERMATITIS.

#### First Aid

First Aid:INHALATION:REMOVE TO FRESH AIR.IF NOT BREATHING,GIVE ARTIFICIAL RESPIRATION,PREFERABLY MOUTH-TO-MOUTH.IF BREATHING IS DIFFICULT,GIVE OXYGEN.EYE CONTACT:FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MIN.I F IRRITATION OCCURS,CONSULT A PHYSICIAN.SKIN CONTACT:WASH SKIN WITH PLENTY OF SOAP AND WATER.SWALLOWING:IF CONSCIOUS,GIVE QUART OF WATER,INDUCE VOMITING.IF VOMITING CANNOT BE INDUCED,TAKE TO HOSPITAL.

# Fire Fighting

Flash Point Method:TCC

Flash Point:142 F

Extinguishing Media: WATER FOG, FOAM, CO2, DRY CHEMICAL. DO NOT USE DIRECT

STREAM WATER.

Fire Fighting Procedures: WEAR PRESSURE DEMAND SELF-CONTAINED BREATHING APPARATUS FOR POSSIBLE EXPOSURE TO HYDROGEN CHLORIDE AND PHOSGENE. Unusual Fire/Explosion Hazard: PERCHLOROETHYLENE INVOLVED IN FIRES CAN DECOMPOSE TO HYDROGEN CHLORIDE AND PHOSGENE.

## **Accidental Release**

Spill Release Procedures: EVACUATE AREA AND VENTILATE. CONTAIN SPILL WITH FLOOR ABSORBENT MATERIAL.

### Handling

Handling and Storage Precautions: DO NOT USE IN POORLY VENTILATED OR CONFINED SPACES. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. Other Precautions: DO NOT STORE IN UNLABELED OR MISLABELED CONTAINERS. DO NOT STORE DEGREASER, CLEAN-OUT SLUDGE IN TIGHTLY SEALED CONTAINERS. AVOID PROLONGED OR REPEATED BREATHING OF VAPOR.

# **Exposure Controls**

Respiratory Protection: NIOSH/MESA APPROVED ORGANIC VAPOR RESPIRATOR FOR CONCENTRATIONS BELOW 1000 PPM.FOR 1000 PPM AND ABOVE, USE AIR-SUPPLIED RESPIRATORY PROTECTION.

Ventilation:LOCAL EXHAUST PREFERRED.MECHANICAL (GENERAL) SUFFICIENT TO MAINTAIN BELOW TLV.

MAINTAIN BELOW ILV.

Protective Gloves: CHEMICAL RESISTANT Eye Protection: SPLASH PROOF GOGGLES

Other Protective Equipment: EYE WASH FOUNTAIN

Supplemental Safety and Health

AVOID CONTACT WITH EYES.AVOID PROLONGED OR REPEATED CONTACT WITH SKIN.DO NOT TAKE INTERNALLY.AVOID USE OF ADRENALIN IN ANY CASE WHERE A PERSON HAS BEEN OVERCOME BY PERCHLOROETHYLENE.

### **Chemical Properties**

Boiling Pt:B.P. Text:250 F Vapor Pres:APP.13. Vapor Density:APP.4.8 Spec Gravity:.967

Solubility in Water: NEGLIGIBLE

Appearance and Odor: WATER WHITE, PUNGENT ODOR.

Percent Volatiles by Volume: 100%

### Stability

 ${\bf Stability\ Indicator/Materials\ to\ Avoid:YES}$ 

NONE

Stability Condition to Avoid: OPEN FLAMES, HOT GLOWING SURFACES, ELECTRIC



ARCS, STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products: HYDROGEN CHLORIDE, TRACES OF PHOSGENE, CARBON MONOXIDE, UNIDENTIFIED ORGANICS.

# **Disposal**

Waste Disposal Methods: DISPOSE OF MATERIAL IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL LAWS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.