



SILICONE SEALANT

MSDS Number

BBBTH

National Stock Number

8030-00B180010

Product Name

SILICONE SEALANT

Manufacturer

RED DEVIL INCORPORATED

Product Identification

Product ID: SILICONE SEALANT

MSDS Date: 01/01/1988

FSC: 8030

NIIN: 00B180010

MSDS Number: BBBTH

Responsible Party

RED DEVIL INCORPORATED

WEBB STREET

PRYOR, OK 74362

US

Emergency Phone: 918825-5744

Cage: DO902

Contractor

RED DEVIL, INCORPORATED

A

PRYOR, OK 74361

US

918-825-5744

Cage: 23577

Ingredients

TITANIUM DIOXIDE (IN WHITE PRODUCT ONLY)-(AS NUISANCE

OSHA PEL15

ACGIH TLV: 10

SILICA (AS AMORPHOUS SILICA, TOTAL DUST)

OSHA PEL20

ACGIH TLV: 20

ETHYL TRIACETOXYSILANE-(AS ACETIC ACID)

OSHA PEL10

ACGIH TLV: 10

Hazards



Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Effects of Overexposure: EYE, NOSE AND THROAT IRRITATION. POSSIBLE SKIN IRRITATION.

First Aid

First Aid: EYES: IMMEDIATELY FLUSH EYES W/ LARGE AMOUNTS OF WATER WHILE HOLDING THE EYELIDS OPEN. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. SKIN: WIPE MATERIAL FROM SKIN WITH CLOTH OR PAPER TOWEL, THEN WASH EXPOSED AREA WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. INHALATION: MOVE VICTIM TO FRESH AIR. GET MEDICAL ATTENTION. INGESTION: CONTACT LOCAL POISON CONTROL CENTER OR PHYSICIAN IMMEDIATELY

Fire Fighting

Flash Point: > 200 F
Extinguishing Media: CARBON DIOXIDE OR FOAM
Fire Fighting Procedures: NO SPECIAL PROCEDURES REQUIRED.

Accidental Release

Spill Release Procedures: WEAR PERSONAL PROTECTIVE EQUIPMENT. CLEAN UP WITH ABSORBANT MATERIAL.

Handling

Handling and Storage Precautions: STORE IN CLOSED CONTAINER IN DRY AREA. NOTE: DO NOT WEAR CONTACT LENSES WHILE APPLYING THIS MATERIAL, AS ACETIC ACID VAPOR MAY BECOME TRAPPED IN LENSES.

Exposure Controls

Respiratory Protection: NOT NORMALLY REQUIRED. IF TLV IS EXCEEDED, OR FOR SYMPTOMS OF OVEREXPOSURE, WEAR A NIOSH-APPROVED RESPIRATOR FOR ORGANIC VAPORS.
Ventilation: LOCAL EXHAUST MAY BE NECESSARY UNDER SOME HANDLING/USE CONDITIONS.
Protective Gloves: NEOPRENE OR CHEMICAL RESISTANT IF NEEDED
Eye Protection: SAFETY GLASSES
Supplemental Safety and Health

Chemical Properties

Vapor Density: > 1
Spec Gravity: > 1
Solubility in Water: INSOLUBLE
Appearance and Odor: THICK LIQUID; SLIGHT VINEGAR ODOR.
Percent Volatiles by Volume:

Stability

Stability Indicator/Materials to Avoid: YES
MOISTURE WILL RELEASE ACETIC ACID VAPOR.
Stability Condition to Avoid: EXTREME HEAT
Hazardous Decomposition Products: SILICON DIOXIDE, CARBON MONOXIDE, CARBON DIOXIDE, TRACES OF FORMALDEHYDE.

Disposal

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.