

ACRYLIC TUB & TILE CAULK

MSDS Number

BBBTK

National Stock Number

8030-00B180012

Product Name

ACRYLIC TUB & TILE CAULK

Manufacturer

RED DEVIL INC

Product Identification

Product ID: ACRYLIC TUB & TILE CAULK

MSDS Date: 06/27/1990

FSC: 8030

NIIN: 00B180012

MSDS Number: BBBTK

Responsible Party

RED DEVIL INC

MID AMERICA INDUSTRIAL DISTRICT

PRYOR, OK 74361

US

Emergency Phone: 918-825-5744 (24 HRS)

Info Phone: 918-825-5744

Preparer: TIMOTHY J. COLLITON, CIH

Cage: 23577

Contractor

RED DEVIL, INCORPORATED

A

PRYOR, OK 74361

US

918-825-5744

Cage: 23577

Ingredients

NAPHTHA, MEDIUM ALIPHATIC

CAS: 64742-88-7

Fraction By Weight: 100%

CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS: 1317-65-3

RTECS: EV9580000

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9192

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

ETHYLENE GLYCOL (SARA III)

CAS: 107-21-1

RTECS: KW2975000

OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM,VAPOR; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

BUTYL BENZYL PHTHALATE (SARA III)

CAS: 85-68-7

RTECS: TH9990000

EPA Report Quantity: 100 LBS

DOT Report Quantity: 100 LBS

2-ETHOXYETHANOL (EGEE) (SARA III)

CAS: 110-80-5

RTECS: KK8050000

OSHA PELS,200 PPM

ACGIH TLV: S, 5 PPM; 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:NONE SPECIFIED BY MANUFACTURER.

Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT IS LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.

Effects of Overexposure:INHALATION OF DUST GENERATED FRMO DRIED PRODUCT MAY CAUSE RESPIRATORY IRRITATION. HIGH VAPOR CONCENTRATION SMAY PRODUCT HEADACHE, DIZZINESS, AND NAUSEA. EYE CONTACT CAUSES IRRITATION. PROLONGED OR REP EATED CONTACT MAY CAUSE MILD SKIN IRRITATION.

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF RESPIRATORY DISORDERS MAY BE AT INCREASED RISK FROM EXPOSURE.

First Aid

First Aid:EYES: IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER. GET MEDICAL ATTENTION IF IRRITATIO PERSISTS. SKIN: WIPE MATERIAL FROM SKIN WITH CLOTH OR PAPER TOWEL, THEN WASH EXPOSED AREA WITH SOAP AND WATER. I NHALATION: MOVE TO FRESH AIR. RESTORE/SUPPORT BREATHING IF NECESSARY. INGESTION: CONTACT LOCAL POISON CONTROL CENTER OR PHYSICIAN IMMEDIATELY!

Fire Fighting

Flash Point:175F,79C

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, OR FOAM.
Fire Fighting Procedures: USE WATER SPRAY OR FOG TO COOL FIRE-EXPOSED CONTAINERS.
Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures: WIPE UP SPILLED MATERIAL. WASH AREA WITH DETERGENT.
Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions: STORE IN A COOL, DRY, WELL VENTILATED AREA AWAY FROM SOURCES OF IGNITION. KEEP CONTAINER CLOSED WHEN NOT IN USE. PROTECT FROM PHYSICAL DAMAGE.
Other Precautions: STORE IN CLOSED CONTAINER IN COOL AREA. THIS PRODUCT CONTAINS BUTYL BENZYL WHICH HAS BEEN FOUND TO BE A PROBABLY CARCINOGEN FOR FEMALE RATS CAUSING AN INCREASED INCIDENCE OF LEUKEMIA.

Exposure Controls

Respiratory Protection: NOT NORMALLY REQUIRED. IF TLV IS EXCEEDED, OR FOR SYMPTOMS OF OVEREXPOSURE, WEAR A NIOSH-APPROVED RESPIRATORY FOR ORGANIC VAPORS.
Ventilation: PROVIDE ADEQUATE GENERAL DILUTION VENTILATION.
Protective Gloves: NEOPRENE OR CHEMICAL RESISTANT GLOVES.
Eye Protection: WEAR SAFETY GLASSES.
Other Protective Equipment: SAFETY SHOWER AND EYE BATH. INDUSTRIAL TYPE WORK CLOTHING AND APRON AS REQUIRED TO AVOID PROLONGED OR REPEATED CONTACT.
Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.
Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

Chemical Properties

HCC: V4
Vapor Density: >1
Spec Gravity: 1.53
pH: 8.0
Evaporation Rate & Reference: Solubility in Water: SLIGHT
Appearance and Odor: SMOOTH, BRIGHT WHITE PASTE; MILD LATEX ODOR.
Percent Volatiles by Volume: 18-19%

Stability

Stability Indicator/Materials to Avoid: YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid: AVOID EXTREME HEAT, OPEN FLAME.
Hazardous Decomposition Products: CARBON DIOXIDE AND CARBON MONOXIDE

Disposal

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.