

LATEX VELVET EXTERIOR FINISHES H 518

MSDS Number

BBBVP

National Stock Number

8010-00B190024

Product Name

LATEX VELVET EXTERIOR FINISHES H 518

Manufacturer

THE SHERWIN WILLIAMS COMPANY

Product Identification

Product ID:LATEX VELVET EXTERIOR FINISHES H 518

MSDS Date:01/01/1987

FSC:8010

NIIN:00B190024

MSDS Number: BBBVP

Responsible Party

THE SHERWIN-WILLIAMS COMPANY

101 PROSPECT AVE,N.W.

CLEVELAND , OH 44115

US

Emergency Phone: 216566-2917

Info Phone: 216566-2902

Cage: DO693

Contractor

THE SHERWIN-WILLIAMS CO

CLEVELAND, OH 44115

US

216-566-2902

Cage: DO693

Ingredients

ETHYLENE GLYCOL (SARA III)

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight:

OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM,VAPOR; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

SILICA, CRYSTALLINE - CRISTOBALITE

CAS: 14464-46-1

RTECS: VV7325000

Fraction By Weight:

OSHA PELSEE TABLE Z3

ACGIH TLV: 0.05 MG/M3 RDUST9293

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 0-25%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

NICKEL ANTIMONY TITANATE

CAS: 8007-18-9

Fraction By Weight: 5%

OSHA PEL0.50

ACGIH TLV: 0.50

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:IRRITATION OF EYES,SKIN AND UPPER RESPIRATORY SYSTEM.IN A CONFINED AREA VAPORS IN HIGH CONCENTRATION MAY CAUSE HEADACHE,NAUSEA OR DIZZINESS.

Effects of Overexposure:REDNESS AND ITCHING OR BURNING SENSATION,MAY INDICATE EYE OF EXCESSIVE SKIN EXPOSURE.

Medical Cond Aggravated by Exposure:NONE GENERALLY RECOGNIZED.

First Aid

First Aid:INHALATION:IF AFFECTED,REMOVE FROM EXPOSURE.RESTORE BREATHING.KEEP WARM AND QUIET.SKIN:WASH AFFECTED AREA THOROUGHLY WITH SOAP AND WATER.REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE RE-USE.EYES:FLU SH EYES W/LARGE AMOUNTS OF WATER FOR 15MINUTES.GET MEDICAL ATTEN.

Fire Fighting

Flash Point:199F

Extinguishing Media:CARBON DIOXIDE,DRY CHEMICAL,ALCOHOL FOAM

Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT INCLUDING SELF-CONTAINED BREATHING APPARATUS.WATER MAY BE INEFFECTIVE.IF WATER IS USED,FOG NOZZLES ARE PREFERABLE.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE (DUE TO THE BUILD-UP OF PRESSURE) WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION.VENTILATE AND REMOVE WITH INERT ABSORBENT.

Handling

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE.TRANSFER ONLY TO APPROVED CONTAINERS WITH COMPLETE AND APPROPRIATE LABELING.KEEP OUT OF REACH OF CHILDREN.

Exposure Controls

Respiratory Protection:IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW APPLICABLE LIMITS BY VENTILATION,WEAR A PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/MSHA FOR PROTECTION.
Ventilation:LOCAL EXHAUST PREFERABLE,GENERAL EXHAUST ACCEPTABLE.
Protective Gloves:RECOMMENDED

Eye Protection:SAFETY SPECTACLES W/UNPERFORATED SHIELDS

Work Hygienic Practices:WASH HANDS AFTER USING.
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:212-388 F
Vapor Density:>THAN AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:69-75

Stability

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:CARBON DIOXIDE,CARBON MONOXIDE

Disposal

Waste Disposal Methods:INCINERATE IN APPROVED FACILITY.DO NOT
INCINERATE CLOSED CONTAINER.DISPOSE OF IN ACCORDANCE WITH
FEDERAL,STATE AND LOCAL REGULATIONS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.