



SOLID COLOR LATEX STAIN N 102

MSDS Number

BBBWK

National Stock Number

8010-00B190041

Product Name

SOLID COLOR LATEX STAIN N 102

Manufacturer

THE SHERWIN WILLIAMS COMPANY

Product Identification

Product ID: SOLID COLOR LATEX STAIN N 102

MSDS Date: 01/01/1987

FSC: 8010

NIIN: 00B190041

MSDS Number: BBBWK

Responsible Party

THE SHERWIN-WILLIAMS COMPANY

101 PROSPECT AVE, N.W.

CLEVELAND, OH 44115

US

Emergency Phone: 216566-2917

Info Phone: 216566-2902

Cage: DO693

Contractor

THE SHERWIN-WILLIAMS CO

CLEVELAND, OH 44115

US

216-566-2902

Cage: DO693

Ingredients

ETHYLENE GLYCOL (SARA III)

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight:

OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM, VAPOR; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

MICA

CAS: 12003-38-2

Fraction By Weight:

ACGIH TLV: 3



TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 0-15%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:IRRITATION OF EYES,SKIN AND UPPER
RESPIRATORY SYSTEM.IN A CONFINED AREA VAPORS IN HIGH CONCENTRATION
MAY CAUSE HEADACHE,NAUSEA OR DIZZINESS.
Effects of Overexposure:REDNESS AND ITCHING OR BURNING SENSATION MAY
INDICATE EYE OR EXCESSIVE SKIN EXPOSURE.
Medical Cond Aggravated by Exposure:NONE GENERALLY RECOGNIZED.

First Aid

First Aid:INHALATION:IF AFFECTED,REMOVE FROM EXPOSURE.RESTORE
BREATHING.KEEP WARM AND QUIET.SKIN:WASH AFFECTED AREA THOROUGHLY
WITH SOAP AND WATER.REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE
RE-USE.EYES:FLU SH EYES W/LARGE AMOUNTS OF WATER FOR 15MINUTES.GET
MEDICAL ATTEN.

Fire Fighting

Flash Point Method:PMCC
Flash Point:> 199 F
Extinguishing Media:CARBON DIOXIDE,DRY CHEMICAL,ALCOHOL FOAM
Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT INCLUDING
SELF-CONTAINED BREATHING APPARATUS.WATER MAY BE INEFFECTIVE.IF
WATER IS USED,FOG NOZZLES ARE PREFERABLE.
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE (DUE TO THE
BUILD-UP OF PRESSURE) WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION.VENTILATE AND
REMOVE WITH INERT ABSORBENT.

Handling

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN
USE.TRANSFER ONLY TO APPROVED CONTAINERS WITH COMPLETE AND
APPROPRIATE LABELING.KEEP OUT OF REACH OF CHILDREN.

Exposure Controls

Respiratory Protection:IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW
APPLICABLE LIMITS BY VENTILATION,WEAR A PROPERLY FITTED ORGANIC
VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/MSHA FOR PROTECTION.
Ventilation:LOCAL EXHAUST PREFERABLE,GENERAL EXHAUST ACCEPTABLE.
Protective Gloves:RECOMMENDED
Eye Protection:SAFETY SPECTACLES W/UNPERFORATED SHIELDS
Work Hygienic Practices:WASH HANDS AFTER USING.
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:212-388 F
Vapor Density:>THAN AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:61-63

Stability

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:CARBON DIOXIDE,CARBON MONOXIDE



Disposal

Waste Disposal Methods:INCINERATE IN APPROVED FACILITY.DO NOT INCINERATE CLOSED CONTAINER.DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL REGULATIONS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.