

STP (R) FOUR CYLINDER OIL TREATMENT

MSDS Number

BBBYC

National Stock Number

6850-00B210005

Product Name

STP (R) FOUR CYLINDER OIL TREATMENT

Manufacturer

UNION CARBIDE

Product Identification

Product ID:STP (R) FOUR CYLINDER OIL TREATMENT

MSDS Date:05/29/1987

FSC:6850

NIIN:00B210005

MSDS Number: BBBYC

Responsible Party

UNION CARBIDE

DANBURY , CT 06817-0001

US

Emergency Phone: 800-424-9300

Info Phone: 203-790-5556

Cage: 07098

Contractor

UNION CARBIDE

EAST HARTFORD, CT 06108

US

800-822-4357

Cage: 07098

Ingredients

SOLVENT DEWAXED HEAVY PARRAFFINIC PETROLEUM DISTILLATES

CAS: 64742-65-0

ACGIH TLV: 5.0 MG/M3 OIL MIST

ETHYLENE-PROPYLENE COPOLYMER

DIAKYLDITHIOPHOSPHORIC

CAS: 68649-42-3

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:SWALLOWING:INGESTION OF PETROLEUM OIL

IS UNLIKELY TO HAVE ANY TOXIC EFFECTS.MAY ACT AS AN INTESTINAL

LUBRICANT AND RESULT IN DIARRHEA OR FREQUENT LOOSE STOOLS.EYE

CONTACT:MAY CAUSE IRRITATION WITH SLI GHT REDDENING AND SWELLING OF

THE CONJUNCTIVA.NO EFFECTS EXPECTED FROM SKIN ABSORPTION.

Effects of Overexposure:INHALATION:IF MISTS OR VAPORS FORM,LIPID

PNEUMONITIS MAY OCCUR IF EXPOSURE IS PROLONGED IN POORLY VENTILATED SURROUNDINGS. THIS PRODUCT MAY CAUSE MODERATE IRRITATION AFTER PROLONGED PERIODS OF SKIN CONTACT.

Medical Condition Aggravated by Exposure: PERSONS WHO ARE PRONE TO ACNE OR SEBORRHEA ARE SUSCEPTIBLE TO BLOCKAGE OF HAIR FOLLICLES BY INSOLUBLE OILS.

First Aid

First Aid: SWALLOWING: DO NOT INDUCE VOMITING. TREAT SYMPTOMATICALLY. SKIN: REMOVE CONTAMINATED CLOTHING. WASH ALL AFFECTED AND EXPOSED AREAS WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. EYES: FLUSH EYES WITH PLenty OF WATER FOR AT LEAST 15 MIN. IF IRRITATION PERSISTS SEEK MEDICAL ATTENTION.

Fire Fighting

Flash Point: T.O.C. 315F
Extinguishing Media: ALCOHOL FOAM, CARBON DIOXIDE, AND DRY CHEMICAL.
Fire Fighting Procedures: WATER OR FOAM MAY CAUSE FROTHING.
Unusual Fire/Explosion Hazard: NONE EXPECTED.

Accidental Release

Spill Release Procedures: WEAR SUITABLE PERSONAL PROTECTIVE EQUIPMENT. COLLECT FOR DISPOSAL. LARGER SPILLS MAY BE ABSORBED ON VERMICULITE OR OTHER SIMILAR MATERIAL.

Exposure Controls

Respiratory Protection: NONE REQUIRED WHEN HANDLING AT MINIMUM FEASIBLE TEMPERATURES.
Ventilation: GENERAL VENTILATION IS ADEQUATE FOR NORMAL HANDLING.
Protective Gloves: NITRILE RUBBER GLOVES
Eye Protection: CHEMICAL SAFETY GOGGLES
Other Protective Equipment: EYE WASH
Work Hygienic Practices: PERSONAL HYGIENE SHOULD BE PRACTICED.
Supplemental Safety and Health
AVOID EYE CONTACT AND PROLONGED CONTACT WITH SKIN.

Chemical Properties

Boiling Pt: B.P. Text: 760 MM HG, F
Vapor Pres: MM HG 68F
Vapor Density: AIR=1
Evaporation Rate & Reference: BUTYL ACETATE=1
Solubility in Water: NIL
Appearance and Odor: VISCOUS, CLEAR AMBER LIQUID
Percent Volatiles by Volume: NIL

Stability

Stability Indicator/Materials to Avoid: YES
Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE, ALDEHYDES AND KETONES, COMBUSTION PRODUCTS OF NITROGEN AND SULFUR.

Disposal

Waste Disposal Methods: INCINERATE OR LANDFILL IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.