

## **STP FIRST STEP IN A TUNE-UP**

### **MSDS Number**

BBBYF

### **National Stock Number**

6850-00B210007

### **Product Name**

STP FIRST STEP IN A TUNE-UP

### **Manufacturer**

STP CORP

### **Product Identification**

Product ID:STP FIRST STEP IN A TUNE-UP

MSDS Date:11/21/1985

FSC:6850

NIIN:00B210007

MSDS Number: BBBYF

### **Responsible Party**

STP CORPORATION

88 LONG HILL ST.

EAST HARTFORD , CT 06108

US

Emergency Phone: 1-800-822-4357

Cage: STPCO

### **Contractor**

STP CORPORATION

EAST HARTFORD, CT 06108

US

800-822-4357

Cage: STPCO

### **Ingredients**

AROMATIC PETROLEUM DISTILLATES

2-BUTOXYETHANOL

CAS: 111-76-2

RTECS: KJ8575000

OSHA PELS, 50 PPM

ACGIH TLV: S, 25 PPM; 9293

### **Hazards**

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:PROLONGED EXPOSURE TO PETROLEUM DISTILLATES CAN CAUSE DIZZINESS,WEAKNESS,WEIGHT LOSS,ANEMIA,A FEELING OF AGITATION,PLUS PAIN,NUMBNESS,AND A TINGLING SENSATION IN THE LIMBS.THE RED BLOOD CELL COUNT MAY BE REDUCED,BONE MARROW MAY BE HYPOPLASTIC,AND PROTEINURIA AND HEMATURIA MAY BE FOUND.SKIN IRRITATION CAN OCCUR.

Effects of Overexposure:SAME AS HEALTH HAZARDS ACUTE AND CHRONIC.

Medical Cond Aggravated by Exposure:BECAUSE OF ITS IRRITATING AND

DEFATTING PROPERTIES,THIS MATERIAL MAY AGGRAVATE AN EXISTING DERMATITIS.BREATHING OF VAPOR AND/OR MIST MAY AGGRAVATE ASTHMA AND INFLAMMATORY OR FIBROTIC PULMONARY DISEASE

## First Aid

First Aid:SWALLOWING:DO NOT INDUCE VOMITING.SKIN:REMOVE CONTAMINATED CLOTHING AND WASH SKIN THOROUGHLY WITH SOAP AND WATER.INHALATION:REMOVE FROM EXPOSURE.IF EXPOSURE IS SEVERE,HOSPITALIZE AND OBSERVE.TREATMENT MAY BE REQUIRED FOR PULMONARY EDEMA AND HEMORRHAGE.EYES:IMMEDIATELY FLUSH EYES WITH COPIOUS AMOUNTS OF WATER FOR AT LEAST 15 MIN.SEEK MEDICAL ATTENTION.

## Fire Fighting

Flash Point Method:TOC  
Flash Point:137F-58C  
Extinguishing Media:FOAM,ALCOHOL FOAM,CARBON DIOXIDE,DRY CHEMICAL AND WATER FOG.  
Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS FOR ENCLOSED AREAS.  
Unusual Fire/Explosion Hazard:AVOID CONTACT WITH STRONG OXIDIZERS.

## Accidental Release

Spill Release Procedures:WEAR APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT AND REMOVE ALL SOURCES OF IGNITION.CONTAIN SPILL.COLLECT MATERIAL FOR DISPOSAL IN A CONTAINER SUITABLE FOR FLAMMABLE WASTE.

## Handling

Other Precautions:AVOID EYES AND SKIN CONTACT.DO NOT BREATHE VAPOR.

## Exposure Controls

Respiratory Protection:USE NIOSH/MSHA APPROVED FULL FACE RESPIRATOR EQUIPPED WITH A CHEMICAL CARTRIDGE FOR OPERATIONS WHERE THE PEL MAY BE EXCEEDED.USE SELF CONTAINED BREATHING APPARATUS FOR FIRE FIGHTING AND MAJOR SPILL CL EAN-UP.  
Ventilation:LOCAL EXHAUST VENTILATION IS RECOMMENDED FOR OPERATIONS WHERE THE PEL MAY BE EXCEEDED.  
Protective Gloves:BUTYL RUBBER GLOVES  
Eye Protection:CHEMICAL SAFETY GOGGLES  
Other Protective Equipment:EYE WASH,SAFETY SHOWER  
Supplemental Safety and Health

## Chemical Properties

Boiling Pt:B.P. Text:760 MM HG F  
Vapor Pres:MM HG 68 F  
Vapor Density:AIR=1  
Evaporation Rate & Reference:BUTYL ACETATE=1  
Solubility in Water:INSOLUBLE  
Appearance and Odor:AMBER COLORED,SOMEWHAT VISCOUS,SLIGHTLY OILY ODOR  
Percent Volatiles by Volume:70

## Stability

Stability Indicator/Materials to Avoid:YES  
Hazardous Decomposition Products:COMBUSTION MAY GIVE OFF CARBON MONOXIDE.

## Disposal

Waste Disposal Methods:WASTE MATERIAL IS A RCRA HAZARDOUS WASTE DUE TO IGNITABILITY.INCINERATION,OR LANDFILLING SHOULD BE CARRIED OUT IN ACCORDANCE WITH APPLICABLE RCRA FEDERAL,STATE,AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.