

1N CONTACT CEMENT

MSDS Number

BBBZR

National Stock Number

6850-00B230018

Product Name

1N CONTACT CEMENT

Manufacturer

W F TAYLOR CO INC

Product Identification

Product ID:1N CONTACT CEMENT

MSDS Date:05/13/1986

FSC:6850

NIIN:00B230018

MSDS Number: BBBZR

Responsible Party

W.F.TAYLOR CO.,INC.

13660 EXCELSIOR DR.

SANTA FE SPRINGS , CA 90670

US

Emergency Phone: 213802-1896

Info Phone: SAME

Cage: DO917

Contractor

W.F.TAYLOR CO.,INC.

SANTA FE SPRINGS, CA 90670

US

SAME

Cage: DO917

Ingredients

NAPHTA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: VL8047000

Fraction By Weight: 60%

OSHA PEL100 PPM

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 20 - 25%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 20%

OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300STEL 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:MAY LEAD TO HEADACHE AND CENTRAL NERVOUS SYSTEM DEPRESSION AND SKIN RASH.

Effects of Overexposure:MAY CAUSE NARCOSIS,UNCONSCIOUSNESS FROM INHALATION.MAY CAUSE DERMATITIS FROM CHRONIC SKIN CONTACT.

First Aid

First Aid:EYE CONTACT:WASH W/WATER.IF IRRITATION PERSIST,SEEK MEDICAL ATTN.SKIN CONTACT:REMOVE FROM SKIN AND APPLY SKIN CREAM.IF IRRITATION PERSIST,SEEK MEDICAL ATTN.INHALATION:REMOVE TO FRESH AIR.ADMINISTER OX YGEN.IF NECESSARY,SEEK MEDICAL ATTN.INGESTION:SEEK MEDICAL ATTN.DO NOT INDUCE VOMITING.THIS COULD CAUSE CHEMICAL PNEUMONITIS.

Fire Fighting

Flash Point Method:TCC

Flash Point:21F

Lower Limits:1%

Upper Limits:7%

Extinguishing Media:WATER SPRAY,FOAM,CARBON DIOXIDE,DRY CHEMICAL

Fire Fighting Procedures:WATER MAY SPREAD BURNING LIQUID.AVOID DIRECT STREAM OF WATER.

Unusual Fire/Explosion Hazard:DO NOT EXPOSE TO EXCESSIVE HEAT,OPEN FLAME OR SPARKS.TURN OFF ALL PILOT LIGHTS.

Accidental Release

Spill Release Procedures:MATERIAL IS FLAMMABLE,ELIMINATE SOURCES OF IGNITION.FOR LARGE SPILLS,EVACUATE AREA.DIKE AND CONTAIN MATERIAL.STOP LEAK,IF POSSIBLE.USE WATER FOG TO SUPPRESS VAPOR CLOUD.USE CLAY OR SAND TO SOAK UP MATERIAL.PLACE MATERIAL IN NON-LEAKING CONTAINER.

Handling

Handling and Storage Precautions:PROTECT AGAINST PHYSICAL DAMAGE,STORE IN A COOL PLACE.KEEP AWAY FROM HEAT AND SPARKS.

Exposure Controls

Respiratory Protection:NONE REQUIRED,UNLESS EXPOSURE IS OVER TLV.USE NIOSH APPROVED RESPIRATOR.

Ventilation:USE LOCAL EXHAUST.DO NOT USE CLOSED AIR CIRCULATING SYSTEM.OPEN WINDOWS & DOORS,IF NECESSARY.

Protective Gloves:ACRYLONITRILE GLOVES

Eye Protection:CHEMICAL GOGGLES/FACESHIELD

Other Protective Equipment:IF CLOTHING BECOMES CONTAMINATED,REMOVE AND CLEAN BEFORE REWEARING.

Work Hygienic Practices:FOLLOW ALL LABEL INSTRUCTIONS.

Supplemental Safety and Health

NO SMOKING,AVOID SPARKS.USE RESPIRATOR UNLESS EXPOSURE IS KNOWN TO BE BELOW TLV.

Chemical Properties

Boiling Pt:B.P. Text:175F
Vapor Density:>THAN 1
Spec Gravity:.84
Evaporation Rate & Reference:>1
Solubility in Water:NIL
Appearance and Odor:GREEN OR CLEAR-SYRUP CONSISTENCY-PUNGENT ODOR.

Stability

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:EXCESSIVE HEAT,OPEN FLAME OR SPARKS.
Hazardous Decomposition Products:CO,CO2 AND OTHER UNIDENTIFIED ORGANIC COMPOUNDS.

Disposal

Waste Disposal Methods:DISPOSE OF ALL WASTES IN ACCORDANCE
W/FEDERAL,STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.