

F 150-3/4,ASBESTOS.

MSDS Number

BBCBK

National Stock Number

5970-00D000004

Product Name

F 150-3/4,ASBESTOS.

Manufacturer

AMATEX CORP

Product Identification

Product ID:F 150-3/4,ASBESTOS.

MSDS Date:01/01/1985

FSC:5970

NIIN:00D000004

MSDS Number: BBCBK

Responsible Party

AMATEX CORP.

1032 STANBRIDGE STREET

NORRISTOWN , PA 19401-3666

US

Cage: D0922

Contractor

AMATEX CORP.

NORRISTOWN, PA 19401-3666

US

215-277-6100 / 215-277-6108

Cage: D0922

Ingredients

ASBESTOS (AMIANTHUS, OBSOLETE AMOSITE), (FOR OSHA PEL, SEE

CAS: 1332-21-4

RTECS: CI6475000

OSHA PEL0.2 FIBERS/CC

ACGIH TLV: 0.5 FIBERS/CC; A1;89

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

Hazards

Effects of Overexposure:>5MM/CC LONG TERM:INCREASED RISK OF
ASBESTOSIS,CANCER(BRONCHIAL,GASTROINTESTINAL,MESOTHELIOMA.

First Aid

First Aid:EMERGENCY:NIOSH APPROVED RESPIRATORY PROTECTION;(UP TO 100
FIBERS/CC AIR PURIFYING RESPIRATOR)FIRST AID.CONSULT A DR.FOR
DERMATITIS.WHEN ASBESTOS GETS INTO THE EYE,FLUSH EYES WITH WATER
FOLLOWED BY TR EATMENTS OF EYE DR.

Accidental Release

Spill Release Procedures:UPON RELEASE OF FIBERS IN EXCESS OF ABOVE TLV,IT IS REQUIRED TO INCORPORATE ENGINEERING CONTROLS,WORK PRATICES,OR APPROVED RESPIRATORY PROTECTION,IN THAT ORDER.

Handling

Handling and Storage Precautions:STORE & HANDLE SUCH THAT FIBERS ARE NOT RELEASED IN EXCESS OF ABOVE TLV.

Other Precautions:SEE SECTION 1910,1001 OF TITLE 29 CHAP.XVII THE OCCUPATIONAL SAFETY HEALTH ADMINISTRATION (OSHA).

Exposure Controls

Respiratory Protection:USE 3M NO.8710 DISPOSABLE OR OTHER NIOSH APPROVED FOR ASBESTOS.

Ventilation:LOCAL EXHAUST IS PREFERRED.

Protective Gloves:WORKING

Eye Protection:SAFETY GOGGLES

Other Protective Equipment:WHEN IN EXCESS OF CEILING TLV-FALL PROTECTIVE CLOTHING

Supplemental Safety and Health
ITEM HAS A CEILING OF 10 FIBERS.

Chemical Properties

HCC:T6

Spec Gravity:2.4-3

Appearance and Odor:WHITE-NO ODOR.

Stability

Stability Indicator/Materials to Avoid:YES

NONE

Hazardous Decomposition Products:NONE

Disposal

Waste Disposal Methods:IF DISPOSAL PRODUCES FIBERS IN EXCESS OF ABOVE TLV,WASTES ARE TO BE COLLECTED & DISPOSED OF IN SEALED IMPERMEABLE BAGS OR OTHER SEALED CONTAINER.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.