

139 4832,RP X-OMAT DEVLPR REPLNSHR,PART C

MSDS Number

BBCBS

National Stock Number

6750-00D000009

Product Name

139 4832,RP X-OMAT DEVLPR REPLNSHR,PART C

Manufacturer

EASTMAN KODAK COMPANY

Product Identification

Product ID:139 4832,RP X-OMAT DEVLPR REPLNSHR,PART C

MSDS Date:01/01/1985

FSC:6750

NIIN:00D000009

MSDS Number: BBCBS

Responsible Party

EASTMAN KODAK COMPANY

Emergency Phone: 716-722-5151

Cage: 19139

Contractor

EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

ROCHESTER, NY 14650-1115

US

716-722-5151/(800) 242-2424

Cage: 19139

Ingredients

ADEHYDE BISULFITE PRODUCT(ALDEHYDE SODIUM SULFITE; % WT

Fraction By Weight: 22.5%

GLUTARALDEHYDE

CAS: 111-30-8

RTECS: MA2450000

Fraction By Weight: 12.5%

OSHA PELC 0.2 PPM

ACGIH TLV: C 0.2 PPM; 9192

60-70%

CAS: 7732-18-5

RTECS: ZC0110000

Fraction By Weight: 65.0%

Hazards

Effects of Overexposure:INH:VAP MAY IRRIT RESP TRACT;EYES:CAUSES EYE
BURNS;SKIN:PROLNGD/REPEATD CONTACT CAUSES IRRITN/ALLRGY

First Aid

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES:FLUSH W LG AMTS H*2O FOR 15 MIN;SKIN:FLUSH W LG AMTS H*2O;INGEST:RINSE MOUTH.IMMEDIATELY GET MED ATTN IF SKIN/EYES IRRIT OR ALLERY REACTION DEVELO PS,LAUNDR CONTMTD CLOTHG.

Fire Fighting

Flash Point:NONE
Extinguishing Media:CO*2, FOAM, DRY CHEM.
Fire Fighting Procedures:WEAR SCBA & PROTCTV CLOTHING TO PREVENT SKIN/EYE CONTACT.
Unusual Fire/Explosion Hazard:EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

Accidental Release

Spill Release Procedures:AVOID INHALATION & SKIN CONTACT.WEAR SUITABLE PROTECTIVE EQUIPMENT;NEUTRALIZE SM SPILL W/SODIUM METABISULFITE.FLUSH TO SEWER IN ACID-REE SEWER IAW FED STATE & LOCAL REGULATIONS;LG SPILL:DIKE FAR AHEAD & PUMP LIQ TO SALVAGE TANK FOR DISPOSAL/NEUTRLIZ.

Handling

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED
Other Precautions:MAY CAUSE SKIN IRRITATION & ALLERGIC SKIN REACTION;AVOID CONTACT W/SKIN,EYES,& CLOTHING.AVOID BREATHING VAPOR.USE W/ADEQUATE VENTILATION; READ CAUTION LABEL ON THE CONTAINER BEFORE USE.

Exposure Controls

Respiratory Protection:AN NIOSH-APPRVD ORGANIC VAPOR RESP OR FORMALDEHYDE VAP.
Ventilation:MECHANICAL(GENERAL) RECOMMENDED,LOCAL EXHAUST IF NEEDED
Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY/CHEM GOGGLES
Other Protective Equipment:NON-ALKALINE(ACID)TYPE HAND CLEANR MINIMZ SKIN ALLRGY ACTION
Supplemental Safety and Health
MSDS FM MFR DATED:5/18/83;PART C OF 3 PART PRODUCT;PH APPROX 3.0;SEE P/N IND A & B,UNDER THIS NSN FOR PART A & PART B DATA.

Chemical Properties

HCC:C3
Boiling Pt:B.P. Text:>212F(>100C
Vapor Pres:18
Vapor Density:0.8
Spec Gravity:1.16
Solubility in Water:COMPLETE
Appearance and Odor:CLEAR TO LIGHT BROWN SOLUTION; ALDEHYDE ODOR.
Percent Volatiles by Volume:80%

Stability

Stability Indicator/Materials to Avoid:YES
MINERAL ACIDS
Hazardous Decomposition Products:SULFUR DIOXIDE

Disposal

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.MFR NOTES,NEUTRALIZE W/SOD METABISULFITE.FLUSH TO SEWER IAW EXISTING REGS FOR DISPOSAL REQUIRED.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.