

13873P,BETASAN 4E

MSDS Number

BBCDD

National Stock Number

6840-00D000041

Product Name

13873P,BETASAN 4E

Manufacturer

STAUFFER CHEM CO (MFR) KENT INTERNATIONAL(DIST)

Product Identification

Product ID:13873P,BETASAN 4E

MSDS Date:01/01/1985

FSC:6840

NIIN:00D000041

MSDS Number: BBCDD

Responsible Party

STAUFFER CHEM.CO.(MFR),KENT INTERNATIONAL(DIST)

NYALA FARMS RD

WESTPORT , CT 06880-6240

US

Cage: DO931

Contractor

STAUFFER CHEM.CO.(MFR),KENT INTERNATIONAL(DIST)

WESTPORT, CT 06880-6240

US

800-828-792

Cage: DO931

Ingredients

S-(O,O-DIISOPROPYL PHOSPHORODITHIOATE)ESTER OF

CAS: 741-58-2

RTECS: TE0250000

Fraction By Weight: 4620%

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 36.5%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

OTHER SOLVENTS (TYPE NOT SPECIFIED)

Fraction By Weight: 17.5%

Hazards

Effects of Overexposure:HARMFUL IF SWALLOWED,SKIN IRRITANT,AS WELL AS EYES.

First Aid

First Aid:INGEST:DO NOT INDUCE VOMIT.IMMEDIATELY GIVE LARGE AMTS. OF WATER.CALL DR. SKIN:FLUSH W/LARGE AMTS. OF WATER FOR 15 MIN.EYES:FLUSH W/LARGE AMTS OF WATER FOR 15 MIN.INHAL:MOVE TO FRESH AIR.

Fire Fighting

Flash Point:104F PMCC
Extinguishing Media:WATER,DRY CHEM.FOAM OR CO*2.
Fire Fighting Procedures:EVACUATE NONESSENTIAL,USE SELF-CONTAINED BREATHING APPARATUS
Unusual Fire/Explosion Hazard:THE MATERIAL IS CONSIDERED COMBUSTIBLE.UNDER FIRE CONDITIONS,WILL SUPPORT COMBUSTION,EMITS TOXICS.

Accidental Release

Spill Release Procedures:SMALL SPILLS:CAN BE HANDLED ROUTINELY.USE ADEQUATE VENTILATION & WEAR AN AIR-SUPPLIED RESPIRATOR.WEAR PROTECTIVE CLOTHING.USE ADSORBENT SUCH AS CLAY,SAWDUST OR KITTY LITTER.PLACE SWEEPINGS IN APPROP.W ASTE CONT.COVER CONTAM.AREAS W/DETERGENT(TIDE).

Handling

Handling and Storage Precautions:CONTAINERS SHOULD BE STORED IN A COOL,DRY,WELL-VENTILATED AREA.STORE AWAY FROM FLAMMABLE MATERIALS & SOURCES OF HEAT & FLAME.DO NO USE NEAR OPEN FIRE.
Other Precautions:DO NOT POUR,SPILL OR STORE NEAR HEAT OR OPEN FLAME.ALSO USE CAUTION TO PREVENT DAMAGE TO OR LEAKAGE FROM THE CONTAINER.STORE MATL ONLY AT TEMPS ABOVE 42F.KEEP MATL OUT OF LAKES,STREAMS OR POND

Exposure Controls

Respiratory Protection:USE SELF-CONTAINED BREATHING APPARATUS.
Ventilation:LOCAL EXHAUST IS RECOMMENDED
Protective Gloves:RUBBER
Eye Protection:CHEM.SAFETY GLASSES
Other Protective Equipment:FACE SHIELD,HOODS,SUITS & RUBBER BOOTS.
Supplemental Safety and Health
ITEM IS MAKE UP OF S-(O,O-DIISOPROPYL PHOSPHORODITHIOATE)ESTER OF N-(2-MERCAPTOETHYL) BENZENESULFONAMIDE(46%); 36.5% XYLENE RANGE HYDROCARBON SOLVENT,OTHER 17.5%

Chemical Properties

HCC:F5
Spec Gravity:1.04.
Viscosity:@ 77F 12CPS
Solubility in Water:NEGLIGIBLE
Appearance and Odor:AMBER-COLORED LIQUID.

Stability

Stability Indicator/Materials to Avoid:YES
AVOID OXIDIZERS,HEAT,FLAME
Stability Condition to Avoid:TEMPS < 42F,CRYSTALLIZATION MAY OCCUR
Hazardous Decomposition Products:GIVES OFF TOXIC MATERIALS

Disposal

Waste Disposal Methods:SEAL CONTAINER & DISPOSE OF IN APPROVED PESTICIDE LANDFILL OR INCINERATE IN AN APPROVED INCINERATOR.MATERIAL THAT CANNOT BE USED OR CHEMICALLY REPROCESSED SHOULD BE DISPOSED OF IN AN APPROVED LANDFILL .CONSULT W/FED.,STATE

AND LOCAL DISPOSAL PEOPLE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.