
SULFURIC ACID(OIL OF VITRIOL)/

MSDS Number

BBCFG

National Stock Number

6810-00D000064

Product Name

SULFURIC ACID(OIL OF VITRIOL)/

Manufacturer

STAUFFER CHEMICAL CO

Product Identification

Product ID:SULFURIC ACID(OIL OF VITRIOL)/

MSDS Date:01/01/1985

FSC:6810

NIIN:00D000064

MSDS Number: BBCFG

Responsible Party

STAUFFER CHEMICAL CO

NYALA FARMS RD

WESTPORT , CT 06880-6240

US

Cage: DO667

Contractor

STAUFFER CHEMICAL COMAPNY

WESTPORT, CT 06881

US

(203) 226-6602

Cage: DO667

Ingredients

SULFURIC ACID (SARA III)

CAS: 7664-93-9

RTECS: WS5600000

Fraction By Weight: 93.2%

OSHA PEL1 MG/M3

ACGIH TLV: 1 MG/M3; 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Effects of Overexposure:INGESTION: MAY CAUSE SEVERE DAMAGE. EYES:
SEVERE BURNS. SKIN: DESTRUCTIVE TO BODY TISSUES. INHALATION: LUNG
DAMAGE.

First Aid

First Aid:INGESTION: GIVE LARGE AMOUNTS OF WATER. INDUCE VOMITING. EYE:
PROMPTLY FLUSH WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. DO NOT

USE OILS OR OINTMENTS IN EYES. SKIN: PROMPTLY FLUSH WITH WATER.
CALL DOC TOR. INHALATION: MOVE TO FRESH AIR. KEEP PATIENT WARM.
CALL DOCTOR.

Fire Fighting

Extinguishing Media: DRY CHEMICAL, CARBON DIOXIDE, OR FOG SPRAY.
Fire Fighting Procedures: COOL TANK WITH WATER, USE SELF-CONTAINED
BREATHING APPARATUS.
Unusual Fire/Explosion Hazard: EXTREMELY HAZARDOUS IN CONTACT WITH MANY
MATERIALS. ATTACKS AND CORRODES MANY METALS BY RELEASE OF HYDROGEN
GAS.

Accidental Release

Spill Release Procedures: SULFURIC ACID LEAKS, SPILLS, OR DRAININGS MUST
NOT COME IN CONTACT W/ SULFIDES WASTES, SUCH AS IN SEWERS, BECAUSE OF
EVOLUTION OF HYDROGEN SULFIDE GAS. COVER W/ SODIUM CARBONATE OR AN
EQUAL MIXTURE OF SODA ASH & SLAKED LIME. ADD WATER AFTER MIX TO FORM
SLUR

Handling

Handling and Storage Precautions: SULFURIC ACID MAY BE SAFELY STORED IN
BULK STORAGE TANKS PROPERLY DESIGNED-PROTECT CONTAINERS AGAINST
PHYSICAL DAMAGE & PREVENT CONTACTS W/ WATER.
Other Precautions: SEPARATE FROM CARBIDES, CHLORATES, FULMINATES, NITRATES,
PICRATES, POWDERED METALS & CHEM. GOGGLES, RUBBER BOOTS &
CHEM. CARTRIDGE RESPIRATOR.

Exposure Controls

Respiratory Protection: SELF-CONTAINED BREATHING APPARATUS OR APPROVED
CANISTER OR AIR MASK.
Ventilation: LOCAL EXHAUST IS RECOMMENDED
Protective Gloves: RUBBER
Eye Protection: SAFETY GOGGLES
Other Protective Equipment: SAFETY SHOWERS, EYE WASH FOUNTAINS, FACE
SHIELD, RUBBER SHOES.
Supplemental Safety and Health
SPILLS OR LEAKS (CONTD): CONTAMINATED AREA SHOULD BE IMMEDIATELY ZONED
OFF TO AVOID ANYONE BEING EXPOSED TO ACID SPRAY OR STREAM, ADJUST
VALVES TO ISOLATE SYSTEM & STOP FURTHER LEAKAGE. NEUTRALIZE

Chemical Properties

HCC: C1
Boiling Pt: B.P. Text: 597F, 314C
Vapor Pres: 1.0
Spec Gravity: 1.834
Solubility in Water: COMPLETE
Appearance and Odor: CLEAR, COLORLESS TO CLOUDY LIQUID. ODORLESS.

Stability

Stability Indicator/Materials to Avoid: YES
NITRATES, CARBIDES, CHLORATES, FULMINATES, PICRATES, COMBUSTIBLES.
Stability Condition to Avoid: DO NOT ADD WATER TO ACID - A LARGE AMOUNT
OF HEAT WILL BE PRODUCED.
Hazardous Decomposition Products: WHEN HEATED EMITS HIGHLY TOXIC FUMES,
HYDROGEN GAS ON CONTACT WITH METALS.

Disposal

Waste Disposal Methods: ADD SLOWLY TO A LARGE AMT OF SOLUTION OF SODA
ASH & SLAKED LIME BY STIRRING. DISCHARGE THE SOLUTION W/ LARGE AMT OF
WATER INTO AN APPROVED DISPOSAL AREA.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.