

121 2505, EKTPRNT 2 BLEACH-FIX & REPL PART A

MSDS Number

BBCHC

National Stock Number

6750-00D000101

Product Name

121 2505, EKTPRNT 2 BLEACH-FIX & REPL PART A

Manufacturer

EASTMAN KODAK COMPANY

Product Identification

Product ID:121 2505, EKTPRNT 2 BLEACH-FIX & REPL PART A MSDS Date:01/01/1985

FSC:6750 NIIN:00D000101

Kit Part:Y MSDS Number: BBCHC

Responsible Party

EASTMAN KODAK COMPANY

Emergency Phone: 716-722-5151

Cage: 19139 Contractor

EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

ROCHESTER, NY 14650-1115

US

716-722-5151/(800) 242-2424

Cage: 19139

Ingredients

THIOSULFATE (10-20%) Fraction By Weight: 15.0%

WATER (80-90%)(CAS #7732-18-5)

CAS: 7732-18-5 RTECS: ZC0110000

Fraction By Weight: 85.0%

Hazards

Effects of Overexposure: PER MFGR MSDS, "LOW HAZARD".; NOT EXPECTED TO BE A PROBLEM; MAINTAIN STRIC HYGIENE.

First Aid

First Aid:MFGR MSDS STATED"NONE INDICATED.";HOWEVER,FLUSH W/PLENTY OF WATER IN CASE OF SKIN/EYE CONTACT.GET MEDICAL HELP IF SYMPTOMS OF IRRITATION/DISCOMFORT OCCUR; IF DIFFICULT IN BREATHING, GIVE CPR/OXY & GET M ED ATTN.

Fire Fighting

Flash Point:NONE Extinguishing Media: CO*2, DRY CHEM



Fire Fighting Procedures: WEAR SELF-CNTND BREATHG APP; COOL EXPSD CONTNR BY WATER SPRAY

Unusual Fire/Explosion Hazard: CONTAINER MAY EXPLODE IN HEAT OF FIRE; SPILL/RUNOFF MAY CAUSE POLLUTION, FIRE, &/OR EXPLOSION.

Accidental Release

Spill Release Procedures: EVACUATE UNPROTECTED PERSONS. ELIM IGN SOURCES. USE PROTECTV CLOTHING/SAFETY GLASSES. STOP LEAK W/O RISK. PROVIDE VENT. DIKE/LG SPILL & PUMP INTO COVRD DRUMS; ABSORB/CONTAIN SM SPILL IN CONT; MFGR RECOMMENDS , FLUSH TO SEWER W/LG AMT OF WATER IAW EXISTING LAW

Handling

Handling and Storage Precautions:STORE AWAY FROM STRONG ALKALI.STORE IN COOL,DRY PLACE.KEEP CONTNRS TIGHTLY CLOSED.PROTECT CONTNRS FROM PHYSICAL DAMAGE.

Other Precautions: AVOID SKIN/EYE CONTACT W/CHEMICAL PRODUCTS. WASH THOROUGHLY AFTER HANDLING. PH OF PROD: 5.3(APPROX).

Exposure Controls

Respiratory Protection: AN APPRVD ORGANIC VAP RESPIRATOR IF VENTILATION IS INADEQUATE

Ventilation: LOCAL EXHAUST & MECHANICAL (GENERAL) RECOMMENDED BY MFGR.

Protective Gloves: IMPERVIOUS

Eye Protection: SAFETY GLASSES/GOGGLES.

Other Protective Equipment: AS NECESSARY TO PREVENT SKIN CONTACT.

Supplemental Safety and Health

MSDS FROM MFGR DATED:3/21/79, REISSUED 8/80; THIS IS PART "A" OF TWO PART KIT. PART B DATA IS UNDER THE SAME NSN BUT UNDER P/N INDICATOR "B".

Chemical Properties

HCC:N1

Boiling Pt:B.P. Text:>212F(100F)

Vapor Pres:17 Vapor Density:0.6 Spec Gravity:1.33

Solubility in Water: COMPLETE

Appearance and Odor:CLEAR,COLORLESS LIQ;SULFUR DIOXIDE ODOR

Percent Volatiles by Volume:48.9

Stability

Stability Indicator/Materials to Avoid:YES STRONG ACIDS OR BASES Stability Condition to Avoid:UNK Hazardous Decomposition Products:SO*2

Disposal

Waste Disposal Methods: KEEP IN COVERED CONTAINERS PENDING DISPOSAL. SHIP WASTE MATL TO DISPOSAL FACILITY IAW DOT/EPA REGS. HANDLE/DISPOSE IN FULL COMPLIANCE W/ALL INTNL, FED, STATE/LOCAL REGS; MFGR RECOMMENDS, FLUSH TO SEWER W/LG AMT OF WATER IAW FED, STATE/LOCAL EFFLUENT LAWS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.