

## **HULTSCRETE**

### **MSDS Number**

BBCJP

### **National Stock Number**

8040-00D000139

### **Product Name**

HULTSCRETE

### **Manufacturer**

HULTSCRETE CO

### **Product Identification**

Product ID:HULTSCRETE

MSDS Date:01/01/1985

FSC:8040

NIIN:00D000139

MSDS Number: BBCJP

### **Responsible Party**

HULTSCRETE CO.

Emergency Phone: 704-376-8484

Cage: DO951

### **Contractor**

HULTSCRETE CO.

WADESBORO, NC 28170

US

704-272-7641

Cage: DO951

### **Ingredients**

EPOXY RESIN

Fraction By Weight: 40.0%

AROMATIC HYDROCARBON SOLVENTS.

Fraction By Weight: 20.0%

ACGIH TLV: 200 PPM

KETONES.

Fraction By Weight: 21.0%

ACGIH TLV: 100PPM

NON HAZARDOUS INGREDIENTS

Fraction By Weight: 19.0%

### **Hazards**

Effects of Overexposure:TEMPORARY DAMAGE TO LUNGS,MAY CAUSE PERMANENT  
DAMAGE & ENE DEATH,DRUNKNESS W/O SPRAY MASKS.

### **First Aid**

First Aid:CLOTHES:REMOVE AND WASH IMMEDIATELY. SKIN:WASH IMMED.W/SOLVENT THEN SOAP & WATER. EYES:FLUSH WITH WATER UNTIL PAIN CEASES & SEE DR.AS SOON AS POSSIBLE.

## Fire Fighting

Flash Point:73F  
Lower Limits:1.0.  
Upper Limits:1.8.  
Extinguishing Media:FOAM,CO\*2 OR DRY CHEMICAL,WATER SPRAY INEFFECTIVE  
Fire Fighting Procedures:FIREMEN SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS.  
Unusual Fire/Explosion Hazard:VAPORS ARE HIGHLY MOBILE & MAY TRAVEL A CONSIDERABLE DISTANCE TO SOURCE OF IGNITION & BACK.

## Accidental Release

Spill Release Procedures:WIPE UP IMMED.WITH DRY RAGS OR POUR SAND ON SPILL.

## Handling

Handling and Storage Precautions:KEEP IN COOL PLACE.KEEP OUT OF DIRECT SUNLIGHT OR HEAT.LEAKING CONTAINERS MUST BE REMOVED TO SAFE PLACE.  
Other Precautions:FOR PROFESSIONAL USE ONLY. KEEP OUT OF REACH OF CHILDREN.

## Exposure Controls

Respiratory Protection:SELF-CONTAINED BREATHING APPARATUS;WEAR MASKS WHEN SPRAYING.  
Ventilation:LOCAL EXHAUST IS RECOMMENDED,SO THAT GASES DO NOT EX.100PPM  
Eye Protection:SAFETY GLASSES  
Supplemental Safety and Health  
ITEM IS MADE UP OF 2 PARTS:A & B, & IS PART OF A KIT. PART A IS COVERED UNDER THIS NSN. PART B IS COVERED SEPARATELY UNDER SAME NSN.  
KEY1:F3.

## Chemical Properties

HCC:F3  
Boiling Pt:B.P. Text:244.4-291.9  
Spec Gravity:1.17  
Evaporation Rate & Reference:Solubility in Water:APPRECIABLE  
Appearance and Odor:LIQUID,PAINT ODOR.  
Percent Volatiles by Volume:50.0

## Stability

Stability Indicator/Materials to Avoid:YES  
REACTIVE AMINES  
Stability Condition to Avoid:FIRE,FLAME,WELDING OR SMIKING IN AREA.  
Hazardous Decomposition Products:CHLORINE AT TEMPERATURES OVER 400F.  
Conditions to Avoid Polymerization:MIXING W/STRONG REACTIVE AMINES;BREATHING FUMES.

## Disposal

Waste Disposal Methods:DO NOT SEND TO ANY DUMP UNLESS DUMP OPERATORS ARE AWARE IT IS FLAMMABLE,EVEN THEN IT SHOULD BE SENT ONLY TO AN APPROVED DUMP AREA.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.