

HULTSCRETE

MSDS Number

BBCJQ

National Stock Number

8040-00D000139

Product Name

HULTSCRETE

Manufacturer

HULTSCRETE CO

Product Identification

Product ID:HULTSCRETE

MSDS Date:01/01/1985

FSC:8040

NIIN:00D000139

MSDS Number: BBCJQ

Responsible Party

HULTSCRETE CO.

Emergency Phone: 704-376-8484

Cage: DO951

Contractor

HULTSCRETE CO.

WADESBORO, NC 28170

US

704-272-7641

Cage: DO951

Ingredients

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 7.0%.

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

METHYL ISOBUTYL KETONE (SARA III)

CAS: 108-10-1

RTECS: SA9275000

Fraction By Weight: 34.0%

OSHA PEL100 PPM/75 STEL

ACGIH TLV: 50 PPM/75 STEL; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000

Fraction By Weight: 34.0%

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

NON HAZARDOUS INGREDIENTS

Fraction By Weight: 25.0%

ACGIH TLV: UNKNOWN.

Hazards

Effects of Overexposure:TEMPORARY DAMAGE TO LUNGS-MAY CAUSE PERMANENT DAMAGE TO LUNGS,EVEN DEATH,DRUNKNESS W/O SPRAY MASKS.

First Aid

First Aid:CLOTHES:REMOVE AND WASH IMMEDIATELY. SKIN:WASH IMMED.WITH SOLVENT AND THEN SOAP & WATER. EYES:FLUSH WITH WATER UNTIL PAIN CEASES & SEE DR. IMMED.

Fire Fighting

Flash Point:53F

Lower Limits:1.0

Upper Limits:2.0.

Extinguishing Media:FOAM,CO*2 OR DRY CHEM.,WATER SPRAY INEFFECTIVE.

Fire Fighting Procedures:FIREMEN SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:VAPORS ARE HIGHLY MOBILE & MAY TRAVEL A CONSIDERABLE DISTANCE TO SOURCE OF IGNITION & BACK.

Accidental Release

Spill Release Procedures:WIPE UP IMMED.WITH DRY RAGS OR POUR SAND ON SPILL.

Handling

Handling and Storage Precautions:KEEP IN COOL PLACE.KEEP OUT OF DIRECT SUNLIGHT OR HEAT.LEAKING CONTAINERS MUST BE REMOVED TO SAFE PLACE.

Other Precautions:FOR PROFESSIONAL USE ONLY.KEEP OUT OF REACH OF CHILDREN.

Exposure Controls

Respiratory Protection:WEAR MASKS WHEN SPRAYING;OTHER TIMES,SELF-CONTAINED BREATHG APPARAT.

Ventilation:LOCAL EXHAUST IS RECOMMENDED,SO VAPORS DO NOT EXC.400 PPM

Eye Protection:SAFETY GOGGLES

Supplemental Safety and Health

ITEM IS MADEUP OF 2 PARTS,A & B IS PART OF A KIT. PART B IS COVERED UNDER THIS NSN. PART A IS COVERED SEPARATELY UNDER SAME NSN.

KEY1:F3.

Chemical Properties

HCC:F3

Boiling Pt:B.P. Text:177F-292F.

Spec Gravity:0.96.

Evaporation Rate & Reference:Solubility in Water:APPRECIABLE

Appearance and Odor:LIQUID,PAINT ODOR.

Percent Volatiles by Volume:75.0

Stability

Stability Indicator/Materials to Avoid: YES
REACTIVE EPOXIES.
Stability Condition to Avoid: FIRE, FLAME, WELDING OR SMOKING IN AREA.
Hazardous Decomposition Products: NONE
Conditions to Avoid Polymerization: BREATHING FUMES.

Disposal

Waste Disposal Methods: DO NOT SEND TO DUMP UNLESS DUMP OPERATOR IS
AWARE IT IS INFLAMMABLE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.