



VERSATEC TONER PREMIX TYPE M.

MSDS Number

BBCJR

National Stock Number

6850-00D000140

Product Name

VERSATEC TONER PREMIX TYPE M.

Manufacturer

PHILIP A HUNT CHEM CORP

Product Identification

Product ID:VERSATEC TONER PREMIX TYPE M.

MSDS Date:01/01/1985

FSC:6850

NIIN:00D000140

MSDS Number: BBCJR

Responsible Party

PHILIP A. HUNT CHEM.CORP.

PALISADES PARK , NJ 07650

Emergency Phone: 201-944-4000

Info Phone: 201-944-4000

Cage: DO532

Contractor

PHILIP A. HUNT CHEM CORP

988

PALISADES PARK, NJ 07650

US

800-OLIN-911

Cage: DO532

Ingredients

MIXED ISODECANES

Fraction By Weight: 99.0%

ACGIH TLV: 400 PPM

Hazards

Effects of Overexposure:HEADACHE,NAUSEA,MILD DEPRESSION &/OR RESPIRATOR IRRITATION,UP SET STOMACH;POSSIBLE IRRITATION,NAUSEA

First Aid

First Aid:INHAL:MOVE TO FRESH AIR. INGEST:DO NOT INDUCE VOMIT.CALL DR. IMMEDIATELY. EYES:FLUSH WELL WITH CLEAN WARM WATER FOR 15 MIN.IF IRRITATION PERSISTS CALL DR.

Fire Fighting

Flash Point:102-107F TCC.

Lower Limits:0.8.

Upper Limits:7.0.

Extinguishing Media:FOAM-TYPE EXTINGUISHERS-SUPERIOR TO CO*2 EXTINGUISHERS.

Fire Fighting Procedures:AVOID WATER-IT TENDS TO SPREAD HYDROCARBON



SOLVENT FIRES.
Unusual Fire/Explosion Hazard:NONE

Accidental Release

Spill Release Procedures:REMOVE IGNITION SOURCES.IF AMT IS SMALL(UNDER 1 PT.) ALLOW TO EVAPORATE-INCREASING AIR CIRCULATION IF POSSIBLE-AND AVOID ANY SPARKS OR OPEN FLAMES.IF LARGE AMT,TRY TO CONTAIN & SOP UP INTO A CONTAINER WHICH CAN BE CLOSED.

Handling

Handling and Storage Precautions:KEEP CONTAINERS CLOSED.AVOID STROAGE NEAR HEAT,STRONG LIGHT (IF CONTAINERS ARE CLEAR),SPARKS,OR OPEN FLAME.

Other Precautions:AVOID USE IN A SMALL CLOSED ROOM OR CONFINED AREA WITH POOR AIR CIRCULATION.WASH SKIN WITH SOAP & WATER AFTER CONTACT.

Exposure Controls

Ventilation:LOCAL EXHAUST & MECHANICAL IS RECOMMENDED
Supplemental Safety and Health

Chemical Properties

HCC:F4

Boiling Pt:B.P. Text:320-350F.

Vapor Pres:2.0

Vapor Density:5.0.

Spec Gravity:0.747.

Evaporation Rate & Reference:0.45,BUTYL ACETATE

Solubility in Water:0.01.

Appearance and Odor:BLACK,MOBILE LIQUID,FAINT HYDROCARBON ODOR.

Percent Volatiles by Volume:99+.

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDANT LIKE CHROMIC ACID,LIQUID CHLORINE,CONC.OXYGEN

Hazardous Decomposition Products:NONE

Disposal

Waste Disposal Methods:LARGE CONTAINERS OF WASTE MUST BE HANDLED BY PERSONS OR FIRMS WITH FACILITIES FOR DISPOSAL; FOR EXAMPLE,CONTROLLED BURNING.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.