

VERSATEC TONER PREMIX TYPE D.

MSDS Number

BBCJS

National Stock Number

6850-00D000141

Product Name

VERSATEC TONER PREMIX TYPE D.

Manufacturer

PHILIP A HUNT CHEM CORP

Product Identification

Product ID:VERSATEC TONER PREMIX TYPE D.

MSDS Date:01/01/1985

FSC:6850

NIIN:00D000141

MSDS Number: BBCJS

Responsible Party

PHILIP A.HUNT CHEM.CORP.

PALISADES PARK , NJ 07650

Emergency Phone: 201-944-4000

Info Phone: 201-944-4000

Cage: DO952

Contractor

PHILIP A.HUNT CHEM.CORP.

988

PALISADES PARK, NJ 07650

US

201-944-4000

Cage: DO952

Ingredients

MIXED ISODECANES

Fraction By Weight: 99.0%

ACGIH TLV: 400 PPM

CARBON BLACK

CAS: 1333-86-4

RTECS: FF5800000

Fraction By Weight: 0.50%

OSHA PEL3.5 MG/M3

ACGIH TLV: 3.5 MG/M3; 9192

Hazards

Effects of Overexposure:HEADACHE,NAUSEA;FOR MORE SEVERE EXPOSURE:MILD DEPRESSION,RESP.IRRITATION,UPSET STOMACH,NAUSEA,IRRIT.

First Aid

First Aid:INHAL:MOVE TO FRESH AIR. INGEST:DO NOT INDUCE VOMIT.CALL DR.IMMEDIATELY. EYES:FLUSH WITH WARM WATER FOR 15 MIN. IF IRRITATION PERSISTS CALL DR.

Fire Fighting

Flash Point:102-107F TCC.
Lower Limits:0.80
Upper Limits:7.0.
Extinguishing Media:FOAM-TYPE EXTINGUISHERS-SUPERIOR TO CO*2 EXTINGUISHERS.
Fire Fighting Procedures:AVOID WATER-IT TENDS TO SPREAD HYDROCARBON SOLVENT FIRES.
Unusual Fire/Explosion Hazard:NONE

Accidental Release

Spill Release Procedures:REMOVE IGNITION SOURCES,IF AMT IS SMALL(UNDER 1 PT.)ALLOW TO EVAPORATE-INCREASING AIR CIRCULATION IF POSSIBLE.AND AVOID ANY SPARKS OR OPEN FLAMES.IF AMT.IS LARGE,TRY TO CONTAIN & SOP UP INTO A CONTAIN ER WHICH CAN BE CLOSED.

Handling

Handling and Storage Precautions:KEP CONTAINERS CLOSED.AVOID STORAGE NEAR HEAT,STRONG LIGHT (IF CONTAINERS ARE CLEAR),SPARKS,OR OPEN FLAME.
Other Precautions:AVOID USE IN A SMALL CLOSED ROOM OR CONFINED AREA WITH POOR AIR CIRCULATION.WASH SKIN WITH SOAP & WATER AFTER CONTACT.

Exposure Controls

Ventilation:LOCAL EXHAUST & MECHANICAL IS RECOMMENDED
Supplemental Safety and Health

Chemical Properties

HCC:F4
Boiling Pt:B.P. Text:320-350F.
Vapor Pres:2.0
Vapor Density:5.0.
Spec Gravity:0.747.
Evaporation Rate & Reference:0.45,BUTYL ACETATE
Solubility in Water:0.01
Appearance and Odor:BLACK,MOBILE LIQUID;FAINT HYDROCARBON ODOR.
Percent Volatiles by Volume:99+.

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDANT LIKE CHROMIC ACID,LIQUID CHLORINE & CONC.O*2.
Hazardous Decomposition Products:NONE

Disposal

Waste Disposal Methods:LARGE CONTAINERS OF WASTE MUST BE HANDLED BY PERSONS OR FIRMS WITH FACILITIES FOR DISPOSAL;FOR EXAMPLE,CONTROLLED BURNING.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.