

## **U.P.I.-UNIFAX II DISPERSANT(ELECTROSTATIC)**

### **MSDS Number**

BBCJT

### **National Stock Number**

6750-00D000142

### **Product Name**

U.P.I.-UNIFAX II DISPERSANT(ELECTROSTATIC)

### **Manufacturer**

PHILIP A HUNT CHEMICAL CO

### **Product Identification**

Product ID:U.P.I.-UNIFAX II DISPERSANT(ELECTROSTATIC)

MSDS Date:01/01/1985

FSC:6750

NIIN:00D000142

MSDS Number: BBCJT

### **Responsible Party**

PHILIP A. HUNT CHEMICAL CO.

PALISADES PARK , NJ 07650

Emergency Phone: 201-944-4000

Info Phone: 201-944-4000

Cage: DO532

### **Contractor**

PHILIP A. HUNT CHEM CORP

988

PALISADES PARK, NJ 07650

US

800-OLIN-911

Cage: DO532

### **Ingredients**

MIXED ISODECANES,

Fraction By Weight: 100%

ACGIH TLV: 300 PPM

### **Hazards**

Effects of Overexposure:HEADACHE,NAUSEA,MILD DEPRESSION &/OR  
RESPIRATORY IRRITATION,UPSET STOMACH,POSSIBLE IRRITATION.

### **First Aid**

First Aid:INHAL:MOVE TO FRESH AIR.INGEST:CALL DR IMMED.DO NOT INDUCE  
VOMIT.EYES:FLUSH WITH WARM WATER FOR 15 MIN.IF IRRITATION  
PERSISTS,CALL DR.

### **Fire Fighting**

Flash Point:102-107F TCC

Lower Limits:1.0.

Upper Limits:7.0.

Extinguishing Media:FOAM-TYPE EXTINGUISHERS-SUPERIOR TO CO\*2  
EXTINGUISHERS.

Fire Fighting Procedures:AVOID WATER-IT TENDS TO SPREAD HYDROCARBON

SOLVENTFIRES.

Unusual Fire/Explosion Hazard:NONE

## Accidental Release

Spill Release Procedures:IF AMT.IS SMALL(UNDER 1 PT)ALLOW TO EVAPORATE.INCREASING AIR CIRCULATION IF POSSIBLE.AVOID SPARKS AND FLAMES. IF AMT.IS LARGE,TRY TO CONTAIN & SOP UP INTO A CONTAINER WHICH CAN BE CLOSED.AVOID BREATHI NG VAPORS.

## Handling

Handling and Storage Precautions:AVOID STORAGE NEAR HEAT,SPARKS,OR OPEN FLAME.

Other Precautions:AVOID USE IN A SMALL CLOSED ROOM OR CONFINED AREA WITH POOR AIR CIRCULATION.WASH WITH SOAP & WATER THE SKIN AFTER CONTACT.

## Exposure Controls

Ventilation:LOCAL EXHAUST & MECHANICAL IS RECOMMENDED

Supplemental Safety and Health

ITEM IS DILUENT FOR LIQUID ELECTROSTATICS OFFICE COPIER TONER.

## Chemical Properties

HCC:F4

Boiling Pt:B.P. Text:320-350F.

Vapor Pres:2.0

Vapor Density:5.05

Spec Gravity:0.748.

Solubility in Water:0.01%

Appearance and Odor:CLEAR,MOBILE,COLORLESS LIQUID;FAINT HYDROCARBON.

Percent Volatiles by Volume:100.

## Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDANTS LIKE CHROMIC ACID,LIQUID CHLORINE,CONC.OXYGN

Hazardous Decomposition Products:NONE

## Disposal

Waste Disposal Methods:LARGE CONTAINERS OF WASTE MUST BE HANDLED BY PERSONS OR FIRMS WITH FACILITIES FOR DISPOSAL (E.G.CONTROLLED BURNING).DO NOT DISCHARGE INTO SEWER,STREAMS OR WATERWAYS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.