



---

## **SOLVENT, FILM ADHERENT**

### **MSDS Number**

BBCPM

### **National Stock Number**

6850-00D000383

### **Product Name**

SOLVENT, FILM ADHERENT

### **Manufacturer**

NAZ DAR COMPANY

### **Product Identification**

Product ID: SOLVENT, FILM ADHERENT

MSDS Date: 01/01/1985

FSC: 6850

NIIN: 00D000383

MSDS Number: BBCPM

### **Responsible Party**

NAZ DAR COMPANY

1087 N NORTH BRANCH ST

CHICAGO, IL 60622-4234

US

Cage: D0971

### **Contractor**

NAZDAR COMPANY

CHICAGO, IL 60622-4292

US

312-943-8338; 800-736-7636

Cage: 76708

### **Ingredients**

ACETONE (SARA III)

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 100%.

OSHA PEL 1000PPM

ACGIH TLV: 750PPM/1000STEL; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

### **Hazards**

Effects of Overexposure: IRRITATES EYES & MUCOUS MEMBRANES, ANESTHETIC, HEADACHE, DIZZINESS STAGGERING GAIT, CONFUSION, COMA.

### **First Aid**

First Aid: INHALATION: REMOVE TO FRESH AIR & CALL A MD. ARTIFICIAL RESPIRATION IF BREATHING IS STOPPED. INGESTION: INDUCE VOMITING & GET MEDICAL HELP PROMPTLY. SKIN: WASH WELL WITH WATER. EYES: FLUSH WITH WATER IMMEDIATELY FOR AT LEAST 15 MINS. CONSULT DR.



## Fire Fighting

Flash Point:0F TCC  
Lower Limits:2.6  
Upper Limits:12.8  
Extinguishing Media:CO\*2,DRY CHEMICAL OR FOAM  
Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE,KEEP FIRE CONTAINERS COOL.  
Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED.ISOLATE FROM HEAT,ELECTRICAL EQUIPMENT,SPARKS & OPEN FLAME.

## Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION(FLAMES,HOT SURFACES & ELECTRICAL,STATIC OR FRICTIONAL SPARKS).AVOID BREATHING VAPORS,VENTILATE AREA.REMOVE WITH INERT ABSORBENT & NON-SPARKING TOOLS.

## Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LARGE QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS II FLAMMABLE LIQUIDS  
Other Precautions:DO NOT TAKE INTERNALLY.CONTAINERS SHOULD BE GROUNDED WHEN POURING.AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES.DO NOT FLAME CUT,BRAZE OR WELD WITHOUT U.S.BUREAU MINES APPD RESPIR,VENTL.

## Exposure Controls

Respiratory Protection:SELF-CONTAINED BREATHING APPARATUS;BUREAU MINES MECH.FILTER RESPIR.  
Ventilation:GENERAL DILUTION OR LOCAL EXHAUST VENTILATION  
Protective Gloves:RUBBER  
Eye Protection:SAFETY GOGGLES.  
Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT WITH CONTAMINATED CLOTHING  
Supplemental Safety and Health  
THE ITEM MANUFACTURERS CODE IDENTIFICATION IS 2137.UNUSAL FIRE & EXPLOSION HAZARDS(CONTD):CLOSED CONTAINER MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.DO NOT APPLY TO HOT SURFACES.

## Chemical Properties

HCC:F3  
Boiling Pt:B.P. Text:134F  
Vapor Pres:180  
Vapor Density:2.0  
Spec Gravity:0.791  
Evaporation Rate & Reference:Solubility in Water:APPRECIABLE  
Appearance and Odor:COLORLESS,VOLATILE LIQUID WITH SWEETISH ODOR.  
Percent Volatiles by Volume:100.

## Stability

Stability Indicator/Materials to Avoid:YES  
OXIDIZABLE MATERIAL,ORGANIC PEROXIDES,RADIOACTIVE MATL.  
Hazardous Decomposition Products:HAZARDOUS FUMES-MAY CONTAIN CO & OXIDES OF NITROGEN.

## Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL,STATE & FEDERAL REGULATIONS DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

